APPENDIX F-4
MAINTENANCE CHECKLIST

SPERRY & LINIVAC	
MAINTENAN	ICE CHECK LIST
PLT. NO. MAIL STATION	DATE
ORGANIZATION NAME	
MAINTENANCE DISCREPANCY	
	•
•	•
REMARKS:	<u>-</u>
•	
	,
	be .
SIGNATURE	DATE COMPLETED
UD1-2608	

APPENDIX F-3

PAGE 144



ECP	<del></del>	***************************************	REV
	3700	)9-1	F
PAGE			-
	1	OF	5

· · · · · · · · · · · · · · · · · · ·							
DETAIL DESCRIPTION Chem	ical & Hazar	dous	Material	HEF	40 CFR	117,	263, 264
Emergency Response	Procedure -	Disk	#L-ac-2			265,	761
ENGINEER	•	DATE	(APPBQVAL	100	4		DATE
D. E. MacDonald	The state of the s		10 bg 2	v /III	Ila.		12/9/85
	, , , , , , , , , , , , , , , , , , ,		7	7			77

#### 1.0 GENERAL

This procedure explains how to handle a hazardous material emergency. In response to an emergency involving hazardous materials an authorized hazardous material coordinator must be contacted. This procedure includes a list of personnel available, chemical handling data and forms to help the coordinator to handle an emergency as efficiently as possible. Use this procedure in the event of a hazardous material emergency for the safety of the environment, health of our personnel and operating capability of Sperry DPG facilities.

#### 2.0 HAZARDOUS MATERIAL EMERGENCY

A hazardous material emergency exists when a spill or occurance involving any hazardous material happens outside of the plants, including all bulk chemical and fuel oil deliveries. These must be reported to the Environmental Management Department. Inside the plant, any occurance involving a material with a hazard code rating of 2 or above or one gallon or more should be treated as an emergency. The hazard code is marked on the CSD diamond hazard code label attached to the container. If a small spill of less than 1 gallon and the material doesn't have any of the hazard code ratings of 2 or higher, refer to ECP 37015 for clean up instructions.

#### 3.0 PERSONNEL RESOURCES

- 3.1 Hazardous Material Emergency Coordinator Personnel that are trained and responsible for this position are listed in Appendix I, Part A.
- 3.2 Hazardous Material Emergency Team Team members consist of personnel from Environmental Management, listed in Appendix I, Part B.
- 3.3 Hazardous Material Emergency Support Groups These groups will help support the coordinator and team as needed in an emergency. The group includes: personnel from Occupational Health Programs Department, the Emergency Brigade, Security Guards, Production and Process Engineers, Communication Department, Facility Maintenance, and independent spill contractor. Personnel to contact in these groups are listed in Appendix I, Part C, and Appendix II.



ECP			REV
	3700	09-1	F
PAGE	O THE STATE OF THE		
	2	OF	5

	8 C 40/2 PRESC 11 15	1 mgs mas mas mas 1 h	Appendix.			
DETAIL DESCRIPTION Chemical & Haza:	rdous Mate	erial	REF	40 CFR	117, 26	3, 264
Emergency Response Procedure					265, 76.	<u> </u>
ENGINEER	DATE	APPROVAL			D	ATE
D. E. MacDonald					1	

#### 4.0 PERSONNEL RESPONSIBILITIES

- 4.1 Hazardous Material Emergency Coordinator The coordinator is responsible for implementing this procedure and to coordinate all hazardous material emergencies. All personnel listed as a coordinator are knowledgeable of all hazardous materials, processes, equipment, and facility layout. They have the authority to commit an independent spill contractor to help in a clean up.
- 4.2 Hazardous Material Emergency Team Members
  - 4.2.1 Environmental Management Members of the team from Environmental Management are responsible for assessing the nature of the emergency, then containing and cleaning up. Environmental Management is also responsible for keeping this procedure updated and keeping all anticipated equipment needed clean and in operating condition.
- 4.3 Occupation Health Occupational Health is responsible for the safety aspect of an emergency, material handling, evacuation and approval of re-entry of areas by personnel.
- 4.4 Emergency Brigade Brigade nembers will report emergencies directly to Security Guards (Ext. 3000), help keep area clear of personnel and help in evacuation if needed.
- 4.5 Security Guards Guards will report a hazardous material emergency to a Hazardous Material Emergency coordinator immediately using Appendix I, Part A. Guards will help with keeping personnel clear, evacuation, communications and back up support.
- 4.6 Production/Process Engineers Engineers will consult with coordinator to identify nature of emergency and provide additional information about the material that is required for safe handling of the material.
- 4.7 Facility Maintenance Provide help in making the necessary repairs, back-up support, help clean up, and movement of equipment as directed by the coordinators.
- 4.8 Communication Department All communications to outside news media will be coordinated by a representative of the Communication Department.
- 4.9 Independent Spill Contractor An open Purchase Order for services of an Independent spill contractor to help in a clean-up is available.

SC1-3938 Pay 4 341



ECP			REV
	3700	09-1	F
PAGE		***************************************	
1	3	OF	.5

	0 0 1 %		e wase		
DETAIL DESCRIPTION Chemical & Haza	ardous	Material	REF	40 CFR 117,	263, 264
Emergency Response Procedure				265,	761
ENGINEER	DATE	APPROVAL		2-00	DATE
D. E. MacDonald					

- 5.0 Procedure in the event of a Hazardous Material Emergency on Sperry Property.
  - 5.1 In the event of a hazardous material emergency, the personnel or the Emergency Brigade member in the area dial Ext. 3000 to report to the guards.
    - 1. Name of person reporting.
    - 2. Location of the emergency.
    - 3. Nature of the emergency.
  - 5.2 The guards must page the Hazardous Material Emergency Coordinator and team by paging the Environmental Management common pager number (#555).
  - 5.3 The Hazardous Material Emergency team will organize a team effort to handle the hazardous material incident.
  - 5.4 At the spill location the Hazardous Material Emergency Coordinator will do everything possible to minimize the hazards to human health, environment and property.
  - 5.5 The Hazardous Material Emergency Coordinator must immediately identify the character, exact source, amount and extent of any released hazardous material. This information is then communicated to all other team members.
  - 5.6 The Hazardous Material Emergency Coordinator must determine the possible hazards to human health or the environment and determine the course of action to take.
  - 5.7 Evacuate personnel whose health is endangered. All unnecessary personnel must be evacuated from the area. Guards and Emergency Brigade will assist in evacuating and securing area.
  - 5.8 The team will contain the emergency in an area as small as possible, clean up and dispose of the hazardous material.
- 6.0 Procedure after a Hazardous Material Incident.
  - 6.1 Occupational Health is responsible for determining when personnel are allowed back into the work areas after an evacuation.
    - 6.1.1 Prepare air sampling equipment.
    - 6.1.2 Enter area and measure air concentration for level of contaminant.

SC1-3938 Pev 4-841

. .



ECP		***************************************	REV
	370	09-1	F
PAGE			
	4	OF	5

		( A A A MAN (A) ( ) (	esares		
DETAIL DESCRIPTION Chemical & Hazar	rdous Mate	erial	REF 40	CFR 117, 2	63, 264
Emergency Response Procedure				265, 7	61
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald		ļ			ļ

- 6.2 Hazardous Material Emergency Coordinator is responsible for notifing appropriate government agencies of a spill.
- 6.3 Hazardous Material Emergency Coordinator is responsible for complete clean up of the area and emergency equipment. This includes calling the independent contractor if the incident requires this action.
- 6.4 Hazardous Material Emergency Coordinator must prepare a written report of the incident as required by 40 CFR Part 264, Subpart D 264.56 (j).
- 7.0 Hazardous Chemical Incident Off Univac Property
  - 7.1 The Security Guards or Telephone Operators will normally be notified of an emergency with regard to a hazardous material shipment of Sperry Chemicals.
  - 7.2 A Hazardous Material Emergency Coordinator is notified immediately by the Security Guards.
  - 7.3 The Sperry Hazardous Material Emergency Coordinator will contact the transporting company, if appropriate, to determine the nature of the incident.
  - 7.4 The Sperry Hazardous Material Emergency Coordinator will ensure that proper government agencies are notified.
  - 7.5 The Sperry Hazardous Material Emergency Coordinator will form a team which can best respond to the incident if required.
  - 7.6 The Sperry Hazardous Material Emergency Coordinator will make arrangements to go to the site of the emergency if needed.
  - 7.7 The team will proceed to the site to advise and supervise containment and cleanup.
  - 7.8 The coordinator will be responsible for providing the EPA Regional Administrator with a written report.

### 8.0 Training or Personnel

- 8.1 All new Environmental Management personnel must receive Hazardous Chemical Emergency response training according to 40 CFR, Part 264, Subpart A, 264.16, within six months after starting work and must not work unsupervised until after receiving the training.
- 8.2 All Emergency Response Team Members must be trained in this procedure and review emergency response procedures at least yearly.

SC1-3938 (Rev 4/84)



ECP			REV
	370	09-1	F
PAGE		- Lunuoun	
	5	OF	5

FNVIR	NNC	FNTA	$I \subset$	ONTROL	<b>PROCEDURE</b>
# W W 1 1 3 C	~13141		\L\	CHINCL	FINALLUIL

DETAIL DESCRIPTION Chemical & Hazardous Material REF 40 CFR 117, 263, 264

Emergency Response Procedure 265, 761

ENGINEER DATE APPROVAL DATE

D. E. MacDonald

8.3 All training must be documented and kept on file according to 40 CFR, Part 264, Subpart A, 264.16. See ECP 37016 for outline of training.



ECP			RE∨
	3700	09-2	F
PAGE			
	1	OF	7

#### 1.0 Emergency Response Equipment Inspection

Use this as a guide to inventory and maintain all equipment that is necessary in a chemical and hazardous material emergency response. Use the monthly checklist at the beginning of each month. Discrepancies and remedial action taken will be noted on a remediable action log. A copy of this procedure and the inspection log must be maintained at each facility.

#### 2.0 Shepard Road Facility

#### 2.1 Safety Equipment Cabinet

Make sure all hand tools are present and in proper working condition. Check that all hard hats are accounted for with face shields mounted, clean and free of abrasions, and scratches, enough to allow good vision. Take inventory on protective chemical suits, making sure each piece of the suit is present and in good shape. Inventory the plug rugs. Inspect the rope for any weaknesses, that it is clear and both metal clips work. The electrical extension cords should not have any abrasions, be clean, and male and female connections are in proper condition. The goggles and safety glasses should be clean and without scratches or abrasions. Take inventory of squeege's, rubber gloves, vacuum tools, and shovel, making sure that they are in good operating condition.

#### 2.2 Emergency Spill Cart

The major concern for the lab spill cart is the inventory of items. The gloves and coveralls are one time use items, so if they are dirty, replace them. Safety glasses should not have any abrasions and be clean.

#### 2.3 Vacuum Cleaner

Make sure vacuum cleaner functions properly by plugging it in and running the motor. The tank and head should be clean. When stored the vacuum head should be offset from tank in order to allow ventilation of the tank, otherwise, moisture, over a long period of time can damage motor parts.

### 2.4 Emergency Pump

1 1/2" Sandpiper Pump on wheels. Hook up sandpiper pump with a suction and discharge hose, also supply house air to run a test by pumping out a five gallon pail of water to check proper function of pump.

SC1-3938 Pay 4 34)

Revision E Page 150



ECP	· · · · · · · · · · · · · · · · · · ·	S-2	REV	aye and a second
	3700	09-2	F	
PAGE			· · · · · · · · · · · · · · · · · · ·	
i	2	OF	7	

	all the Page 8 4 1				
DETAIL DESCRIPTION Chemical & Hazar	dous Mate	rial	REF 40	CFR 117, 2	.63, 264
Emergency Response Procedure				265, 7	61
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald	1				}

2.5 Safety Cabinet for 1 1/2" Hoses

Check for holes, dangerous looking abrasions, or weakness of hose. Also check gaskets and fittings at each end of hose for wear or improper function.

- 2.6 Scott Breathing Apparatus, Air-Pak 2.2 and the SKA-PAK emergency escape unit.
  - 1. The Air-Pak 2.2 Air Cylinders shall be fully charged according to the manufacturer's instructions. It shall also be determined that the regulator warning devices functions properly. Respirator inspections shall include a check of the tightness of the connections and the condition of the face-piece, head bands, valves, and connecting tubes. Rubber or elastic parts shall be inspected for pliability and signs of deterioration. Stretching and manipulating rubber or elastomer parts with a massaging action will keep them pliable and flexible and prevent them from distorting during storage.
  - 2. The SKA-PAK emergency escape unit only differs in inspection from the Air Pak 2.2, when it comes to the air supply system and regulator warning device. There is no regulator warning device. The supply of air has to meet the requirements of 2216 P.S.I. of Med-Air Class D in the five minute air cylinder. The two 180/lb cylinders require tags on both cylinder necks that read full, partially full, and empty. One cylinder should be full at all times, which is 2200 P.S.I. The other cylinder can be partially full, but must be replace when empty. Air supply hoses must be pressurized and inspected for leaks and bad fittings. Check that tank regulators are set at 125 P.S.I.

#### 2.7 Emergency Spill Trailer

Check to insure that all of the equipment listed in Appendix III, F is on hand, clean and serviceable. Check the operation of the gas operated air compressor to insure that it operates properly. Check the supply of gasoline for the compressor. Check the operation of the turn lights, the brake, parking and tail lights by hooking it into one of the Security trucks trailer outlet. Replace any equipment that is missing, make repairs as necessary.

#### 2.8 Emergency Spill Drums

Check the location of the drums per Appendix III, G. Insure that they are in good condition. Check the quantity of absorbent material.

Replace the drums if defective. Replenish the supply of absorbent material if needed.



ECP	_	II GALLESTO	REV
	370	09-2	F
PAGE			.,
	3	OF	7

DETAIL DESCRIPTION Chemical & Haza	rdous Mat	erial RE	f 40 CFR	117, 263, 264
Emergency Response Procedure			•	265, 761
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	1			

### 3.0 Sperry Park

3.1 Safety Equipment Cabinets

Make sure all hand tools are present and in proper working condition. Check that all hard hats are accounted for with face shields mounted clear and free of abrasions and scratches, enough to allow good vision. Take inventory on protective chemical suits, making sure each piece of the suit is present and in good shape. The electrical extension cords should not have any abrasions, be clean, and the male and female connections are in proper condition. The goggles and safety glasses should be clean and without scratches or abrasions. Take inventory of squeege's, rubber gloves, shovels, 20 ft. rope, throw away coveralls, making sure that all items are in operating and functional condition.

3.2 Emergency Spill Cart

Refer to 2.2 for inspection requirements.

3.3 Vacuum Cleaner

Refer to 2.3 for inspection requirements.

3.4 Emergency Pump

Refer to 2.4 for inspection requirements.

3.5 Scott Breathing Apparatus

Refer to 2.6 for inspection requirements.

3.6 Emergency Spill Drums

Refer to 2.8 for inspection requirements.

#### 4.0 Midway

4.1 Emergency Spill Drums

Refer to 2.8 for inspection requirements.

SC1-3938 Ret 4 641



37009-2 F
PAGE
4 OF 7

EN'	VIRONMENTAL CONT	ROL	PRO	CEDI	JRE					
	DESCRIPTION Chemical & Hazar	dous	Materi	al	REF	4	O CFR	117, 2 265, 7		4
ENGINI	gency Response Procedure	DATE	АР	PROVAL			······································		DATE	
D. E	. MacDonald			<del>and the state of </del>						
Shep	ard Road Facility Checklist		4						S-4	<b></b>
l.	Safety Equipment Cabinet-Shepard Road						7. 73	<u>-</u>		
2.	Emergency Spill Cart Shepard Road									
3.	Vacuum Cleaner Shepard Road					_				
4.	Emergency Pump Shepard Road									
5.	Safety Cabinet for Hose-Shepard Road									
6.	Scott Breathing Apparatus Shepard Road		*							
	Air-Pak 2.2									
	SKA-PAK Emergency Escape Unit									
7.	Emergency Spill Trailer									
:	Equipment Inventory							-		_
	Compressor Operation									
	Gasoline Supply							ather and a second second		
	Light Operation									
8.	Emergency Spill Drums Shepard Road		}							
	Chemical Dock									
	Tank Farm									
•	Boiler Room									
÷	P.C.B. Capacitors									

### G-2 ARRANGEMENTS WITH LOCAL FIRE AND POLICE DEPARTMENTS

Appendix G-2 (Page 238) are copies of the letters of transmittal when we submitted the contingency plan to the City of Eagan Fire Department, the City of Eagan Police Department, and Divine Redeemer Hospital.

Representatives of the Eagan Fire and Police departments tour each of the facilities to refamiliarize them on the layout and location of hazardous material storage areas. The city of Eagan Fire and Police Departments are the only Fire and Police Departments which would be contacted by us in an emergency.

The most recent tour was on February 16, 1984 with the Eagan fire marshall. Areas reviewed included chemical storage areas, laboratories, electrical equipment with capacitors and safety equipment locations. We also reviewed the contingency plan, and discussed the contracts we have with outside spill control contractors.



ECP | REV | STORY | ST

ENVIRONMENTAL CONTROL PROCEDURE									
	DESCRIPTION Chemical & Haza	rdous Ma	aterial		REF	40		17, 26 65, 76	3, 264
ENGINE	gency Response Procedure	DATE	APPRO	VAL			4		ATE
D.E.	MacDonald	<u> </u>							
Sper	ry Park Facility Checklist								
1.	Safety Equipment Cabinet-Sperry Park								
2.	Emergency Spill Card Sperry Park						e de primero de la companya de la c		and the same of th
3.	Vacuum Cleaner Sperry Park								**************************************
4.	Emergency Pump Sperry Park								
5.	Scott Breathing Apparatus Sperry Park						1		
	Air Pak 2.2				-				(Control of the Control of the Contr
	SKA-PAK Emergency Escape Unit								
6.	Emergency Spill Drums Sperry Park								
1	Boiler Room					4VIIII			
	P.C.B. Capacitors								
!	Cooling Towers								
<u> </u>  -	Chemical Fill Station								
:	Move Crew Dock								

Spills occurring in normal starage areas are contained by trenches protecting the room entrances. These trenches drain to separate underground containment tanks for treatment. Spills occurring outside the normal storage areas are contained by the use of clay absorbant materials which are stored in emergency spill drums (drum locations are listed on Page 161).



37009-2 F
PAGE
6 OF 7

							0	O1	- 1	
EWV	VIRONMENTAL CONT	ROL	PR(	OED	UR					
DETAIL	DESCRIPTION Chemical & Haza	rdous	Mater	ial		REF	40 CFF	117,	263,	264
	zency Response Procedure				ļ			265,	-	
NGINE		DATE	م	PPROVA			-,		DATE	
D. E.	MacDonald									
Midwa	ay Facility Checklist									
1.	Emergency Spill Drums Minnehaha Avenue		September 1997							
	P.C.B. Capacitors		7,777			- 11 - 02-0899				
	Tank Farm									
	Boiler Room									
	Maintenance Oil Storage									
	Flammable Storage Room									
							<u> </u>	<b></b>		-



37009-2 F
PAGE
7 OF 7

	ENVIRONMENTAL CONTROL PROCEDURE								
	L DESCRIPTION Chemical & Haza gency Response Procedure	rdous	Material	REF	40 CFF	2 117, 263, 264 265, 761			
ENGIN	EER	DATE	APPROVAL			265, 761 DATE			
<u> </u>	D. E. MacDonald  REMEDIAL ACTION LOG								
		KEEED.							
NO.	PROBLEM OBSERVATION	INI	REMEDIA ACTION		INI	DATE			
1.									
!									
2.	<u></u>								
:									
3.									
4.				_					
i 	,	•							
5.			THE STATE OF THE S						
6.									
••									
7.				construction (in the construction of the const					
				· ····································		****			
8.		:							
9.									
				town or the state of the state		70-kan markan marka			
10.									
11.			4949	wo with House He Townson		httis:#VDania			
12.			4.						
13.									
14.			The state of the s						
-	<u> </u>	L		,	<u> </u>	<u></u>			



ECP		TOTAL SOUND	REV	
	3700	09-3	F	
PAGE				
	1	OF	9	

DETAIL DESCRIPTION Chemical & Hazar	dous Mate	rial	REF 4	O CFR	117, 2	263, 264
Emergency Response Procedure -	Disk #L-a	ic-2			265, 7	761
ENGINEER	DATE	APPROVAL				DATE
D. E. MacDonald		İ				

#### 1.0 General Information

- 1.1 The Chemical and Hazardous Material Emergency Response Procedure incorporates the following security procedures:
  - SM-5.1.2 Emergency Action Plan
  - SM-5.2.4 Emergency Contingency Procedure Emergency Brigade
  - SM-5.4.8 Emergency Contingency Procedure Fire Evacuation
- 1.2 These are the procedures which identify the method of plant evacuation, the alarm system and the training requirements of the emergency brigade personnel.

SC1-3938 Rev 4 841

Revision E Page 157



### SECURITY MANUAL

TITLE	SUPERSEDES	NUMBER
	06/01/84	SM-5.2.4
EMERGENCY CONTINGENCY PROCEDURE	ISSUE DATE	EFFECTIVE DATE
EMERGENCY BRIGADE	02/01/85	02/01/85

#### I. PURPOSE

A. Sperry Defense Products Group, Computer Systems Division (CSD) Emergency Brigade is established to provide an organization which will respond to any emergency constituting a threat to CSD.

In order, Brigade responsibilities are to:

- 1. Assist in evacuating or protecting employees.
- Assist public emergency forces as needed or to protect company property pending arrival of public emergency forces.
- Anticipate problems and request preventive action where the potential for problems exists.
- B. To accomplish this, Emergency Brigade members are trained and familiarized with a common plan. Training will consist of actual demonstrations, periodic drills, review of education material, First Aid, CPR and fire fighting equipment.

#### II. SCOPE

This procedure applies to all CSD Facilities in the Twin City/Metropolitan area.

#### III. RESPONSIBILITY

### A. Emergency Coordinator

It is the responsibility of the Emergency Coordinator to assure:

- 1. The existence and training of the Emergency Brigade.
- 2. The exercise of periodic evacuations and drills.
- 3. That management is informed of potential emergency situations and/or corrective action required to meet an emergency.
- 4. To assure that coordination is maintained with community agencies that might be called in an emergency.

### B. Emergency Coordinator - Alternate

The alternate to the Emergency Coordinator will assist in the performance of the Emergency Coordinator's duties and assure Brigade responsibilities.

### C. Facility Brigade Captains

It is the responsibility of the Facility Brigade Captains to:

- Notify the Emergency Coordinator of potential hazard areas in his/her facility.
- 2. Assure the staffing and direction of the Facility Brigade by verifying the availability of members once a month and appointing replacements where necessary.
- 3. Implement drills as requested by the Emergency Coordinator.
- 4. Serve in liasion with the Emergency Coordinator, Emergency Brigade members, Civil Emergency Organizations, and Facilities service functions in an emergency situation.

### D. Alternate Facility Captains

It is the responsibility of the Facility Brigade Captain Alternate to act in the absence of the Facility Brigade Captain and to assist in the exercise of the responsibilities.

### E. Emergency Brigade Members

It is the responsibility of the individual Emergency Brigade member to:

- Be familiar with his/her area, its potential hazards, use of emergency equipment and alarm procedures so that he/she can respond positively in an emergency.
- Notify the Facility Captain of potential problems or hazards in his/her area such as lack of or improper extinguishers, excessive accumulation of waste, or blocked exits.
- 3. Participate in Emergency Brigade drills or training sessions.
- 4. Serve in a liaison capacity between Facility Brigade Captains and area supervisory personnel.
- 5. Assure the orderly movement or evacuation of area personnel in a drill or emergency situation.
- 6. Assist in the protection of company property according to instructions from Facility Brigade Captains in an actual emergency situation.



### SECURITY MANUAL

TITLE	SUPERSEDES	NUMBER
PMED CEVAY COUNTY OF ACT AND	06/01/84	SM-5.4.8
EMERGENCY CONTINGENCY PROCEDURE FIRE EVACUATION	ISSUE DATE	EFFECTIVE DATE
FIRE EVACUATION	02/01/85	02/01/85

#### I. PURPOSE

To establish an orderly evacuation procedure in case of fire or bomb threat.

#### II. SCOPE

This procedure applies to all Sperry Defense Products Group, Computer Systems Division (CSD) locations in the Twin City/Metropolitan area.

### III. GENERAL

- A. TO REPORT A FIRE: (24 hours a day, 7 days a week), AT ALL FACILITIES DIAL 3000. This number gives you the Facility telephone operator, the nurse, and the main guard post.
- B. Fire is usually the cause or present at any major emergency or disaster. The possibility of serious fires is reduced by the installation of proper fire protection equipment, good housekeeping and fire prevention practices, but the proper and quick response at the time a fire is first discovered is the most effective means of reducing loss or injury to personnel.
- C. When telephoning, report the nature and location of the fire to the guard by grid locations, such as the mail station. He/she will initiate the facility evacuation siren and call the Fire Department.
- D. If for some reason operators or guards cannot be reached, telephone the Fire Department, using the emergency 911 system.

### E. Emergency Brigade Action

- 1. Initiation of an evacuation for fire will be by continuous sounding of the siren. Termination will be announced by two short signals of the fire siren.
- The Emergency Coordinator will proceed to the area of emergency.
   The Facility Brigade Captain and Alternate will report to the main Facility lobby.
- Facility medical, safety, and designated Facility maintenance or service-area personnel will report to the Facility Brigade Captian in the lobby.

- 4. Emergency Brigade members will report to their pre-assigned post and assist in the orderly evacaution of personnel. Hard hats are to be worn to identify Emergency Brigade members to evacuating personnel.
- 5. When his/her area is evacuated the Emergency Brigade members will notify the Captain by the most expeditious means and be available for additional services as required. He/she will also notify the Captian of any special emergency or hazard to personnel.
- 6. Brigade members after evacuation of personnel may attempt to extinguish or confine fires pending arrival of the Fire Department if such action does not constitute hazard to the member.
- 7. Emergency Brigade members not in the area of fire may be directed by Emergency Brigade Captain to assist in fire fighting or protecting equiment after their area is evacuated.
- 8. Upon arrival of the Fire Department, fire extinguishing responsibilities will be turned over to firemen unless the assistance of Emergency Brigade members is requested.
- 9. Emergency Brigade members shall watch for problems encountered in the course of an evacuation drill and report them to the Facility Brigade Captain for corrective action.

### IV. GENERAL INSTRUCITONS TO BE GIVEN EMPLOYEES

Prior to initiation of drills, Emergency Brigade member should notify employees how to report a fire, of the exits to be used in evacuating their areas, the method used to announce drills, and what their conduct should be in a drill/evacuation.

The following guides should be followed in instructing employees how to conduct themselves in a fire drill.

- 1. Stop work immediately.
- 2. Turn off sources of power to machines and other electrical equipment.
- 3. Store government classified information in proper containers. If taking time to store material presents a hazard to the employee, classified information may be carried with the employee until suitable storage can be found. If neither of the above can be done, notify the facility guard.
- 4. Proceed through the nearest emergency exit quickly and quietly. DO NOT RUN!

- 5. Once outside move a sufficient distance from the exit (approximately 300 feet) to permit all emloyees to exit and wait for instructions from supervisors, or, in case of drill, notification that drill is terminated.
- 6. If returning to facility, use the same entrance you exited from.
- 7. Remain in assembly area until signaled to return, are dismissed, or given additional instruction from your supervisor.
- 8. DISPLAY BADGES UPON RE-ENTRY.

#### V. SPECIAL RESPONSIBILITIES

### A. Supervisory Personnel

- 1. On a continuing basis, notify area Emergency Brigade members of any problems or special hazard in their area involving his/her personnel or material.
- Upon initiation of a fire evacuaton or drill, supervisor will assist Emergency Brigade members in assuring an orderly evacuation of employees under their responsibility.
- Proceed with his/her employees to an area outside of the facility and assist in communicating instructions and/or control over subordinates.

#### B. Telephone Operators/Guards

Upon receipt of notification, telephone operators or guards will:

- Sound the emergency facility fire alarm and call the Fire Department.
- 2. At the time of call, obtain information such as location, extent, and imminent danger that may arise from the fire.
- 3. Reject other incoming calls.
- Maintain contact with Emergency Brigade Captains unless advised or required to evacuate.

#### C. Others

- 1. Nurses will report to the Facility Emergency Brigade Captain.
- 2. Contact Electric Company representatives will report for instructions to the Emergency Brigade Captain in the Facility lobby.
- 3. Lead maintenance personnel will report to the Facility Emergency Brigade Captain at the Facility lobby.

SM-5.4.8 3 of 3



### SECURITY MANUAL

TITLE	SUPERSEDES	NUMBER
	06/01/84	SM-5.1.2
EMERGENCY ACTION PLAN	ISSUE DATE	EFFECTIVE DATE
	02/01/85	02/01/85

#### I. PURPOSE

A. Sperry Defense Products Group, Computer Systems Division (CSD) has established contingency procedures to be followed in the event of major business interruptions due to any unforeseen disasters such as: Fire, tornado, storms, explosion, etc.

NOTE: The following procedures cover related disaster contingency plans:

Emergency Facility Closings Procedure - SM-4.6.20 Emergency Brigade Procedure - SM-5.2.4 Contingency Plan for Vital Records Bomb Threats - SM-5.6.18 Tornado/Severe Weather - SM-5.6.16 Fire Evacuation - SM-5.4.8 Disaster Plan - SM-5.6.14 Fire Prevention Plan - SM-5.3.6

#### II. SCOPE

This Procedure applies to all CSD locations in the Twin Cities/Metropolitan Area.

### III. GENERAL

- A. 1. In emergency life threatening situations during a fire, Sperrys' primary concern is "Life Safety" and to evacuate to a safe place all occupants of the threaten facility.
  - 2. The Emergency Brigade in each facility has escape route assignments at hallway intersections, and exit doors and act under the direction of their facilities captain.
  - 3. Evacuation route maps are posted in each facility.
  - 4. A fire alarm system is located in each facility.
  - 5. Unless life threatening, all large electrical equipment shall be shut off as personnel are exiting.

#### B. Emergency Assistance

1. To report a fire: dial 3000 (24 hours a day, 7 days a week). This number will give you the facilities telephone operator, the nurse and the main guard post.

#### III. GENERAL (Continued)

- When phoning, report the nature and location of the fire to the guard by grid location, such as the mail station. The guard will initate the facility evacuation siren and call the Fire Department.
- 3. If for some reason operators or guards cannot be reached, phone the Fire Department direct by calling 911 or 224-7371 (St. Paul), 454-3700 (Eagan), or 451-1818 (Mendota Heights).
- 4. Notify your supervisor of emergency if possible.

### C. Emergency Evacuation

- Employees who are not members of the Emergency Brigade and are not involved in the emergency will follow the instructions of their supervisor to:
  - (A) Evacuate the building and assemble a minimum of 300 feet away from the site and report to their supervisor or alternate.
  - (B) All visitors will be escorted out of the building to a safe area. Emergency Brigade will assist handicapped employees to evacuate facility.

NOTE: The Emergency Brigade will provide for the safe and expeditious evacuation of all building occupants due to an actual or potential life threatening condition.

- All exits are identified as required by law.
- D. Fire Control and Rescue
  - The control or suppression of fires is our secondary concern and will be manned by members of the Emergency Brigade using portable extinguishers and fire hoses on "Incipient type" fires only. Training on portable extinguishers is on an annual basis for the Emergency Brigade members.
  - 2. All other building occupants will leave the area.
- E. Assistance to Ill or Injured

Depending on circumstances:

- Injury Do not move unless to prevent additional exposure or injury.
- Illness Make comfortable until medical aid arrives.

SM-5.1.2

### III. GENERAL (Continued)

NOTE: All Facilities Protection personnel are trained:

- First Aid
   Cardiopulmonary Resuscutation (CPR)
   Fire suppression
- 4. Self Contained Breathing Appartus (SCBA)

Also a majority of the Emergency Brigade members are trained in the above mentioned subjects.

F. For additional information or clarification of the Emergency Action Plan contact the Emergency Coordinator, Facilities Protection Department at Sperry Park (612) 456-4550.



ECP	***********	·	REV	
	3700	9	F	
PAGE	***************************************			
	1	OF	1	

DETAIL DESCRIPTION Chemical & Hazardous Material REF 40 CFR 117, 263, 264

Emergency Response Procedure 265, 761

ENGINEER DATE APPROVAL DATE

D. E. MacDonald

#### APPENDICIES

- I. List of Available Personnel
- II. List of Agency and Emergency Telephone Numbers
- III. List of Available Equipment
- IV. Reportable Quantities of Various Chemicals
- V. Hazardous Material Incident Report Form
- VI. Emergency Information of Various Chemicals
- VII. Facility Lay-Outs



ECP			REV
	370	09	F
PAGE			4444
	1	OF	2

<b>ENVIRONS</b>	MENTAL	CONTROL	PROCEDURE
	WILMIII PAL		

DETAIL DESCRIPTION Chemical &	Hazardous Ma	aterial	REF	40 CI	FR 117,	263, 264
Emergency Response Procedu	ıre				265,	761
ENGINEER	DATE	APPROVAL				DATE
D E MacDanald						1

### Appendix I

### A. Hazardous Material Emergency Coordinator

	Home Ph.	Work Ph.	<u>Pager</u>
Roger Martin	non-responsive	456-4654	535
Dan MacDonald	non-responsive	696-4714	915
Mark Wilson	non-responsive	456-4220	565
Greg Weisjahn	non-responsive	456-2662	955

### B. Hazardous Material Emergency Team

Environmental Management	Home Ph.	Work Ph.	Pager
Greg Grinols	non-responsive	456-4625	575
Bill Polta	non-responsive	696-4639	905
Roger Ranzau	non-responsive	696-4656	925
Mike Medina (3rd shift)	non-responsive	456-4625	565
Mark Pierson (3rd shift)		696-4639	935
Bob Haselman (2nd shift)	non-responsive	456-4625	575
Joe Fitzgerald (2nd shift)	non-responsive	696-4639	945
Paul Skogquist		696-4639	
(Sat-Sun only - day shift)	-	or 456-4625	•

### C. Hazardous Material Emergency Support

Occupational Health Programs Roscoe Evavold Ron Berndt John Davis Tim Morris	non-responsive non-responsive non-responsive	696-4150 696-4837 696-4151 456-2751	532
Communications Mark Kessler Dick Nicholson	non-responsive	456-4512 456-2001	683
Emergency Brigade/Security Dick Herbst Jim Bailey	non-responsive	456-4549 456-4550	518 685
Janitoríal Ralph Voight	non-responsive	456-2179	697



ECP	100-100		REV	
	3700		F	
PAGE	***************************************			
	2	OF	2	

DETAIL DESCRIPTION Chemical & Emergency Response Proces		iterial	AEF	40 CF1	265,	263, 264 761
ENGINEER	DATE	APPROVAL		-		DATE
D. E. MacDonald		Į				

### C. Hazardous Material Emergency Support (continued)

	Home Ph.	Work Ph.	<u>Pager</u>
Maintenance Louie Handwerk (UP) Jim Belisle (SR)	non-responsive	456-2307 696-4089	689 583



ECP	37009A	REV	C
0405	14	0.5	15

ENVIRONMENTAL CONT	ROL	PR	OCEDUR		 Propriesentaliinisista siimisii kia kunneessa
DETAIL DESCRIPTION Chemical & Hazar Emergency Respons Procedure	rdous 1	Mate	rial	REF	 , (14)
ENGINEER	DATE	,	APPROVAL		DATE

2. Vacuum Cleaner

Wet or dry with 16 gallon tank.

Convert 'A' collar to adapt vacuum cleaner head to a 55 gallon drum.

Location: DI Pit

3. 1 1/2" Sandpiper Pump on Wheels

Location: DI Pit

### IV. OTHER SUPPLIES AVAILABLE

- A. Chemicals
  - 1. Lime
  - 2. Sodium bicarbonate
  - 3. Oil absorbent
  - 4. Sand
  - 5. Chemical absorbent pillows
- B. Equipment Other Groups
  - 1. Communication Equipment
  - 2. Portable fire extinguishers
  - 3. Company trucks
  - 4. Tractor with hydraulic hoist
  - 5. Eyewash, portable
  - 6. Gas pump plus hoses

UD1-3938



ECP			REV
	370		F
PAGE	- Campana		
	1	OF	1

					1	ŲF.	1
	NMENTAL CONT						
	Propose Procedure	dous Mate	rial	REF	40 CF		263, 264
EMETER ENGINEER	Response Procedure	DATE	APPROVAL	1		265,	DATE
D. E. Macl	Donald						
		Append	lix II				•
Emercency	Telephone Numbers						
<u>cmer 8 euc y</u>	istabilions wampers						
1.	CHEMTREC			(800)	424-9	300	
2.	MPCA (Emergency Spill	1)			296-7	373	
3.	EPA (Emergency Spill)	)		(312)	896-7	7591	
4.	Coast Guard (Emergene	cy Spill)		(314)	622-4	614	
5.	National Response Cer	nter		(800)	424-8	802	
6.	OHM Materials				935-4	804	
7.	St. Paul Fire				224-7	7371	
8.	St. Paul Police				291-1	1234	
9.	St. Paul Ambulance				224-	7371	
10.	Eagan Fire				454-3	3700	
11.	Eagan Police		•		454-3	3700	
12.	Hennepin County Pois (24 Hr.)	on Control	l Ctr.		347-3	3141	
13.	Union Carbide Hazard (24 Hr.)	ous Emerg	ency	(304)	744-	3487	
14.	Linde Division Midwe	st Office		(312)	454-	2347	
15.	Bay West Inc.		,		770-	3610	



ECP		Aodan	REV	
	370	09	F	
PAGE				
	1	OF	6	

DETAIL DESCRIPTION Chemical & Hazardous Material REF 40 CFR 117, 263, 264

Emergency Response Procedure 265, 761

ENGINEER DATE APPROVAL DATE

D. E. MacDonald

Appendix III

List of Available Equipment

#### I. INDIVIDUAL

- A. Chemical and Hazardous Material Emergency folder one at work one at home
- B. Hazardous Material Data File

#### II. SHEPARD ROAD

- A. Safety Equipment Cabinets (2)
  - 1. Location: Both at L and R Aisles Intersection
  - 2. Contents (Cabinet #1):
    - a. Tool box with assorted tools, like crescent wrenches, pliers, screw drivers, flashlite and extra batteries.
    - b. 3 sets of hard hats with face shields.
    - c. 4 sets of protective chemical suits, which consist of jackets, bib overalls, and hoods.
    - d. 1-box of plug rugs, which consist of 4 pliable mats that are used to seal off floor drains.
    - e. 20 foot x 1/2 inch rope with clips on both ends.
    - f. Two 50 foot electrical extension cords.
    - g. 1 dozen rubber gloves.
    - h. 2-squeege's.
    - i. Shovel.
    - j. Vacuum tools.
    - k. Goggles and safety glasses.

SC: 3938 Rev 4 941



ECP	3		REV	
	3700		F	
PAGE	· · · · · · · · · · · · · · · · · · ·			
	2	OF	6	

Emergency Response Procedure

DATE

- 3. Contents (Cabinet #2):
  - a. Hoses for 1 1/2" Sandpiper pump
- B. Emergency Spill Cart
  - l. Location: Waste Treatment Building
  - 2. Description and Contents;
    - a. Janitor type cart on four wheels to be used for small lab spills.
    - b. The cart contains: mop wringer and bucket, 25 gallon rigid liner for waste, coveralls and rubber boots in medium and large size, rubber gloves, safety glasses, clean-up neutralizing kits for caustic, acid and mercury spills, mop, lab broom, floor broom, whisk broom, dust pan and squeege, also general purpose absorbent pads, chemical spill signs and protective barrier tape.
- C. Vacuum Cleaner, wet or dry, with 16 gallon tank.
  - 1. Location: Waste Treatment Building
  - Convert 'A' collar to adapt vacuum cleaner head to a 55 gallon drum.
- D. 1 1/2" Sandpiper Pump on Wheels.
  - 1. Location: Waste Treatment Building
- E. Scott Breathing Apparatus
  - 1. Location:
- F. Emergency Spill Trailer
  - 1. Location: Outside Waste Treatment Building (north side)
  - 2. Contents:
    - a. Protective coveralls
    - b. Goggles
    - c. Rubber gloves
    - d. Large nonexplosive flashlights
    - e. Rope
    - f. Barrier tape
    - g. Overshoes



ECP		·	REV
	3700	)9	F
PAGE		***************************************	
	3	OF	6

DETAIL DESCRIPTION Chemical & Hazardous Material REF 40 CFR 117, 263, 264

Emergency Response Procedure 265, 761

ENGINEER DATE APPROVAL DATE

D. E. MacDonald

- h. Dust masks
- i. Spare batteries for flashlights
- j. 1 1/2" sandpiper pump
- k. Two 55 gallon spill drums
- 1. Oil absorbent
- m. Drum cart
- n. Gass engine powered air compressor
- o. Hand pump for flammable liquids
- p. Suction and dispense hose for both airpump and handpump
- q. Crow bar
- r. Tool box with assorted tools
- s. Traffic cones
- t. Portable eye wash

#### G. Emergency Spill Drums

#### l. Locations:

Chemical Dock - Two Drums
Tank Farm - Two Drums
Boiler Room - One Drum
P.C.B. Capacitors - One Drum
One Powerline
Pole, Northwest corner of lot.

#### Contents:

Contain one bag of oil absorbent and one bag of absorbent pads, minimum.

#### III. SPERRY PARK

- A. Safety Equipment Cabinets
  - Locations: One cabinet is located outside Environment Management Lab. The other one is located at top of stairs that leads to the CTC Labs.
  - 2. Contents: Both cabinets have:
    - a. Tool box with assorted tools, like crescent wrenches, screw drivers, pliers, flashlite and extra batteries.
    - b. Two hard hats with faceshields.
    - c. Two sets of protective chemical suits, which consist of jackets, bib overalls, and hoods, each in medium and large size.



ECP			REV
	3700	9	F
PAGE			
	4	OF	6

Emergency Response Procedure

DATE

DATE

DATE

DATE

DATE

- d. Two sets of one piece coveralls that are throw-aways, in medium and large size.
- e. 20 foot of 1/2 inch rope.
- f. Two 50 foot electrical extension cords.
- g. Rubber gloves.
- h. 2-squeeges.
- i. Shovel
- Goggles and safety glasses.
- B. Emergency Spill Cart
  - 1. Location: Environmental Management Equipment Room
  - 2. Description and Contents:
    - a. Janitor type cart on four wheels to be used for small lab spills.
    - b. The cart contains: mop, wringer and bucket, 25 gallon rigid liner for waste, coveralls and rubber boots in medium and large size, rubber gloves, safety glasses, clean-up neutralizing kits for caustic, acid and mecury spills, lab broom, floor broom, whisk broom, dust pan and squeege, also general purpose absorbent pads, chemical spill signs and protective barrier tape.
- C. Vacuum Cleaner
  - 1. Location: Environmental Management Equipment Room
  - 2. Description:
    - a. Wet or dry with 16 gallon tank.
    - b. Convert 'A' collar to adapt vacuum cleaner head to a 55 gallon drum.
- D. 1 1/2" Sandpiper Pump on Wheels
  - l. Location: Environmental Management Equipment Room

SC1-3938 Rev 4 841

Revision E Page 173



ECP			REV		
	3700	09	F		
PAGE		· · · · · · · · · · · · · · · · · · ·	<u>. d., </u>	-	
	5	OF	6		

DETAIL DESCRIPTION Chemical & Hazardous Material 40 CFR 117, 263, 264 Emergency Response Procedure 265, 761 ENGINEER DATE APPROVAL DATE D. E. MacDonald

- Ē. Scott Breathing Apparatus
  - One near each safety cabinet and a third one is outside the double doors leading to the Environmental Management equipment room.
- F. Emergency Spill Drums - Sperry Park
  - l. Locations:

P.C.B. Capacitors - One Drum North side of building by entrance gate. Boiler Room - Two Drums Between Cooling - Two Drums towers. Chemical Fill - One Drum Move Crew Dock - Two Drums

2. Contents:

> Contain one bag of oil absorbent and one bag of absorbent pads, minimum.

#### IV. MIDWAY

- Emergency Spill Drums Α.
  - 1. Locations:

P.C.B. Capacitors - Two Drums North side of building, Driveway loop. Fuel Oil Tank Form - Two Drums Boiler Room - One Drum Maintenance Oil Storage Room - One Drum Flammable Storage Room - One Drum

Contents:

Contain one bag of oil absorbent and one bag of absorbent pads, minimum.

SC1-3938 Ray 4 84)

Revision E Page 174



ECP		F	REV
	3/0	09	F
PAGE			and the state of t
	6	O#	6

DETAIL DESCRIPTION Chemical & H	lazardous M	laterial	REF	40	CFR	117,	263,	264
Emergency Response Procedur	İ			265,	761			
ENGINEER	DATE	APPROVAL					DAT	E
D. E. MacDonald								

#### V. OTHER SUPPLIES AVAILABLE

- A. Chemicals
  - 1. Location: Chemcial Storage Areas (Shepard Road and Sperry Park)
  - 2. Content:
    - a. Lime
    - b. Sodium bicarbonate
- B. Equipment Supplied by Other Groups
  - 1. Communication Equipment Guards
  - 2. Portable fire extinguishers Guards
  - 3. Company trucks Transportation
  - Tractor with hydraulic hoist Maintenance
  - 5. Eyewash, portable Maintenance
  - 6. Gas pump plus hoses Maintenance



ECP	·····		REV
	3700	09	F
PAGE			(mp
	1	OF	2

DETAIL DESCRIPTION Chemical & Hazardous Material REF 40 CFR 117, 263, 264

Emergency Response Procedure 265, 761

ENGINEER DATE APPROVAL DATE

D. E. MacDonald

#### APPENDIX IV

## Reportable Quantities of Various Chemicals

Acetic Acid, Glacial Corrosive Material	EPA min - 1000 lbs.
Butyl Acetate Flammable liquid	EPA min - 5000 lbs.
Calcuim cyanide Poison Class B	EPA min - 10 lbs.
Chromic Acid Oxidizing material	EPA min - 1000 lbs.
Chromic Acid Corrosive material	EPA min - 1000 lbs.
Carbolic Acid (Phenol), Liquid Poison Class B	EPA min - 1000 lbs.
Caustic Soda (Liquid) Corrosive material	EPA min - 1000 1bs.
Caustic Soda (solid) Corrosive material	EPA min - 1000 lbs.
Copper Cyanide Poison Class B	EPA min - 10 lbs.
Cyanide of Potassium, Liquid Poison Class B	EPA min - 10 lbs.
Cyanide of Potassium, Solid Poison Class B	EPA min - 10 lbs.
Cyanide of sodium, liquid Poison Class B Cyanide mixture, dry	EPA min - 10 lbs.  EPA min - 10 lbs.
Poison Class B Hydrochloric acid	EPA min - 5000 lbs.
Corrosive Material Hydrochloric Acid Mixtures	EPA min - 5000 lbs.
Corrosive Material Hydrofluoric acid	EPA min - 5000 lbs.
Corrosive Material Mercury Compounds	EPA min - 1 lb.
Poison Class B Naphtha	EPA min - 5000 lbs.
Flammable Liquid Nitric acid solutions	EPA min - 1000 lbs.
Corrosive Materials Phosgene	EPA min - 5000 lbs.
Poison Class A Sulfuric Acid	EPA min - 1000 lbs.
Corrosive Material	



ECP	***************************************		REV
	370	09	F
PAGE			
	2	OF	2

ENVIRONMENTAL CO	ONTROL F	ROCEDUR	E					
DETAIL DESCRIPTION Chemical & Emergency Response Procedu		iterial	REF	40	CF R	117, 265,	263, 761	264
ENGINEER D. E. MacDonald	DATE	APPROVAL					DAT	E
Toluene Flammable Liquid	E	CPA min - 100	O lbs.					
Xylene Flammable Liquid	E	EPA min - 100	O lbs.					

Sperry
Defense Products Group
Box 64525 - M.S. U1N14
St. Paul, MN 55164
ont (612) 456-4812

## APPENDIX V HAZARDOUS MATERIAL INCIDENT REPORT FORM

	3700			Rev	. F
Page	1	of	_1		

		Date
Name of Facility	Address	Phone Number
Reported by	Type of Incident (eg	. Fire, Spill, Explosion
Date of Incident		Time of Incident
Chemical(s) Involved		
Amount of Chemical(s)		
Chemical Information		
List of Personnel Involved		ordinator
Steps taken to contain		
Extent of Injuries		Employed by
Explanation		
Outside Organizations Notified:		
Method of Clean Up		
Estimated Quantity & Disposition of Material F	Recovered	· · · · · · · · · · · · · · · · · · ·
Equipment Used		
Date Equipment Cleaned & Replaced		
sessment of actual or potential hazards to h	numan health of the environ	nment, where applicable



ECP			REV
	370	09	F
PAGE			
	1	OF	46

DETAIL DESCRIPTION Chemical & Hazardous Material Hazardous Materials Emergency Response Procedure Safety Manual APPROVAL DATE

#### APPENDIX VI

#### CORROSIVE

### Definition:

D. E. MacDonald

A liquid or solid that causes visible destruction or irreversible damage to skin tissue at the point of contact, or that has a corrosion rate on steel.

Phosphorus pentachloride, solid; Potassium flouride solution;

Sulfuric Acid.

### POTENTIAL HAZARDS

Fire--May catch fire.

Health-- Vapors extremely irritating.

Contact may cause burns to skin and eyes. If inhaled, may be harmful.

Runoff may pollute water supply.

### IMMEDIATE ACTION

Identify material involved.

Keep unnecessary people away.

Keep upwind, isolate hazard area.

Wear full protective gear.

#### IMMEDIATELY FOLLOW-UP ACTION

Move containers from fire area if without risk. Fire--

Small fire--Dry chemical or CO2.

Large fire--Foam or water.

> Cool containers with water from maximum distance until well after the fire is out.

#### SPILL or LEAK

Stop leak if without risk.

Do not touch spilled material.



ECP	- Lan Ma		REV
	370	09	F
PAGE			
	2	OF.	46

DETAIL DESCRIPTION Chemical & Haz	ardous	Materials	REF	Hazardous Materials
Emergency Response Procedure				Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	ļ	ļ		

Small Spill- Flush area with water

Large Spill- Dilute with large amount of water and dike for later disposal.

FIRST-ALD

Remove contaminated clothing and shoes.

In case of contact with material immediately flush skin or eyes with running water FOR AT LEAST 15 MINUTES.

Keep patient warm and quiet.

Effects of contact or inhalation may be delayed.

Call physician.

#### FLAMMABLE - COMBUSTIBLE

Flammable Liquid Definition:

Any liquid which under specified test procedures has a flashpoint of less than 100°F. (37.8°C).

Examples: Ether, Gasoline.

(Under new regulations Flammable placard may also signify Class C Explosives—which are defined as manufactured articles which contain restricted quantities of Class A and/or Class B explosives as components and certain types of fireworks.)

Combustible Liquid Definition:

A liquid not meeting the definition of any other hazardous materials class having a flashpoint of 100°F. (37.8°C) or more and less than 200°F. (93°C).

Examples: Formaldehyde; Fuel oil, and Lube oil.

POTENTIAL HAZARDS

Fire-- Highly flammable.

Flammable vapors may spread from spill.

Container may explode due to heat of fire.

Runoff may create fire or explosion hazard in sewer system.

SC\*-3938 Pet 4 841



ECP		<del>*************************************</del>	REV
	.3700	<b>)</b> 9	F
PAGE		#	
†	3	OF	46

DETAIL DESCRIPTION Chemical	& Hazardous Ma	aterials	REF	Hazardous Materials
Emergency Response Proce	edure			Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald				Ì

Health-- Vapors indoors may cause dizziness or suffocation.

Fire may produce irritating or poisonous gases.

IMMEDIATE ACTION

Identify material involved.

Keep all unnecessary people away.

Keep upwind, isolate hazard area.

Eliminate all open flames; No smoking; No flares.

Evacuate by at least 2,000 feet.

IMMEDIATE FOLLOW-UP ACTION

FIRE-- Small fire: Dry chemical, CO2, foam.

Large fire: Water spray, fog, or foam.

Move containers from fire area if without risk.

Cool containers with water from maximum distance until well after fire is out.

Stay away from ends of tank.

SPILL or LEAK

Stop leak if without risk.

No flares, smoking, or flames in hazard area.

Use water spray to reduce vapors.

Large spills: Dike for later disposal, cover with foam.

Small spills: Take up with sand, earth, or other noncombustible

absorbent material. Cover with foam for later dispo-

sal. (Foam is highly recommended, prevents

re-ignition).

FIRST-AID

Remove to fresh air.

Use standard first-aid procedures.



ECP			REV	
	3700	09	F	
PAGE			- <u>t</u> -	
	4	OF	46	

DETAIL DESCRIPTION Chemical & Hazar	rdous Mate	erials F	EF Hazardous Mat	erials
Emergency Response Procedure		Safety Manual		
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	1			

#### FLAMMABLE GAS

#### Definition:

Gas which is flammable or explosive under prescribed test procedures.

Examples: Acetylene, Hydrogen; Propane.

POTENTIAL HAZARDS

Fire-- May be ignited by heat, sparks, flames.

Flammable vapors may spread from spill.

Containers may explode due to heat of fire.

Gas explosion hazard indoors, or in sewers.

Health- Contact with liquid may cause burns to skin and eyes.

Vapors indoors may cause dizziness or suffocation.

Fire may produce irritating or poisonous gases.

#### IMMEDIATE ACTION

If FLAME IMPINGEMENT occurs on the vapor space, withdraw immediately it will rupture within 10-15 minutes.

Identify material involved.

Eliminate all open flames. No smoking. No flares. Keep internal combustion engines at least 3000 feet away from vapor cloud.

Keep unnecessary people away.

Keep upwind, isolate the area.

Evacuate by at least 3,000 feet.

IMMEDIATE FOLLOW-UP ACTION

Fire-- Let burn unless leak can be stopped immediately.

Small fire: Dry chemical CO2.



ECP		F	IEV
	370	09	F
PAGE		7 1.000 G	Valla Maria Company
	5	OF	46

Emergency Response Procedure

DATE

Large fire:

Water Spray or fog.

Move containers from fire if without risk.

Cool containers with water from maximum distance until well after fire is out. (500 gallons/minute--minimum recommendation)

Stay away from ends of tanks.

Apply water to side of tanks.

Withdraw immediately in case of rising sound from venting safety device.

For massive fire in cargo area, use unmanned hose holder or monitor nozzles.

If this is impossible, withdraw from area and let fire burn.

## SPILL or LEAK

No flares, smoking, or flames in hazard area.

Stop leak if without risk.

Use water spray to reduce vapors.

Do not touch spilled liquid.

Isolate area until gas has dispersed.

#### FIRST-AID

Remove to fresh air.

Use standard first-aid procedures.

### NON-FLAMMABLE GAS

#### Definition:

Gas which is hazardous by virtue of being under pressure, but which does not burn or explode under prescribed tests.

Examples:

Helium; Oxygen; Sulfor dioxide; Argon; Nitrogen and Anyhdrous ammonia.

SC1-3938 Per 4 841



ECP	******		REV	
	3700	)9	F	į
PAGE				200
ŀ	6	OF	46	

DETAIL DESCRIPTION Chemical & Hazar	dous Mate	rials BEF	Hazardous M	aterials
Emergency Response Procedure			Safety Manu	al
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	l			

#### POTENTIAL HAZARDS

Fire-- May burn when subjected to intense heat.

Container may explode in heat or fire.

Health-- Runoff may pollute water supply.

Vapors extremely irritating.

Contact may cause burns to skin and eyes.

If inhaled, may be harmful.

#### IMMEDIATE ACTION

Identify material involved.

Keep unnecessary people away.

Keep upwind, isolate hazard area.

Wear self-contained breathing apparatus and full protective gear.

If FLAME IMPINGEMENT occurs, withdraw immediately, it will rupture within 10-15 minutes.

#### IMMEDIATE FOLLOW-UP ACTION

Fire-- Small fires: Dry Chemical or CO2.

Large fires: Water spray or fog.

Move containers from fire area if without risk.

Cool containers with water from maximum distance until well after fire is out.

#### SPILL or LEAK

Do not touch spilled material.

Stop leak if without risk.

Use water spray to reduce vapors.

Isolate area until gas has dispersed.

SC1-3938 Rev 4 84:

Revision E Page 184



ECP			REV
	3700	09	F
PAGE			
	7	OF	46

DETAIL DESCRIPTION Chemical & Hazar	erials REF	Hazardous Mate	rials	
Emergency Response Procedure		Safety Manual		
ENGINEER	DATE	APPROVAL	C	DATE
D. E. MacDonald	ļ			

#### FIRST-AID

Remove to fresh air. Call for emergency medical care.

If victim is not breathing, use resuscitation procedures. If the victim's heart has stopped beating, use CPR procedures.

If victim contacted material, immediately flush skin or eyes with running water FOR AT LEAST 15 minutes.

Remove contaminated clothing.

Keep victim warm and quiet.

#### ORGANIC PEROXIDE

#### Definition:

A derivative of hydrogen peroxide in which part of the hydrogen has been replaced by an organic material.

Examples:

Acetyl benzoyl peroxide; Benzoyl peroxide; Lauroyl Peroxide.

#### POTENTIAL HAZARDS

Fire-- May be ignited by heat, sparks, flames.

May ignite combustibles (wood, paper, oil, etc).

Container may explode in heat of fire.

May explode from friction, shock, heat or contamination.

Runoff to sewer may create fire or explosion hazard.

Health-- Contact may cause burns to skin and eyes.

Fire may produce irritating or poisonous gases.

#### IMMEDIATE ACTION

Identify material involved.

Keep unnecessary people away.

Keep upwind, isolate hazard area.

Wear full protective gear.



ECP	······································	- Circuration - Control	REV		/s
	3700	)9		F	
PAGE			<u> </u>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	8	OF		46	

DETAIL DESCRIPTION Chemical & Hazardous Materials

Emergency Response Procedure

ENGINEER

DATE

DATE

DATE

D. E. MacDonald

IMMEDIATE FOLLOW-UP ACTION

Fire-- Small fires: Dry chemical or CO2.

Large fires: Flood with water.

Cool containers with water from maximum distance until well after fire is out.

Fight fire from maximum distance.

For massive fire in cargo area, use unmanned hose holder or monitor nozzles.

Keep upwind, isolate hazard area.

Wear full protective gear.

#### IMMEDIATE FOLLOW-UP ACTION

Fire-- Small fires: Dry chemical or CO2.

Large fires: Water spray or fog.

Move containers from fire area if without risk.

Cool containers with water from maximum distance until well after fire is out.

Fight fire from maximum distance.

For massive fire in cargo area, use unmanned hose holder or monitor nozzles.

#### SPILL or LEAK

Stop leak if without risk.

Do not touch spilled material.

Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large spills: Dike for later disposal.

Small spills: Take up with sand, earth, or other noncombustible

absorbent materials.

Sweep small dry spills into dry metal containers and keep tightly covered.



ECP		***************************************	REV
_	3700	)9	F
PAGE		***************************************	<u></u>
	9	OF	46

DETAIL DESCRIPTION Chemical & Hazar	dous Ma	terials	REF Hazaro	ious Materials
Emergency Response Procedure	Safety Manual			
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald				

#### FIRST-ALD

Remove to fresh air.

Call for emergency medical care.

Remove contaminated clothing and shoes.

In case of contact with material immediately flush skin or eyes with running water FOR AT LEAST 15 MINUTES.

Keep patient warm and quiet.

Effects of contact or inhalation may be delayed.

Use standard first-aid procedures.

### OXIDIZER

#### Definition:

A substance that yields oxygen readily to stimulate the combustion of certain other substances.

Examples:

Ammonium nitrate, mixed fertilizer; Lead nitrate, Lead peroxide, Hydrogen Peroxide

#### POTENTIAL HAZARDS

Fire-- May ignite combustibles (wood, paper, oil, etc.).

Mixtures with fuels may explode.

Health-- Fire may produce irritating or poisonous gases.

## IMMEDIATE ACTION

Identify material involved.

Keep unnecessary people away.



-	ECP			REV	
		3700	9	F	
	PAGE				
		10	OF	46	

DETAIL DESCRIPTION Chemical & Hazardous Materials REF Hazardous Material					
Emergency Response Procedure			Safety	Manual	
ENGINEER	DATE	APPROVAL		DATE	
D. E. MacDonald	<u></u>	]			

### OXYGEN

### Definition:

Oxygen (Pressurized Liquid) in contact with fuels, oils and other combustible materials can cause violent, rapid combustion or explosion. Sources of ignition, sparks, impacts, friction, or sudden shocks should be prevented in areas exposed to liquid oxygen spills or leakages.

#### POTENTIAL HAZARDS

Fire- Materials may ignite in oxygen vapor.

Automobile engine will catch fire in oxygen atmosphere.

### Explosion--

Container may explode due to heat of fire.

Mixtures with fuels may explode.

Gas explosion hazard indoors, outdoors or in sewers.

Health-- Contact with liquid may cause burns to skin and eyes.

#### IMMEDIATE ACTION

Identify material involved.

Wear full protective gear.

Eliminate all open flames; No smoking; No flares. Keep internal combustion engines away from vapor cloud area.

Evacuate by AT LEAST 2,000 FEET.

#### IMMEDIATE FOLLOW-UP ACTION

FIRE-- Small fires: Dry chemical or CO2.

Large fires: Foam or water.

Move containers from fire area if without risk.

Cool containers with water from MAXIMUM DISTANCE until well after fire is out.

For massive fire in cargo area, use unmanned hose holder or monitor nozzles. If this is impossible, withdraw from area and let fire burn.

Page 188

sc:-3938 Gev 4 84: Revision E



ECP			REV		***************
	3700	9		F	
PAGE	***************************************			ι <del>ν</del>	
	11	OF		46	

	O I I I WAS NOTE	9 6 C. And American (may 1999) 5		
DETAIL DESCRIPTION Chemical & Ha	zardous M	laterials	REF	Hazardous Materials
Emergency Response Procedure				Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald				

#### SPILL or LEAK

Do not touch spilled liquid.

Stop leak if without risk.

Keep combustibles away from spilled material.

Isolate area until gas has dispersed.

#### FIRST-AID

Remove victim to fresh air.

Remove contaminated clothes.

Use standard first-aid procedures.

### POISON B

#### Definition:

Poison B-liquids or solids (including pastes and semi-solids) known to be so toxic to man as to create a health hazard during transportation; or which are presumed to be toxic to man because of effects of laboratory animals.

Examples:

Arsenic, some insecticides; Carbolic acid (phenol); cyanide

#### POTENTIAL HAZARDS

Fire--May catch fire.

Health-- Liquids cause burns to skin and eyes. Absorption by clothes or shoes

may cause delayed burns.

Vapors extremely irritating.

Vapors may be fatal if inhaled.

Runoff may pollute water supply.

## IMMEDIATE ACTION

Identify material involved.

Keep unnecessary people away.

Revision E Page 189



ECP	A CONTRACTOR OF THE CONTRACTOR		REV	
	3700	9.	F	
PAGE				
	12	OF	46	

DETAIL DESCRIPTION Chemical & Haza	rdous	Materials	REF Haza	ardous Materials
Emergency Response Procedure			Saf	ety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	1	ļ		

Keep upwind, isolate hazard area.

Wear self-contained breathing apparatus, and full protective gear.

IMMEDIATE FOLLOW-UP ACTION

Fire-- Small fires: Dry Chemical or CO2.

Large fires: Foam or water.

Move containers from fire area if without risk.

Cool containers with water if exposed to fire.

SPILL or LEAK

Do not touch spilled liquid.

Stop leak if without risk.

Use water spray to reduce vapors.

Small spills: Take up with sand, earth or other non-combustible absorbent material.

FIRST-AID

Remove victim to fresh air. Call for emergency medical care. Effects of contact or inhalation may be delayed.

If victim is not breathing, use resuscitation procedures. If the victim's heart has stopped beating, use CPR Procedures.

If victim contacted materials, immediately flush skin or eyes with running water FOR AT LEAST 15 MINUTES.

Remove contaminated clothing.

Keep victim warm and quiet.

Transmit with the victim the exact nature of the poison.

Hennepin County Poison Control Center (612) 347-3141 24 hrs.

SC1-3938 Rev 4 341



ECP			REV
	3700	9	F
PAGE	*****	***************************************	
	13	OF	46

DETAIL DESCRIPTION Chemical & Hazar	dous Mate	rials	REF Hazardous Safety Man	
Emergency Response Procedure			Salety Man	uaı
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald				

#### POISON GAS

#### Definition:

Poison A--specifically enumerated gases or liquids of such nature that a small quantity of gas or the vapor is dangerous to life.

Examples:

Phosgene, Cyanogen; Hydrocyanic acid, Phosphine, arsine, nitric

oxide.

#### POTENTIAL HAZARDS

Fire-- May or may not catch fire

Explosion: Container may explode due to heat of fire.

Health-- Contact causes burns to skin and eyes.

Vapors may be fatal if inhaled.

Runoff may pollute water supply.

## IMMEDIATE ACTION

Identify material involved.

Wear self-contained breathing apparatus and full protective gear.

Keep upwind, isolate hazard area.

Keep unnecessary people away.

#### IMMEDIATE FOLLOW-UP ACTION

Fire-- Move container from fire area if without risk.

Cool containers with water from maximum distance until after the fire is out.

Do not get water inside containers.

### SPILL or LEAK

Do not touch spilled material.

Stop leak if without risk.

Use water spray to reduce vapors.



ECP	,		REV
	3700	9	F
PAGE		***************************************	
	14	OF	46

DETAIL DESCRIPTION Chemical & Hazar	dous Mate	erials	REF	Hazardous Mat	erials
Emergency Response Procedure				Safety Manual	
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald					Ì

Isolate area until it has dispersed.

Do not get water inside containers.

FIRST-AID

Remove victim to fresh air. Call for emergency medical care.

If victim is not breathing, use resuscitation procedures. If victim's heart has stopped beating, use CPR procedures.

If victim contacted material, immediately flush skin or eyes with running water FOR AT LEAST 15 MINUTES.

Remove contaminated clothing.

Keep victim warm and quiet.

\*For detailed assistance in handling the hazard, call CHEMTREC (Chemical Transportation Emergency Center) toll free (800) 424-9300.

#### RADIOACTIVE

#### Definition:

Substances which spontaneously emit radiation capable of penetrating and damaging living tissue and undeveloped film. Fissile radioactive materials are classified according to the controls required for nuclear criticality safety.

Examples:

Cobalt 60; Gold 198; Iridium 192.

## POTENTIAL HAZARDS

Health-- Rac

Radiation hazard may be internal due to breathing vapor or dust, or contamination of skin, open cuts, etc.

Radiation hazard may be external (like X-Rays) from contamination on skin or exposure to unshielded material.

Prolonged exposure may be a threat to health or life.

Effects of radiation may be delayed.

Rotate personnel to cut down exposure time.

SC1-3938 Rev 4 84)



ECP	760 K - 2	Sich bereichten fast im der	REV
	3700	9	F
PAGE			
	15	OF	46

	<del>-</del>			1
DETAIL DESCRIPTION Chemical & H	lazardous Ma	terials REF	Hazardous Materials	]
Emergency Response Procedur	e		Safety Manual	
ENGINEER -	DATE	APPROVAL	DATE	1
D. E. MacDonald			ļ	

#### IMMEDIATE ACTION

Identify material involved.

Keep unnecessary people away.

Keep upwind, isolate hazard area.

Wear self-contained breathing apparatus and full protective gear.

Delay clean-up until arrival of qualified radiation monitoring assistance.

IMMEDIATE FOLLOW-UP ACTION

Fire-- Small fires: Dry chemical or CO2.

Large fires: Foam or water.

Fight fire from maximum distance.

Move undamaged packages from fire area if without risk.

Do not move damaged packages.

#### SPILL or LEAK

Do not touch spilled material or leaking or damaged packages.

Small spills: Take up with sand, earth, or other non-combustible absorbent material.

Large spills: Dike for later decontamination and disposal.

Do not enter spill area unless absolutely necessary to save life.

Limit entries to shortest time possible and record time to exposure.

Alternate persons for entry if possible.

#### FIRST-AID

Call for emergency medical care.

Use standard first-aid procedures.

Remove contaminated clothing and shower thoroughly with soap and water.

Advise rescue personnel and physicians that persons or equipment may be radioactively contaminated.



ECP			REV
	3700	9	F
PAGE			
1	16	OF	46

	I L L Nove Person i	: 11 W W made W	y a tem	
DETAIL DESCRIPTION Chemical & Haz	ardous M	aterials	AFF	Hazardous Materials
Emergency Response Procedure				Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald				ļ

# ACETIC ACID, GLACIAL CORROSIVE MATERIAL

Acetic acid glacial is a clear, colorless liquid with a very strong irritating odor. It is not classed as a flammable liquid but will burn. Prolonged exposure of skin may result in burns. If temperature drops below 60°F may freeze.

If material on fire or involved in fire:

Use water in large quantities.

If material not on fire and not involved in fire:

Keep sparks and flames away. Do not deliberately ignite without proper authorization. Build dikes to contain flow. Keep material out of streams and sewers.

#### Personnel protection

Do not handle broken packages without protective equipment. Wear protective gloves and safety glasses. Use self-contained breathing apparatus. Wash away any material which may have contacted body with copious amounts of water or soap and water.

### ACETONE FLAMMABLE LIQUID

Acetone is a clear colorless liquid having a pleasant odor somewhat similar to wood alcohol. It is produced by the distillation of acetate of lime. It is used as a solvent in the manufacture of smokeless powder, lacquers, etc. It is very flammable, having a flash point below 20°F. Acetone is completely miscible with water. Fires involving the chemical can be flushed with large quantities of water as an effective extinguishing agent.

If material on fire or involved in fire:

Use water in large quantities, water fog or foam, but liquid water may be ineffective.

Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

Revision E Page 194



ECP	W. C.		REV	
	3700	9	F	
PAGE				
	17	OF	46	

DETAIL DESCRIPTION Chemical & Hazardous Materials REF Hazardous Materials							
Emergency Response Procedure				Safety Manual			
ENGINEER	DATE	APPROVAL		DATE			
D. E. MacDonald							

#### ACETYLENE

#### FLAMMABLE COMPRESSED GAS

Acetylene is a flammable gas that has a rather wide "Flammability range" and for this reason it forms flammable mixtures with air over a much wider range of proportions than many other flammable gases. Acetylene becomes extremely dangerous if the gas alone is compressed under any ordinary conditions. Because of this, the D.O.T. Regulations authorize shipment only when gas is absorbed and compressed into a solvent (usually acetone) in cylinders that have been filled with some porous material. The D.O.T. Regulations require that the cylinder and filler comply with specified standards.

If material on fire or involved in fire:

Do not extinguish fire unless gas flow can be stopped. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away.

Personnel protection:

Avoid breathing gas.

Evacuation:

If it appears that fire can be controlled, get away but don't evacuate-- put hoses on stands, etc.

# ACIDS, LIQUIDS, N.O.S. CORROSIVE MATERIAL

This may include a large number of very hazardous liquids. An attempt should be made to find out specifically what material is involved.

If material on fire or involved in fire:

Use water in large quantities. Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.) Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

SC1/3938 Rev 4 841



ECP	(2007-10)		REV	
	3700	9	F	
PAGE	·····	• • • • • • • • • • • • • • • • • • • •		
	18	OF	46	

		$\sim \sim \sim 100$	PROCEDURE
EMAIDOLI	AICIA I AT	CONTROL	rnuceuune

DETAIL DESCRIPTION Chemical & Haza	rdous Mate	erials F	REF Hazardous Mai	erials
Emergency Response Procedure			Safety Manual	Ľ
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	}			]

#### Personnel Protection:

Do not handle broken packages without protective equipment. Avoid breathing vapors.

Wear protective gloves and safety glasses.

Wear self-contained breathing equipment.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

#### AIR COMPRESSED

#### NONFLAMMABLE COMPRESSED GAS

Air compressed is ordinary air compressed to high pressure and shipped in steel cylinders. It has the same hazards in transportation as other combustible and nontoxic compressed gases.

If material is involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)
Cool all affected containers with large amounts of water.

### ALCOHOL, BUTYL FLAMMABLE LIQUID

Alcohol, butyl is a clear colorless liquid having an aromatic odor. It varies in composition and may or may not be classed as a flammable liquid depending on the flash point.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

SC1-3938 Rev 4 841



ECP			RE∨
	3700	9	F
PAGE	C/Olle-		No.
	19	OF	46

DETAIL DESCRIPTION Chemical & Emergency Response Procedu		aterials	REF	Hazardous Materials Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	[			•

# ALCOHOL, DENATURED FLAMMABLE LIQUID

Alcohol, denatured consists of ethyl alcohol to which some other substance has been added to render it unfit for use as a beverage. Various formulas for denaturing alcohol are authorized by the Internal Revenue Department. The flash point of denatured alcohol is commonly about the same as that of ethyl alcohol.

- If material on fire or involved in fire:

Use water in large quantities or water fog or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

## ALCOHOL, ETHYL FLAMMABLE LIQUID

Alcohol, ethyl is a clear colorless liquid of characteristic taste and odor. It is obtained by the fermentation of grains, starch, sugar or molasses. It has a flash point of approximately 55°F.

If material on fire or involved in fire:

Use water in large quantities, water fog or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow.

# ALCOHOL, PROPYL FLAMMABLE LIQUID

Alcohol, Propyl is a clear colorless liquid having an odor similar to ethyl alcohol.

If material on fire or involved in fire:

Use water in large quantities, water fog or foam. Cool all affected containers with large amounts of water.

Revision E Page 197



ECP			REV
	3700	19	F
PAGE	<u> </u>	- House	· · · · · · · · · · · · · · · · · · ·
	20	OF	46

DETAIL DESCRIPTION Chemical & Hazar	rdous Mate	erials	REF H	azardous Mat	erials
Emergency Response Procedure	S	afety Manual			
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald	ļ	· ·			

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow.

# ALCOHOL, WOOD (METHANOL, METHYL ALCOHOL), FLAMMABLE LIQUID

Alcohol, wood (Methanol, methyl alcohol) is a clear colorless liquid of pleasant odor. It is obtained by the distillation of wood or is made from carbon monoxide and hydrogen. It mixes with water in all proportions, and has a flash point of about 45°F.

If material on fire or involved in fire:

Use water in large quantities, water fog or foam.

Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow.

# ALKALINE CAUSTIC LIQUIDS, N.O.S. CORROSIVE MATERIAL

Alkaline caustic liquids, n.o.s. are liquids which will cause damage to living tissue or will materially damage other freight. Most of them are water soluble and in case of spillage should be flushed away with large quantities of water. Great care should be taken to keep this material out of the eyes.

If material involved in fire:

Flood with water.

Extinguish fire using agent suitable for type of surrounding fire.

(Material itself does not burn.)

If material not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

SC1-3938 Rev 4 841



ECP			REV		
	3700	9	1	F	,
PAGE	, , , , , , , , , , , , , , , , , , , ,	****			
	21	OF		46	

i					
DETAIL DESCRIPTION Chemical & Haza	rdous Mate	rials	REF	Hazardous Materials	
Emergency Response Procedure				Safety Manual	
ENGINEER	DATE	APPROVAL		DATE	
D F MacDonald		1			

#### Personnel Protection:

Do not handle broken packages without protective equipment. Wear protective gloves and safety glasses. Wash away any material which may have contacted body with copious amount of water or soap and water.

# AQUA AMMONIA SOLUTIONS CONTAINING ANHYDROUS AMMONIA NONFLAMMABLE COMPRESSED GAS

Aqua ammonia solutions containing anhydrous ammonia are usually fertilizer solutions containing free ammonia gas. When the absolute pressure exceeds 40 pounds per square inch at 70°F or 104 pounds per square inch at 130°F the solutions are classed as nonflammable compressed gases.

If material involved in fire:

Extinguish fire using suitable for type of surrounding fire. (Material itself does not burn.)
Cool all affected containers with large amount of water.

If material not involved in fire:

Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel protection:

Avoid breathing vapors.
Wear protective gloves and safety glasses.
Wear self-contained breathing apparatus.

### ARGON NONFLAMMABLE COMPRESSED GAS

Argon is a colorless, odorless, incombustible gas obtained from the atmosphere. It is used in filling incandescent electric light globes and for most gas welding. It is shipped in steel cylinders, compressed to a pressure of about 1.800 pounds per square inch, when not liquefied.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)
Cool all affected containers with large amount of water.

Revision E Page 199



ECP	·····	γ	REV	
	3700	9	F	
PAGE				
	22	OF	46	

DETAIL DESCRIPTION Chemical & Hazar	rdous Mate	eríals	REF Hazar	dous Materials
Emergency Response Procedure		Safet	y Manual	
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	1.			ļ

#### Personnel Protection:

Do not breathe Argon. It can cause air hunger as it replaces oxygen.

#### ARSINE

## POISON GAS AND FLAMMABLE GAS

Arsine is a colorless highly toxic and flammable gas which acts as a blood and nerve poison. It may be fatal if inhaled, and may form explosive mixtures with air.

If material on fire or involved in fire:

Do not extinguish burning gas if flow cannot be shut off immediately. Keep all cylinders cool with large amounts of water.

If material not on fire or not involved in fire:

Evacuate area and keep personnel upwind. Use self-contained breathing apparatus and shut off leak if without risk.

## Personnel protection:

Avoid breathing vapor.

Wear full protective gear including self-contained breathing equipment.

Get medical attention immediately if exposed to gas.

# BORON TRICHLORIDE CORROSIVE

Boron Trichloride is a colorless, corrosive, toxic liquid which is shipped at its vapor pressure of 4 psi at 70°F. It causes burns on contact with eyes, skin and mucous membranes. It is a nonflammable gas.

If involved in fire:

Keep all cylinders cool with large amounts of water.

If not involved in fire:

Evacuate area and keep personnel upwind. Use self-contained breathing apparatus and protective clothing. Shut off leak if without risk.

Revision E



ECP		~	REV
	3700	9	F
PAGE		······································	
	23	OF	46

DETAIL DESCRIPTION Chemical & Haza Emergency Response Procedure	rdous	Materials	REF	Hazardous Materials Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	1	<b>\</b>		•

Personnel protection:

Avoid breathing vapors.

Wear full protective clothing and use self-contained breathing equip-

In case of contact flush with large amounts of water. Get medical attention immediately if exposed to gas.

## BUTYL ACETATE FLAMMABLE LIQUID

Butyl acetate is a clear, colorless liquid that has a pleasant fruit like odor. It may or may not be flammable under D.O.T. Regulations depending on purity, etc. The hazard is that of flammability.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Liquid water may be ineffective. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

## CALCIUM CYANIDE POISON CLASS B

Calcium Cyanide is a grayish colored powder used principally as an insecticide. It is highly poisonous when taken internally and when exposed to air moisture it gives off hydrocyanic acid gas which is also poisonous.

If material on fire or involved in fire:

Use water in large quantities. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep material out of streams and sewers.

SC1-3938 Rev 4 841 Revision E

Page 201



ECP		Millian	REV
	3700	9	F
PAGE			+6
	24	OF	46

DETAIL DESCRIPTION Chemical & Ha	zardous Ma	aterials	REF	Hazardous Materi	als
Emergency Response Procedure				Safety Manual	
ENGINEER	DATE	APPROVAL		DA	TE
D. E. MacDonald					

#### Personnel protection:

Do not handle broken packages without protective equipment. Do not attempt to burn without proper authorization. Avoid breathing dust.

Wear protective gloves and safety glasses.

Wear self-contained breathing apparatus. Releases poisonous Hydrocyanic gas with acids.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CARBOLIC ACID (PHENOL), LIQUID SOLID POISON CLASS B

Carbolic acid (phenol) is shipped either in solid form or in liquid form. Both forms have the very familiar strong odor of carbolic acid. It is poisonous and extremely irritating to tissue. In case of contact with clothing or body, wash with liberal quantities of soap and water. If severe or prolonged contact occurs, summon medical aid.

If material on fire or involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.)

If material not on fire or involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

#### Personnel protection:

Do not handle broken packages without protective equipment. Avoid breathing vapors.

Wear full protective clothing.

Wear self-contained breathing equipment when fighting fire.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CAUSTIC SODA (LIQUID) CORROSIVE MATERIAL

Caustic soda (Liquid) consists of caustic soda (Sodium hydroxide) in water solution. The solutions are similar in physical properties to caustic potash, liquid.

301-3938 Rev 4 341

Revision E Page 202



ECP			REV
	3700	19	F
PAGE			
	25	OF	46

DETAIL DESCRIPTION Chemical & Hazardous Materials			REF	Hazardous Ma	terials
Emergency Response Procedure			•	Safety Manua	1
ENGINEER	DATE	APPROVAL	- Maddell Maddell Action		DATE
D. E. MacDonald	1	ļ.			

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

If material not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

#### . Personnel protection:

Do not handle broken packages without protective equipment. Wear protective gloves and safety glasses. Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CAUSTIC SODA, SOLID CORROSIVE MATERIAL

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. Material itself does not burn. Avoid breathing fumes.

If material not involved in fire:

Keep material out of streams and sewers.

Personnel protection:

Do not handle broken packages without protective equipment. Avoid breathing dusts. Wear protective gloves and safety glasses.

### CHLOROTRIFLUORETHYLENE (FREON) FLAMMABLE GAS

Chlorotrifluorethylene is a colorless, flammable toxic liquefied gas which is inhibited because of its extreme reactivity and tendency to polymerize.

If material on fire or involved in fire:

Do not extinguish burning gas if flow cannot be shut off immediately. Keep all cylinders cool with large amounts of water.

SC1-3938 ≘ev 4 94)



ECP			REV
	3700	, ,	F
PAGE	······································		
	26	OF	46

DETAIL DESCRIPTION Chemical & Hazardous Materials				Hazardous Mat	erials
Emergency Response Procedure	•		Safety Manual		
ENGINEER	DATE	APPROVAL			DATE .
D. E. MacDonald					

If material not on fire or not involved in fire:

Evacuate area and keep personnel upwind.
Use self-contained breathing apparatus and protective clothing and shut off leak if without risk.
Keep sparks and flames away.

### Personnel protection:

Avoid breathing vapor.

Wear full protective gear and safety glasses.

In case of contact, flush with large amounts of water.

Get medical attention immediately if exposed to gas.

# CHROMIC ACID OXIDIZING MATERIAL

Chromic acid is in the form of reddish brown crystals. It is a strong oxidizing material, and when mixed with organic material produces heat, and may cause fire. It should therefore, be packed so as to avoid any possible contact with combustible materials.

Chromic acid, liquid, is a water solution of chromic acid, solid is very corrosive; spillage or fires involving the chemical should be flushed with large quantities of water.

If material on fire or involved in fire:

Use water in large quantities.

#### Personnel protection:

Wear protective gloves and safety glasses. Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CHROMIC ACID SOLUTION CORROSIVE MATERIAL

Chromic acid solution is a dark red liquid formed by dissolving solid chromic acid in water. There may be other acids, such as sulfuric, present also. In case of spillage flush with large quantities of water.

SC1-3938 Pel 4 341



ECP ·			REV
	3700	9	F
PAGE			
	27	OF	46

DETAIL DESCRIPTION Chemical &	Hazardous Ma	terials REF	Hazardous Materials
Emergency Response Procedu	ıre		Safety Manual
ENGINEER .	DATE	APPROVAL	DATE
D. E. MacDonald		ļ	

If material involved in fire:

Use water in large quantities. Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Personnel protection:

Wear protective gloves and safety glasses.
Wash away any material which may have contacted body with copious amounts of water or soap and water.

### COMBUSTIBLE LIQUID, N.O.S. (FLASH POINT ABOVE 80°F BUT NOT EXCEEDING 150°F)

If material on fire or involved in fire:

Use water fog, foam, dry chemical or carbon dioxide.

If material not on fire and not involved in fire:

Keep sparks and flames away.

Do not deliberately ignite without proper authorization.

# COMPRESSED GASES, N.O.S. FLAMMABLE

A compress gas is defined as any material or mixture having in the container either an absolute pressure exceeding 40 pounds per square inch at  $70^{\circ}$ F, or an absolute pressure exceeding 104 pounds per square at  $130^{\circ}$ F, or both; or any liquid flammable material having a Reid vapor pressure exceeding 40 pounds per square inch absolute at  $100^{\circ}$ F.

If material on fire or involved in fire:

Do not extinguish fire unless gas flow can be stopped. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away.

Do not deliberately ignite without proper authorization.

Do not use explosives on bulk containers without proper authorization.

Do not puncture bulk containers with rifle bullets.

Build dikes to contain flow.

Keep material out of streams and sewers.

SC1-3938 Rev 4 84



1	ECP		·	REV	
		37009	)	F	
	PAGE				
		28	OF	46	

LATINOMALMIAL COMMON PROCEDURE						
DETAIL DESCRIPTION Chemical & Haz	ardous Ma	aterials	REF	Hazardous Materials		
Emergency Response Procedure				Safety Manual		
ENGINEER	DATE	APPROVAL		DATE		
D. E. MacDonald		i				

#### Evacuation: '

If it appears that fire can be controlled, get away but don't evacuate—put hoses on stands, etc.

If large quantities involved, evacuate for radius of 1500 feet if fire becomes uncontrollable.

#### COMPRESSES GASES, N.O.S. NONFLAMMABLE

A Compressed Gas is defined as any material or mixture having in the container either an absolute pressure exceeding 40 pounds per square inch at 70°F, or an absolute pressure exceeding 104 pounds per square inch at 130°F, or both; or any liquid flammable material having a Reid vapor pressure exceeding 40 pounds per square inch absolute in 100°F.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.)
Cool all affected containers with large amount of water.

# COPPER CYANIDE POISON CLASS B

Copper cyanide consists of a green powder. This material is much less poisonous than cyanides of sodium, potassium or calcium.

If materials involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Cool all affected containers with large amount of water.

If material not on fire and not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

## Personnel protection:

Do not handle broken packages without protective equipment. Avoid breathing vapors.

Wear protective gloves and safety glasses.

Wear self-contained breathing equipment.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

SQ1-3938 - Pey 4 341



ECP			REV		
	3700	9		F	
PAGE	· · · · · · · · · · · · · · · · · · ·		····		
	29	OF		46	

DETAIL DESCRIPTION Chemical & Hazardous Materials

Emergency Response Procedure

ENGINEER

DATE

DATE

DATE

DATE

# CYANIDE OF POTASSIUM, LIQUID

POISON CLASS B

Cyanide of potassium, liquid is a water solution of cyanide of potassium.

If material involved in fire:

Use water in large quantities.
Extinguish fire using agent suitable for type of surrounding fire.
(Material itself does not burn.)
Cool all affected containers with large amounts of water.

If material not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

## Personnel protection:

Do not allow cyanides to come in contact with acids.

Wear self-contained breathing apparatus.

Do not handle broken packages without proper protective equipment.

Do not attempt to burn without proper authorization.

Avoid breathing vapors or gases.

Wear protective gloves and safety glasses.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CYANIDE OF POTASSIUM, SOLID POISON CLASS B

Cyanide of potassium, solid, is in the form of a heavy white salt. It is highly poisonous, but not otherwise dangerous. It is used in recovering precious metals, in case hardening and electro-plating.

If material involved in fire:

Use water in large quantities. Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.) Cool all affected containers with large amounts of water.

If material not involved in fire:

Keep material out of streams and sewers.

301-3938 Rev 4 34



ECP	A State of the Sta		REV	
	3700	9	F	
PAGE			<u> </u>	1
1	30	OF	46	

Emergency Response Procedure

Engineer

Date

## Personnel protection:

Do not allow cyanides to come in contact with acids. Wear self-contained breathing apparatus. Do not handle broken packages without protective equipment. Avoid breathing dusts. Wear protective gloves and safety glasses. Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CYANIDE OF SODIUM, LIQUID POISON CLASS B

Cyanide of sodium, liquid, similar in properties to cyanide of potassium liquid.

If material involved in fire:

Use water in large quantities. Cool all affected containers with large amounts of water.

If material not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

#### Personnel protection:

Do not allow cyanides to come in contact with acids. Wear self-contained breathing apparatus. Do not handle broken packages without protective equipment. Avoid breathing vapors. Wear protective gloves and safety glasses. Wash away any material which may have contacted body with copious amounts of water or soap and water.

# CYANIDES OR CYANIDE MIXTURES, DRY POISON CLASS B

If material involved in fire:

Use water in large quantities. Avoid breathing fumes. Cool all affected containers with large amounts of water.

If material not involved in fire:

Keep material out of streams and sewers.

3C1-3938 Rev 4 941



ECP			REV	- CANADA ANTON
	3700	9	F	
PAGE	2.H-1		-	CHICAGO CONTRACTOR CON
	31	OF	46	

DETAIL DESCRIPTION Chemical & Hazardous Materials   REF   Hazardous Nature   Safety Manu					erials
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald				•	

#### Personnel protection:

Do not allow cyanides to come in contact with acids.

Wear self-contained breathing apparatus.

Do not handle broken packages without protective equipment.

Do not attempt to burn without proper authorization.

Avoid breathing vapors or dusts.

Wear protective gloves and safety glasses.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

# DICHLOROSILANE FLAMMABLE GAS

Dichlorosilane is a highly flammable, toxic and corrosive gas. It causes severe burns on contact with eyes, skin and mucous membranes.

If material on fire or involved in fire:

Do not extinguish burning gas if flow cannot be shut off immediately. Keep all cylinders cool with large amounts of water.

If material not on fire or not involved in fire:

Evacuate area and keep personnel upwind. Use self-contained breathing apparatus and protective clothing and shut off leak if without risk.

Keep sparks and flames away.

#### Personnel protection:

Avoid breathing vapor.

Wear full protective gear and safety glasses.

In case of contact, flush with large amounts of water.

Get medical attention immediately if exposed to gas.

#### ETHER FLAMMABLE LIQUID

Ether is a clear, colorless, highly volatile and flammable liquid. It has a peculiar pungent odor, boils at temperature of 97°F and has a flash point below 0°F. It is made by treatment of alcohol with sulfuric acid. It is used medicinally as an anesthetic, technically as a solvent of fats, oils, rosins, etc. and mixed with alcohol as a solvent for nitrocellulose in the manufacture of smokeless powder.

3C1-3938 Rev 4 841



ECP	200		REV	
	.3700	9	F	
PAGE	** ***********************************	- American		
	32	OF	46	

DETAIL DESCRIPTION Chemical & Hazardous Materials

Emergency Response Procedure

ENGINEER

DATE

DATE

APPROVAL

DATE

DATE

If material on fire or involved in fire:

Liquid water may spread fire.
Use water fog, dry chemical, carbon dioxide or foam.
Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

#### Personnel protection:

Avoid breathing vapors.
Wear protective gloves and safety glasses.
Wear air-purifying gas mask.

#### Evacuation:

If it appears that fire can be controlled, get away but don't evacuate—put hoses on stands, etc. If large quantities involved, evacuate for radius of 1500 feet if fire (or polymerization reaction) becomes uncontrollable.

#### ETHYL ACETATE FLAMMABLE LIQUID

Ethyl acetate is a clear, colorless volatile liquid of fragrant odor, used as a medicine, as a flavoring and as a solvent. It is very flammable, having a flash point of approximately 40°F.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep materials out of streams and sewers.

SC1 5938 Rev 4 341

Revision E Page 210



ECP	11/10/20/20	40t.	REV
	3700	9	F.
PAGE			
	33	OF	46

DETAIL DESCRIPTION Chemical & Hazardous Materials REF Hazardous Material					
Emergency Response Procedure		Safety Manual			
ENGINEER	DATE	APPROVAL		DATE	
D. E. MacDonald					

## FLAMMABLE LIQUID, N.O.S.

Flammable liquid N.O.S.-- Any liquid not specifically shown, having a flash point of 80°F, or below, for purposes of transportation under D.O.T. Regulations as determined by the Tagliabue open cup test.

Try to ascertain the contents if not marked.

If material on fire or involved in fire:

Use water in large quantities, water fog, dry chemical, carbon dioxide, or foam.

Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

## FREON (TRICHLOROFLUOROMETHANE, TRICHLOROTRIFLUOROETHANE-TF)

#### ORM-A

Freon is a halogenated hydrocarbon which is colorless, nearly odorless heavy, non-flammable liquid.

If material involved in fire:

Cool all affected containers with large amounts of water.

If material not involved in fire:

Build dikes to contain flow.

Personnel protection:

Wear protective gloves and safety glasses. Wash promptly upon skin contact. Avoid breathing vapors.

### HEPTANE FLAMMABLE LIQUID

Heptane is a clear, transparent, water-white liquid that is quite volatile. It is classed as a flammable liquid. The hazard in transportation is that of flammable liquid such as the petroleum or coal tar derivatives.

SC1-3938 Rev 4 841



ECP			REV
	3700	9	F
PAGE	T+1×1		
}	34	OF	46

Emergency Response Procedure

ENGINEER

DATE

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Do not extinguish fire unless flow can be stopped. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

### <u>HELIUM</u>

#### NONFLAMMABLE COMPRESSED GAS

Helium is a colorless noncombustible and extremely stable gas. It is shipped in compressed condition and is classed as a nonflammable compressed gas.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Cool all affected containers with large amounts of water.

## HYDROCHLORIC ACID (MURIATIC ACID) CORROSIVE MATERIAL

Hydrochloric acid (Muriatic acid) is a corrosive liquid varying from colorless to yellow, according to purity. It gives off acid vapor of an irritating odor. It cannot be shipped in iron drums, and is commonly shipped in drums or tanks provided with acid-proof lining. This acid, as commonly shipped, is a water solution of the anhydrous hydrochloric acid gas. This acid does not cause fires, but will destroy many articles by contact.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

If material not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

301-3938 Rev 4 841



ECP			REV	***************************************
	3700	9	F	
PAGE	***************************************			
	35	OF	46	

		0 1		
DETAIL DESCRIPTION Chemical & Haza	ardous Mat	erials	REF Hazardous Mat	erials
Emergency Response Procedure			Safety Manual	
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	ļ			

#### Personnel protection:

Do not handle broken packages without protective equipment. Wear full protective clothing and self-contained breathing apparatus. Wash away any material which may have contacted body with copious amounts of water or soap and water.

#### HYDROCHLORIC ACIDS, ANHYDROUS NONFLAMMABLE COMPRESSED GAS

Hydrochloric acid, anhydrous is the dry hydrochloric acid gas which has been compressed to a liquid condition. Material is shipped in steel cylinders.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Cool all affected containers with large amounts of water.

#### Personnel protection:

Avoid breathing vapors.
Wear protective gloves and safety glasses.
Wear full protective clothing and self-contained breathing apparatus.

## HYDROCHLORIC ACID MIXTURES CORROSIVE MATERIAL

Hydrochloric acid mixtures are liquids containing a considerable amount of hydrochloric acid mixed with water and other ingredients. Such mixtures are frequently used to clean metal and other surfaces.

If material on fire or involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.)

If material not on fire and not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

301-3938 Ray 1 31:



ECP			REV
	3700	19	F
PAGE			
	36	OF	46

ENVINORMENTAL CONTROL PROCEDURE						
DETAIL DESCRIPTION Chemical & Haz	ardous M	laterials	REF	Hazardous Materials		
Emergency Response Procedure				Safety Manual		
ENGINEER	DATE	APPROVAL		DATE		
D. E. MacDonald	ì	Į.				

#### Personnel protection:

Do not handle broken packages without protective equipment. Wear full protective clothing and self-contained breathing apparatus. Wash away any material which may have contacted body with copious amounts of water or soap and water.

## HYDROGEN

#### FLAMMABLE COMPRESSED GAS

Hydrogen is a colorless flammable gas. It is compressed to high pressures and shipped in steel cylinders or in tank cars. The gas has an extremely wide flammability range.

If material on fire or involved in fire:

Approach fires of hydrogen with extreme caution. May be highly explosive.

Do not extinguish fire unless gas flow can be stopped. Cool all affected containers with large amounts of water.

If material not on fire or not involved in fire:

Keep sparks and flames away.
Do not deliberately ignite without proper authorization.

#### Personnel protection:

Do not attempt to burn without proper authorization.

#### Evacuation:

If it appears that fire can be controlled, get away but don't evacuate—put hoses on stands etc.

If large quantities involved, evacuate for radius of 2500 feet if fire becomes uncontrollable.

## LACQUER BASE LIQUID FLAMMABLE LIQUID

Lacquer base, liquid, consists of the usual ingredients of lacquer, but with less than the usual amount of solvent or thinner. The lacquer bases require thinning with more solvent or thinner before being used.

501-3908 Rev 4 841



ECP			REV
	3700	9	F
PAGE			
	37	OF	46

DETAIL DESCRIPTION Chemical & Hazar	dous Ma	terials	REF	Hazardous Ma	terials
Emergency Response Procedure				Safety Manua	1
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald					

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away.

#### MERCURY COMPOUNDS POISON CLASS B

Mercury compounds——Practically all mercury compounds are classed as class B poisons, See Mercuric acetate to Mercury cyanide, inclusive of Commodity List, D.O.T. Regulations for these compounds.

If material on fire or involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.)

If material not on fire and not involved in fire:

Keep material out of streams and sewers.

Personnel protection:

Do not handle broken packages without protective equipment.

Do not attempt to burn without proper authorization.

Avoid breathing vapors or dusts.

Wear protective gloves and safety glasses.

Wear self-contained breathing apparatus when fighting fire.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

## METHYL ETHYL KETONE FLAMMABLE LIQUID

Methyl ethyl ketone is a clear transparent liquid that has a rather pleasant odor. It is a flammable liquid under D.O.T. Regulations. The hazard is that of flammability and for practical purposes of transportation is similar to acetone.

If material on fire or involved in fire:

Use water in large quantities. Cool all affected containers with large amounts of water.

SC1-3938 Pev 4 54.



ECP			REV
	3700	9	F
PAGE			
	38	OF	46

DETAIL DESCRIPTION Chemical & Hazar	rdous Mate	erials AEF	Hazardous Materials
Emergency Response Procedure			Safety Manual
ENGINEER	DATE	APPROVAL	DAT.E
D. E. MacDonald	ļ		

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

Personnel protection:

Wear protective gloves and safety glasses.

# NAPHTHA DISTILLATE FLAMMABLE LIQUID

Naphtha, naphtha distillage.—The term is commonly applied to petroleum distillates heavier than gasoline, but lighter than kerosene. However, the term may also be applied to other grades of petroleum distillates. Most of the material to which the term naphtha is applied is classed as a flammable liquid.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep materials out of streams and sewers.

#### NEON GAS NONFLAMMABLE COMPRESSED GAS

Neon gas is a colorless, odorless incombustible gas that is extremely stable. It is shipped in steel cylinders.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)
Cool all affected containers with large amounts of water.

SC1-3938 Rev 4 34)

Revision E Page 216



ECP		V V-2000	REV
	3700	9	F
PAGE		~~~~	
	39	OF	46

DETAIL DESCRIPTION Chemical & Haza  Emergency Response Procedure	rdous Mate	erials AE	Hazardous M Safety Manu	
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald				

## NITRIC ACID AND NITRIC ACID SOLUTIONS CORROSIVE MATERIALS

Nitric acid and nitric acid solutions are very corrosive liquids varying in concentration and color from almost water-white to red. Some nitric acids fume also if exposed to air. In addition to being corrosive as an acid, it is a very active oxidizing agent and may start fires on contact with combustible organic matter especially if such organic matter is porous and finely divided. This tendency to start fires on contact with organic matter increases with the increasing strength of acid.

The D.O.T. Regulations authorize the shipment of various strengths of nitric acid in metal and glass containers. Glass containers must be packed and cushioned in materials that do not react readily with the acid to start fires.

All strengths of nitric acid are extremely corrosive and harmful to human tissue and to many materials of commerce. In event of leakage, whether or not fire is involved, flush with large quantities of water.

If material involved in fire:

Use water in large quantities.

Cool all affected containers with large amounts of water.

Reacts with many chemicals that may cause explosion.

If material not involved in fire:

Build dikes to contain flow.
Keep material out of streams and sewers.

Personnel protection:

Do not handle broken packages without protective equipment. Avoid breathing vapors. Wear protective gloves and safety glasses. Wear self-contained breathing apparatus.

#### OXYGEN NONFLAMMABLE COMPRESSED GAS

Oxygen is a colorless, odorless, incombustible gas, commonly obtained by separation from the atmosphere or by electrolysis of water. It is shipped compressed to a pressure of approximately 2,000 lbs. per sq. inch in steel cylinders.

301-3938 Pet 4 341

Revision E Page 217



ECP			REV	
	3700	9	F	
PAGE			4	
	40	OF	46	

DETAIL DESCRIPTION Chemical & Hazardous Materials

Emergency Response Procedure

ENGINEER

DATE

DATE

DATE

DATE

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn but accelerates burning of combustible materials.)

Cool all affected containers with large amounts of water.

## PERMANGANATES, N.O.S. OXIDIZING MATERIAL

Permanganates, N.O.S. are similar in appearance and hazards to permanganate of potash.

If material involved in fire:

Use water in large quantities. Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.) Mixtures with some combustible materials may ignite spontaneously.

If material not involved in fire:

Keep material out of streams and sewers.

Personnel protection:

Wear protective gloves and safety glasses. Wash away any material which may have contacted body with copious amounts of water or soap and water.

## PETROLEUM DISTILLATE FLAMMABLE LIQUID

Petroleum distillate consists of the lighter distillates from petroleum and includes benzine and naphtha. These liquids generally have a flash point below 80°F.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

Revision E Page 218



ECP		W. O. C.	REV
***************************************		9	F
PAGE			
	41	OF	46

DETAIL DESCRIPTION Chemical & Hazardous Materials Emergency Response Procedure			_	lazardous Mat Safety Manual	
ENGINEER	DATE	APPROVAL	<u> </u>	, arce, 11011001	DATE
D. E. MacDonald					

#### PHOSGENE (DIPHOSGENE)

#### POISON CLASS A

Phosgene (Diphosgene) at ordinary temperatures is a gas which at 47°F condenses to a colorless liquid or 1.38 specific gravity. Phosgene gas is highly toxic. It is used to some extent as a dye intermediate, and has also been used as a so-called poison gas in warfare.

If material involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)
Avoid breathing fumes.
Cool all affected containers with large amounts of water.

If material not involved in fire:

Keep material out of streams and sewers.

#### Personnel protection:

Do not handle broken packages without protective equipment.

Do not attempt to burn without proper authorization.

Avoid breathing vapors or gases. Highly toxic.

Wear full protective gear including self-contained breathing equipment.

#### Evacuation:

If it appears that fire can be controlled, get away but don't evacuate—put hoses on stands, etc.

If large leakage (no fire) involved, evacuate 2500 feet.

## PHOSPHINE POISON GAS AND FLAMMABLE GAS

Phosphine is a colorless, highly toxic, flammable gas which paralyzes the olfactory senses. May be fatal if inhaled and may form explosive mixtures with air.

If material on fire or involved in fire:

Do not extinguish burning gas if flow cannot be shut off immediately. Keep all cylinders cool with large amount of water.

SC1-3938 | Rev 4 941

## UNIVAC

ECP	37009	С	REVC	
	28		44	

ENVIRONMENTAL	CONTROL F	PROCEDURE	
DETAIL DESCRIPTION	WW-9489-4	REF	
ENGINEER	DATE	APPROVAL	DATE

### CYANIDE OF POTASSIUM, LIQUID POISON CLASS B

Cyanide of potassium, liquid is a water solution of cyanide of pot-

If Material involved in Fire:

Use water in large quantities. Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Cool all affected containers with large amounts of water. If Material not Involved in Fire: Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel Protection:

Do not allow cyanides to come in contact with acids.

Wear self-contained breathing apparatus.

Do not handle broken packages without protective equipment. Do not attempt to burn without proper authorization.

Avoid breathing vapors or gases.

Wear protective gloves and safety glasses.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

#### CYANIDE OF POTASSIUM, SOLID POISON CLASS B

Cyanide of potassium, solid, is in the form of a heavy white salt. It is highly poisonous, but not otherwise dangerous. It is used in recovering precious metals, in case hardening and electro-plating.

If Material Involved in Fire:

Use water in large quantities.

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Cool all affected containers with large amounts of water.

If Material not Involved in Fire:

Keep material out of streams and sewers.

Personnel Protection

Do not allow cyanides to come in contact with acids.

Wear self-contained breathing apparatus.

Do not handle broken packages without protective equipment.

Avoid breathing dusts.

Wear protective gloves and safety glasses.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

#### CYANIDE OF SODIUM, LIQUID POISON CLASS B

Cyanide of sodium, liquid, similar in properties to cyanide of Po-



ECP			REV	The state of the s
	2700	9	F	
PAGE			<del>*</del>	
	42	OF	4	6

DETAIL DESCRIPTION Chemical & Hazar	rdous Mate	erials	REF	Hazardous Mat	erials
Emergency Response Procedure				Safety Manual	
ENGINEER	DATE	APPROVAL			DATE
D. E. MacDonald	1				

If material not on fire or not involved in fire:

Evacuate area and keep personnel upwind.

Use self-contained breathing apparatus and shut off leak if without risk.

Keep sparks and flames away.

#### Personnel protection:

Avoid breathing vapors.

Wear full protective gear including self-contained breathing equipment.

Wash away any material which may have contacted body with copious amounts of water.

Get medical attention immediately if exposed to gas.

## PHOSPHOROUS PENTAFLUORIDE NONFLAMMABLE GAS

Phosphorous Pentafluoride is a colorless, highly toxic, highly corrosive, acid

gas which is hydrolyzed by moisture to hydrogen fluoride and phosphoryl fluoride. It causes severe burns on contact with eyes, skin and mucous membranes.

If involved in fire:

Keep all cylinders cool with large amounts of water.

If not involved in fire:

Evacuate area and keep personnel upwind.

Use protective clothing and self-contained breathing apparatus and shut off leak if without risk.

#### Personnel protection:

Avoid breathing or skin contact with gas.

Wear full protective clothing and use self-contained breathing equipment.

In case of contact flush with large amount of water.

Get medical attention immediately if exposed to gas.

Apply 0.2% Zephiran Chloride to exposed skin.

#### POISONOUS LIQUIDS, N.O.S. POISON CLASS B

Try to ascertain exact content of material.

SC1-3938 Rev 4 841



ECP			REV	
		9	F	
PAGE	***		, , , , , , , , , , , , , , , , , , ,	
	43.	OF	46	

DETAIL DESCRIPTION Chemical & Hazardous Materials

Emergency Response Procedure

ENGINEER

DATE

DATE

DATE

DATE

If material on fire or involved in fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.)
Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

#### Personnel protection:

Do not handle broken packages without protective equipment. Do not attempt to burn without proper authorization. Avoid breathing vapors.

Wear full protective gear including self-contained breathing equipment.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

#### SILANE GAS FLAMMABLE GAS

Silane is a colorless, spontaneously flammable gas under pressure. It reacts violently with heavy metal halides and free halogens other than hydrogen chloride. It is very toxic.

If material on fire or involved in fire:

Fire cannot be extinguished. Shut off gas flow if without risk. Keep all cylinders cool with large amounts of water.

If material not on fire or not involved in fire:

Evacuate area and keep personnel away. Shut off leak if without risk.

## SOLVENTS, N.O.S. FLAMMABLE LIQUID

Solvents include such flammable liquids as acetone, alcohol, ether, naphtha, etc. Solvents may have flash points above or below 80°F, according to their composition. If the flash point is 80°F or below the material is classed as a flammable liquid.



ECP			REV
	3700	9	F
PAGE			
	44	OF	46

DETAIL DESCRIPTION Chemical & Hazardous Materials

Emergency Response Procedure

ENGINEER

DATE

DATE

DATE

DATE

DATE

If material on fire or involved in fire:

Use water in large quantities, water fog, dry chemical, carbon dioxide or foam.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

## SULFURIC ACID (OIL OF VITRIOL) CORROSIVE MATERIAL

Sulfuric acid (Oil of vitriol) is a heavy, oily, corrosive, odorless liquid. It varies from colorless to almost black, according to purity. Sulfuric acid will char wood or almost any organic matter on contact, but is unlikely to cause fire. It is largely used in the manufacture of chemicals, acids, fertilizers, explosives, and refining of oil. It is very corrosive and will cause serious burns on contact with the skin.

#### If material involved in fire:

Use water in large quantities from as far away as possible. Water will cause evolution of extreme heat and possibly small steam "explosives". Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Avoid breathing fumes.

#### If material not involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

#### Personnel protection:

Do not handle broken packages without protective equipment. Wear protective gloves and safety glasses. Wear full protective clothing. Wash away any material which may have contacted body with copious amounts of water or soap and water.

301-3933 Rev 4 84.



ECP		- Harris	REV		emma
	3700	19		F	
PAGE	-				
	45	ΩE		46	

- Comment of the Comm				
DETAIL DESCRIPTION Chemical &	Hazardous M	aterials	HEF	Hazardous Materials
Emergency Response Proced	ure	a brilling and a second a second and a second a second and a second a second and a second and a second and a		Safety Manual
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald	ł	1		j

## TOLUENE (TOLUOL) FLAMMABLE LIQUID

Toleune (Toluol) is a distillate from coal tar and is also made synthetically. It resembles benzol in color and appearance, but is somewhat heavier and less volatile. It is used in manufacture of explosives. It has a flash test of about 55°F.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

Personnel protection:

Wear self-contained breathing apparatus.

## TRICHLOROETHANE (METHYL CHLOROFORM) ORM-A

Trichloroethane is a colorless, heavy, liquid which is nonflammable with a mild chloroform like odor. It is moderately toxic by inhalation.

If material on fire or involved in fire:

Cool all affected containers with large amounts of water.

If material not on fire or involved in fire:

Build dikes to contain flow. Keep material out of streams and sewers.

Personnel protection:

Wear protective gloves and safety glasses. Wash promptly upon skin contact. Avoid breathing vapors.

SC1-3938 Rev 4 34)



ECP			REV
	3/00	9	F
PAGE			
	46	OF	46

DETAIL DESCRIPTION Chemical & Hazar	dous Mate	rials	REF Hazar	dous Materials
Emergency Response Procedure	Safet	y Manual		
ENGINEER	DATE	APPROVAL		DATE
D. E. MacDonald		ļ		

#### TRICHLOROETHYLENE

#### ORM-A

Trichloroethylene is a colorless liquid with a sweet odor like chloroform. It boils at 188°F and is a heavy liquid. Is highly toxic by inhalation and moderately by ingestion and skin absorption.

If material on fire or involved in fire:

Avoid fumes, gives off phosgene when burning which is highly toxic. Cool all affected containers with large amounts of water.

If material not on fire and not involved in fire:

Build dikes and contain. Avoid breathing fumes.

Personnel protection:

Wear protective gloves and safety glasses. Wash promptly upon skin contact.

## XYLENE (XYLOL) FLAMMABLE LIQUID

Xylol (xylene) is a coal tar distillate similar to toluol, but heavier and somewhat less flammable. The pure material has a flash point of 95°F and is not classed as a flammable liquid.

If material on fire or involved in fire:

Use water fog, dry chemical, carbon dioxide, or foam.

Cool all affected containers with large amount of water.

If material not on fire and not involved in fire:

Keep sparks and flames away. Build dikes to contain flow. Keep material out of streams and sewers.

Personnel protection:


Wear self-contained breathing apparatus when fighting fire.


5C1 3938 Pat 4 341

Revision E Page 224

Power Pole (iz) (ii) (si) (21) (22) (23) (24)(25)(28)(27)(28) Chemical Receiving & Freon-Shipping Dock Tank (\$) APPENDIX VII (5) (6) (7) **(0)** . 449-9 (1)(PN) (NY) (NA) Berenta[ 116) (17) 118 (19: 120) Alste "E" · (V) CONTINUATION (D) UNIVAC PLANT NO. I SCALE IN FEET Revis Page FIRST FLOOR PLAN SCALE 1" . 1'-0" DATE \_\_\_ NH. on 24A DWG. NO.\_\_\_ SECOND FLOOR PLAN PLANT ENGINEERING DEPT. (8) (લો ∧ High Potential Spill Area \* Environmental Management Ar

Fuel Oil Tanks






## UNIVAC PARK

GROUND FLOOR

- A High Potential Spill Area
- ▲ Environmental Management Area

• Drums Chemical Absorbant



## UNIVAC

ECP	3700	9 C	RE	٧.,	<u>C</u>	

PAGE	33	OF	44
	_3 _3	UE	-

ENVIRONMENTAL CONT	ROL PF	ROCEDUR		
DETAIL DESCRIPTION	***		REF	
ENGINEER	DATE	APPROVAL	W-1	DATE

fire. (Material itself does not burn.)

Cool all affected containers with large amounts of water.

Personnel Protection:

Avoid breathing vapors.

Wear protective gloves and safety glasses.

Wear full protective clothing and self-contained breathing apparatus.

## HYDROCHLORIC ACID MIXTURES CORROSIVE MATERIAL

Hydrochloric acid mixtures are liquids containing a considerable amount of hydrochloric acid mixed with water and other ingredients. Such mixtures are frequently used to clean metal or other surfaces.

If Material on Fire or Involved in Fire:

Extinguish fire using agent suitable for type of surrounding Fire. (Material itself does not burn or burns with difficulty.)

If Material not on Fire and not involved in Fire:

Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel protection:

Do not handle broken packages without protective equipment. Wear full protective clothing and self-contained breathing apparatus.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

#### HYDROGEN

#### FLAMMABLE COMPRESSED GAS

Hydrogen is a colorless flammable gas. It is compressed to high pressures and shipped in steel cylinders or in tank cars. The gas has an extremely wide flammability range.

If Material on Fire or Involved in Fire:

Approach fires of Hydrogen with extreme caution. May be highly explosive.

Do not extinguish fire unless gas flow can be stopped. Cool all affected containers with large amounts of water.

If Material not on Fire and not Involved in Fire:

Keep sparks and flames away.

Do not deliberately ignite without proper authorization. Personnel Protection:

Do not attempt to burn without proper authorization. Evacuation:

If it appears that fire can be controlled, get away but don't evacuate--put hoses on stands etc.

If large quantities involved, evacuate for radius of 2500 feet if fire becomes uncontrollable.

UD1 3938

ECP	37009	<u>C</u> F	REV	<u> </u>
PAGE	34	OF	44	

ENVIRONMENTAL CONT	TROL PR	ROCEDUR	e e e e e e e e e e e e e e e e e e e	
DETAIL DESCRIPTION		ACCIONAL CONTROL CONTR	REF	N-NO SEE GEE AND EAST AND AN AN AN AN AN AN AN AN AN AN AN AN AN
ENGINEER	DATE	APPROVAL	A	DATE

## LACQUER BASE LIQUID FLAMMABLE LIQUID

Lacuer base, liquid, consists of the usually ingredients of lacquer, but with less than the usual amount of solvent or thinner. The lacquer bases require thinning with more solvent or thinner before being used.

- If Material on Fire or Involved in Fire:
  Use water fog, dry chemical, carbon dioxide or foam.
  Cool all affected containers with large amounts of water.
- If Material not on Fire and not Involved in Fire: Keep sparks and flames away.

#### MERCURY COMPOUNDS POISON CLASS B

Mercury compounds---Practically all mercury compound are classed as class B poisons. See Mercuric acetate to Mercury cyanide, inclusive of Commodity List, D.O.T. Regulations for these compounds.

- If Material on Fire or Involved in Fire:
  Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty.)
- If Material not on Fire and not Involved in Fire: Keep material out of streams and sewers.

Personnel Protection:

Do not handle broken packages without protective equipment. Do not attempt to burn without proper authorization. Avoid breathing vapors or dusts.

Wear protective gloves and safety glasses.

Wear self-contained breathing apparatus when fighting fire.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

## METHYL ETHYL KETONE FLAMMABLE LIQUID

Methyl ethyl ketone is a clear transparent liquid that has a rather pleasant odor. It is a flammable liquid under D.O.T. Regulations. The hazard is that of flammability and for practical purposes of transportation is similar to acetone.

If Material on Fire or Involved in Fire:
Use water in large quantities
Cool all affected containers with large amounts of water.

If Material not on Fire and not Involved in Fire:
Keep sparks and flames away.
Build dikes to contain flow.
Keep material out of streams and sewers.

ECP	37009℃	REV. C

Ρ	Α	G	E	35	OF	44

ENVIRONMENTAL C	CONTROL	PROCEDURE	
DETAIL DESCRIPTION		REF	
ENGINEER	DATE	APPROVAL	DATE

Personnel Protection:
Wear protective gloves and safety glasses.

#### NAPHTHA NAPHTHA DISTILLATE FLAMMABLE LIQUID

Naphtha, naphtha distillage. -- The term is commonly applied to petroleum distillates heavier than gasoline, but lighter than kerosene. However, the term may also be applied to other grades to petroleum distillates. Most of the material to which the term naphtha is applied is classed as a flammable liquid.

If Material on Fire or Involved in Fire:
Use water fog, dry chemical, carbon dioxide or foam.

If Material not on Fire and not Involved in Fire:
Keep sparks and flames away.
Build dikes to contain flow.
Keep material out of streams and sewers.

### NEON GAS NONFLAMMABLE COMPRESSED GAS

Neon gas is a colorless, odorless incombustible gas that is extremely stable. It is shipped in steel cylinders.

If Material Involved in Fire:
Entinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)
Cool all affected containers with large amounts of water.

## NITRIC ACID AND NITRIC ACID SOLUTIONS CORROSIVE MATERIALS

Nitric acid and nitric acid solutions are very corrosive liquids varying in concentration and color from almost water-white to red. Some nitric acids fume also if exposed to air. In addition to being corrosive as an acid, it is a very active oxidizing agent and may start fires on contact with combustible organic matter especially if such organic matter is porous or finely divided. This tendency to start fires on contact with organic matter increases with the increasing strength of acid.

The D.O.T. Regulations authorize the shipment of various strengths of nitric acid in metal and glass containers. Glass containers must be packed and cushioned in materials that do not react readily with the acid to start fires.

All strengths of nitric acid are extremely corrosive and harmful to human tissue and to many materials of commerce. In event of leak-

ECP	37009	C	REV	~ ~
PAGE	36	OF_	44	

ENVIRONMENTAL		= : :
DETAIL DESCRIPTION	TO THE THE THE THE THE THE THE THE THE THE	IREE

DETAIL DESCRIPTION

ENGINEER

DATE APPROVAL

age, whether or not fire is involved, flush with large quantities of water.

If Material Involved in Fire:

Use water in large quantities.

Cool all affected containers with large amounts of water. Reacts with many chemicals that may cause explosion.

If Material not Involved in Fire:

Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel protection:

Do not handle broken packages without protective equipment.

Avoid breathing vapors.

Wear protective gloves and safety glasses.

Wear self-contained breathing apparatus.

#### OXYGEN

#### NONFLAMMABLE COMPRESSED GAS

Oxygen is a colorless, odorless, incombustible gas, commonly obtained by separation from the atmosphere or by electrolysis of water. It is shipped compressed to a pressure of approximately 2,000 lbs. per sq. inch in steel sylinders.

If Material Involved in Fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn but accelerates burning of combustible materials.)

Cool all affected containers with large amounts of water.

#### PERMANGANTAES, N.O.S. OXIDIZING MATERIAL

Permanganates, N.O.S. are similar in appearance and hazards to permanganate of potash.

If Material Involved in Fire:

Use water in large quantities,

Extinguish fire using agent suitable for type of surrounding

fire. (Material itself does not burn.)

Mixtures with some combustible materials may ignite

spontaneously.

If Material not Involved in Fire:

. Keep material out of streams and sewers.

Personnel protection:

Wear protective gloves and safety glasses.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

ECP	37009C	REV	Ċ
	3 3		4

2 ^	GΕ	3 <i>7</i>	0.5	4.	4
-μ	JE		OF.		7

ENVIRONMENTAL C	ONTROL P	ROCEDURE	And the state of t
DETAIL DESCRIPTION		REF	
ENGINEER	DATE	APPROVAL	DATE

#### PETROLEUM DISTILLATE FLAMMABLE LIQUID

Petroleum distillate consists of the lighter distillates from petroleum and includes benzine and naphtha. These liquids generally have a flash point below 80°F.

If Material on Fire or Involved in Fire: Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water.

If Material not on Fire and not Involved in Fire: Keep sparks and flames away. Build dikes to contain flow.

Keep material out of streams and sewers.

### PHOSGENE (DIPHOSGENE) POISON CLASS A

Phosgene (Diphosgene) at ordinary temperatures is a gas which at 47°F. condenses to a colorless liquid or 1.38 specific gravity. Phosgene gas is highly toxic. It is used to some extent as a dye intermediate, and has also been used as a so-called poison gas in warfare.

If Material Involved in Fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

Avoid breathing fumes.

Cool all affected containers with large amounts of water.

If Material not Involved in Fire:

Keep material out of streams and sewers.

Personnel Protection:

Do not handle broken packages without protective equipment. Do not attempt to burn without proper authorization. Avoid breathing vapors or gases. Highly toxic!

Wear full protective gear including self-contained breathing equipment.

#### Evacuation:

If it appears that fire can be controlled, get away but don't evacuate--put hoses on stands, etc. If large leakage (No fire) involved, evacuate 2500 feet.

#### PHOSPHINE

#### POISON GAS AND FLAMMABLE GAS

Phosphine is a colorless, highly toxic, flammable gas which paralyzes the olfactory senses. May be fatal if inhaled and may form explosive mixtures with air.

If Material on Fire or Involved in Fire:

Do not extinguish burning gas if flow cannot be shut off immediately.

UNIVAC

ECP_	37009C	REV	<u>C</u>
	, .		

Δ	GΕ	38	OΕ	44
•			$\sim$	

	ENVIRONMENTAL CON	TROL	PROCEDUR			
	DETAIL DESCRIPTION		Tilden and an analysis of the state of the s	REF	THE ANDREASE OF THE STREET OF	Addistant and a second a second and a second a second and
***************************************	ENGINEER	DATE	AFPROVAL	**************************************		DATE

Keep all cylinders cool with large amount of water.

If Material not on Fire or not Involved in Fire:

Evacuate area and keep personnel upwind.

Use self-contained breathing apparatus and shut off leak if without risk.

Keep sparks and flames away.

Personnel Protection

Avoid breathing vapors.

Wear full protective gear including self-contained breathing equipment.

Wash away any material which may have contacted body with copious amounts of water.

Get medical attention immediately if exposed to gas.

#### PHOSPHOROUS PENTAFLUORIDE NONFLAMMABLE GAS

Phosphorous Pentafluoride is a colorless, highly toxic, highly corrosive, acid gas which is hydrolyzed by moisture to hydrogen fluoride and phosphoryl fluoride. It causes severe burns on contact with eyes, skin and mucous membranes.

If Involved in Fire:

Keep all cylinders cool with large amounts of water.

If not Involved in Fire:

Evacuate area and keep personnel upwind.

Use protective clothing and self-contained breathing apparatus and shut off leak if without risk.

Personnel Protection

Avoid breathing or skin contact with gas.

Wear full protective clothing and use self-contained breathing equipment.

In case of contact flush with large amounts of water. Get medical attention immediately if exposed to gas. Apply 0.2% Zephiran Chloride to exposed skin.

#### POISONOUS LIQUIDS, N.O.S. POISON CLASS B

Try to ascertain exact content of material.

If Material on Fire or Involved in Fire:

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn or burns with difficulty Cool all affected containers with large amounts of water.

If Material not on Fire and not Involved in Fire:

Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel Protection:

Do not handle broken packages without protective equipment. Do not attempt to burn without proper authorization.

PAGE	39	OF	44
1706		1.77"	

ENVIRONMENTAL	CONTROL PROCEDURE			
DETAIL DESCRIPTION		VAIII001110	REF.	
ENGINEER	DATE	APPROVAL		DATE

Avoid breathing vapors.

Wear full protective gear including self-contained breathing equipment.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

### <u>SILANE GAS</u> FLAMMABLE GAS

Silane is a colorless, spontaneously flammable gas under pressure. It reacts violently with heavy metal halides and free halogens other than hydrogen chloride. It is very toxic.

If Material on Fire or Involved in Fire:

Fire cannot be extinguished. Shut off gas flow if without risk.

Keep all cylinders cool with large amounts of water.

If Material not on Fire or not Involved in Fire: Evacuate area and keep personnel away. Shut off leak if without risk.

### SOLVENTS, N.O.S. FLAMMABLE LIQUID

Solvents include such flammable liquids as acetone, alcohol, ether, naphtha, etc. Solvents may have flash points above or below 80°F., according to their composition. If the Flash point is 80°F. or below the material is classed as a flammable liquid.

If Material on Fire or Involved in Fire:

Use water in large quantities, water fog, dry chemical, carbon dioxide or foam.

If Material not on Fire and not Involved in Fire:
Keep sparks and flames away.
Build dikes to contain flow.
Keep material out of streams and sewers.

## SULFULIC ACID (OIL OF VITRIOL) CORROSIVE MATERIAL

Sulfuric acid (Oil of vitriol) is a heavy, oily, corrosive, odorless liquid. It varies from colorless to almost black, according to purity. Sulfuric acid will char wood or almost any organic matter on contact, but is unlikely to cause fire. It is largely used in the manufacture of chemicals, acids, fertilizers., explosives, and in refining of oil. It is very corrosive and will cause serious burns on contact with the skin.

If Material Involved in Fire:

Use water in large quantities from as far away as possible. Water will cause evolution of extreme heat and possibly small steam "explosives".

## UNIVAC

ECP	370	<u>09C</u> f	RÉV	C
		•		
PAGE_	40	OF	44	

DATE

ENVIRONMENTAL	CONTROL	PROCEDURE
TO THE RESERVE OF THE PARTY OF	70-700	

DETAIL DESCRIPTION REF

ENGINEER

Extinguish fire using agent suitable for type of surrounding fire. (Material itself does not burn.)

APPROVAL

Avoid breathing fumes.

If Material not Involved in Fire:

Build dikes to contain flow.

Keep material out of streams and sewers.

DATE

Personnel Protection:

Do not handle broken packages without protective equipment Wear protective gloves and safety glasses.

Wear full protective clothing.

Wash away any material which may have contacted body with copious amounts of water or soap and water.

### TOLUENE (TOLUOL) FLAMMABLE LIQUID

Toleune (Toluol) is a distillate from coal tar and is also made synthetically. It resembles benzol in color and appearance, but is somewhat heavier and less volatile. It is used in manufacture of explosives. It has a flash test of about 55°F.

If Material on Fire or Involved in Fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amounts of water. .

If Material not on Fire and not Involved in Fire:

Keep sparks and flames away.

Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel Protection:

Wear self-contained breathing apparatus.

### TRICHLOROETHANE (METHYL CHLOROFORM) ORM-A

Trichloroethane is a colorless, heavy, liquid which is nonflammable with a mild chloroform like odor. It is moderately toxic by inhalation.

If Material on Fire or Involved in Fire:

Cool all affected containers with large amounts of water.

If Material not on Fire and not Involved in Fire:

Build dikes to contain flow.

Keep material out of streams and sewers.

Personnel Protection:

Wear protective gloves and safety glasses.

Wash promptly upon skin contact.

Avoid breathing vapors.

:D1-3938



ECP	37009	C	REV.	C
		,		***************************************

PAGE	41	0.E	44
		•	

ENVIRONMENTAL CON	TROL	PROCEDURE		
DETAIL DESCRIPTION		R	EF :	
ENGINEER	DATE	APPROVAL		DATE

## TRICHLOROETHYLENE ORM-A

Thichloroethylene is a colorless liquid with a sweet odor like chloroform. It boils at 1880F. and is a heavy liquid. Is highly toxic by inhalation and moderately by ingestion and skin absorption.

If Material on Fire or Involved in Fire:

Avoid fumes, gives off phosgene when burning which is highly toxic.

Cool all affected containers with large amounts of water.

If Material not on Fire and not Involved in Fire:

Build Dikes and contain

Avoid breathing fumes.

Personnel Protection:

Wear protective gloves and safety glasses. Wash promptly upon skin contact.

#### XYLENE (XYLOL) FLAMMABLE LIQUID

Xylol (xylene) is a coal tar distillate similar to toluol, but heavier and somewhat less flammable. The pure material has a flash point of  $95^{\circ}F$ . and is not classed as a flammable liquid.

If Material on Fire or Involved in Fire:

Use water fog, dry chemical, carbon dioxide or foam. Cool all affected containers with large amount of water


If Material not on Fire and not Involved in Fire:

Keep sparks and flames away.

Build dikes to contain flow. Keep material out of streams and sewers.

Personnel Protection:


Wear self-contained breathing apparatus when fighting fire.





 $\triangle$  High Potential Spill Area

Drums Chemical Absorbant

<sup>▲</sup> Environmental Management Area







APPENDIX G-2

LETTER EAGAN FIRE DEPARTMENT

SPERRY CORPORATION COMPUTER SYSTEMS SPERRY PARK, P.O. BOX 43525 ST. PÁUL, MINNESOTA 55164-0525 TELEPHONE (612) 456-2222

July 17, 1984

Chief Administrator Divine Redeemer Hospital 724 19 Avenue North So. St. Paul, MN

Dear Sir:

Enclosed is a copy of our revised Chemical and Hazardous Material Emergency Response procedure (Contingency Plan) to be used in the event of a chemical spill, chemical fire or other incidents involving hazardous materials.

This plan covers our facilities located at 2751 Shepard Road, 1902 Minnehaha Avenue in St. Paul, and 3333 Pilot Knob Road in Eagan.

If you have any questions or would like to review our chemical storage area give me a call at 456-4654 so we can arrange a convenient time.

Sincerely,

SPERRY

Roger/J: Martin

Manager

Envi'ronmental Management

SPERRY CORPORATION COMPUTER SYSTEMS SPERRY PARK, P.O. BOX 43525 ST. PAUL, MINNESOTA 55164-0525 TELEPHONE (612) 456-2222

July 17, 1984

Police Chief City of Eagan 3800 Pilot Knob Rd. Eagan, MN 55121

Dear Sir:

Enclosed is a copy of our revised Chemical and Hazardous Material Emergency Response procedure (Contingency Plan) to be used in the event of a chemical spill, chemical fire or other incidents involving hazardous materials.

This plan covers our facility located at 3333 Pilot Knob Road, Eagan, MN.

If you have any questions or would like to review our chemical storage area, give me a call at 456-4654 so we can arrange a convenient time.

Sincerely,

SPERRY

Roger J. Martin

Mariager

Environmental Management

SPERRY CORPORATION COMPUTER SYSTEMS SPERRY PARK, P.O. BOX 43525 ST. PAUL, MINNESOTA 55164-0525 TELEPHONE (612) 456-2222

July 17, 1984

Fire Chief City of Eagan Eagan Fire Department 3800 Pilot Knob Road Eagan, MN 55121

Dear Sir:

Enclosed is a copy of our revised Chemical and Hazardous Material Emergency Response procedure (Contingency Plan) to be used in the event of a chemical spill, chemical fire or other incidents involving hazardous materials.

This revised plan supercedes the one we provided to your department in September, 1982. The previous plan should be discarded.

This plan covers our facilities located at 3333 Pilot Knob Road.

Sincerely,

**SPERRY** 

Roger J. Martin

Manader

Environmental Management



UNIVAC PARK, P.O. BOX 3525 SY. PAUL, MINNESOTA 55165 TELEPHONE (612) 456-2222

September 8, 1982

Chief
Eagan Fire Department
City of Eagan
3795 Pilot Knob Rd.
Eagan, MN 55121

Dear Sir:

For your use, we are submitting a copy of the Emergency Response Procedure we use for the Univac DSD facilities in the Twin City area, for responding to chemical spills.

Information on our Univac Park facility is included in this procedure.

If you have any questions on the procedure or if you would want to tour our facility, please call me at 456-4654.

Sincerely,

SPERRY UNIVAC

Roger J. Martin

Mánagér

Environmental Management

APPENDIX G-3

MEDICAL EMERGENCY PROCEDURES

#### ORGANIZATION AND STAFFING

1. Dr. John A. Williams, Company Physician.

Margie Ann Kirby, Medical Department Manager Report to the Personnel Department

- 2. The Physician's responsibilities are:
  - a. Performance and supervision of preplacement exam.
  - Evaluating and returning employees to work after medical absences.
  - Establishing standing medical directives.
  - d. Advice and consultation.
- 3 Physician Hours:
  - a. Plant 1 Daily 12:30 PM to 1:30 PM.
  - b. Plant 8 Friday 11:30 12 Noon.
- 4. Nurse Staff Hours are:
  - a. Shepard Road Helen Sigmeth, R.N. 7:00 AM to 3:30 PM
    Helen Cartford, R.N. 7:00 AM to 3:30 PM
    Beverly Plum, R.N. 3:30 PM to 12:00 Midnight
  - b. Midway Mary Jane Hedlund, R.N. 7:30 AM to 4:00 PM
  - c. Univac Park Thelma Blakkestad, R.N. 8:00 AM to 4:30 PM
  - d. Corporate Square Phyllis Martin, R.N. 7:00 AM to 3:30 PM.
- 5. Company Physician:
  Dr. John A. Williams
  Midway Family Physicians
  1690 University Park Medical Building
  Suite 370
  St. Paul, Minnesota 55104
  Telephone: 645-9477
  Private Office: 645-8624
  - a. His Associates are: Dr. Ken Lerdahl Dr. Robert Baker Dr. Ron Otremba
  - b. Consultant Physicians: See Listings

#### MEDICAL DIRECTIVES

Medical Directives are written procedures, approved and signed by the physician who has been designated by management as the physician responsible for the medical direction of the employee health program. Medical Directives serve as the medical authorization for the registered professional nurse in giving emergency care to employees for occupational and non-occupational injuries and illnesses. These are developed jointly by the physician and nurse. Review, updating and reapproval are recommended at least yearly or when procedures change.

# MEDICAL DIRECTIVES AND NURSING PROCEDURES Emergency Situations

The Occupational Health Nurse must be able to act in any emergency situation. The nurse is expected to have professional competence and skill and use good judgement at all times.

#### General Principles Applicable in All Emergency Situations:

- 1. Act promptly
- 2. Think clearly
- 3. Do first things first
- 4. Practice within the scope of the State Nurse Practice where employed.

#### General Procedures Applicable in Emergency Situations:

- 1. Maintain open airway, breathing and circulation.
- 2. Control bleeding.
- 3. Call paramedic ambulance-service
  - a. Plant 1 & 2 St. Paul Paramedics 911
  - b. Plant 8 & Corporate Square Divine Redeemer Ambulance - 455-9609
- 4. Call a physician.
- 5. Prevent and treat for shock (see shock).
- 6. Prevent infection and further injury.
- 7. Provide the physician with history and assessment findings.
- Arrange for follow-up care and record all pertinent data.

#### Additional Medical Directives Applicable in All Emergency Situations:

- 1. Oxygen (flow to be determined by nurse) may be used prn.
- 2. Transport all emergencies to Hospital of Choice, St. Paul Ramsey Hospital or Divine Redeemer Hospital.
- 3. Cardiac Arrest emergencies are transported to St. Paul Ramsey or Divine Redeemer Hospital.
- 4. All work related emergencies are transported to Midway
  Hospital for Shepard Road and Midway Facility, Divine
  Redeemer Hospital for Eagan and Corporate Square Facility.
  (This includes chemcial spills, etc.)

# MEDICAL DIRECTIVES AND NURSING PROCEDURES OTHER SITUATIONS

#### General Procedures Applicable in Other Situations:

- 1. Make a nursing assessment.
- 2. Record the history and nursing assessment findings.
- 3. Take vital signs on all persons, TPR and BP.
- 4. Chronic or recurring disorders should be referred to the employee's physician.
- 5. When referring an employee (at his request) to a physician or dentist, always present more than one name. (See Professional Referral Pages)
- 6. If an employee requests the nurse to give injections or medications which have been prescribed by his/her own physician, the nurse may do so, providing the employee's physician requests this in writing and submits the patient's diagnosis. This order then must be approved by the physician in charge of the Health Service. This does not include allergy shots.
- 7. The Medical Department shall provide necessary emergency care for non-occupational injuries and refer the employee to his/her personal physician for definitive treatment.
- 8. STANDING ORDER DRUG TREATMENT IS AS FOLLOWS:
  - a. Aspirin, Tylenol, Anacin and Bufferin may be used at the nurse's discretion.
  - b. ALWAYS check for allergies, past medical and health problems, or contraindictions for use before giving any medication.
  - c. Do not give more than TWO doses of any medication during an eight hour shift.
  - d.' Most minor problems should not be treated for more than TWO days. See specific condition in procedures.
  - e. An employee must be evaluated in the Medical Department before receiving any medications.
- When physician consult is needed, call Company M.D., Dr. J. A. Williams, if employee has no private physician or proviate M.D. is not available.

RECOMMENDATIONS: Call employee's physician when symptoms are unusual, (fainting, acute, or when employee is pregnant) and more than mild transitory problem, i. e. URI, flu.



SPERRY CORPORATION COMPUTER SYSTEMS SPERRY PARK, P.O. BOX 43525 ST. PAUL, MINNESOTA 55164-0525 TELEPHONE (612) 696-4242

Rev. 10 Oct, 1983

To: Midway Hospital Emergency Rooms
Divine Redeemer Hospital Emergency Rooms

Re: Hydrofluoric Acid Burns

All hydrofluoric acid burns greater than 65 square centimeters in diameter should be admitted to the hospital with continuous cardiac monitoring with particular reference to the QT interval. Blood gases and serum electrolytes should be drawn with special reference to calcium and magnesium. Intravenous Calcium Gluconate (1 gram) with N/S should be started with continuous IV drip on all cases with EKG changes. Contact Company Physician for continuing follow-up orders:

Dr. John A. Williams
Midway Family Physicians
1690 University Park Medical Building
Suite 370
St. Paul, Minnesota 55104
Telephone: 645-9477 Night & Day

The following orders should have been completed at the plant before transportation to hospital:

- Remove clothing if involved to prevent inhalation of fumes and vapors.
- 2. Continuous irrigation with water for 20 minutes.
- 3. Application of Magnesium Oxide to neutralize the toxic fluoride ion.
- 4. Numbers 2 and 3 must be completed before transportation to hospital. This step is critical.
- 5. Paramedics to continue EKG monitoring during transportation.
- 6. Determine concentration of acid, if possible.

Hudrofluoric Acid Burns - Page 2

All cases where the employee has been exposed to Hydrofluoric vapors in large concentrations and/or over a four hour period of time should be treated in the same manner at the Emergency Room. Oxygen at 7 liters per minute, should be administered at descretion of nurse in charge and should be continued during period of transportation to the hospital.

These orders apply only to Sperry Computer System Employees.

Dr. John A. Williams Company Physician

JAW/dn

# MEDICAL DIRECTIVES AND NURSING PROCEDURES FOR EMERGENCY CARE OF OCCUPATIONAL AND NON-OCCUPATIONAL INJURIES AND ILLNESSES

NAME AND ADDRESS OF COMPANY
SPERRY COMPUTER SYSTEMS, DSD
UNIVAC PARK, P.O. BOX 64525
ST. PAUL, MINNESOTA 55164-0525

NAME AND ADDRESS OF PHYSICIAN

DR. JOHN WILLIAMS

TELEPHONE: 645-9477

1690 UNIVERSITY PARK MEDICAL BUILDING

SUITE 370

ST. PAUL, MINNESOTA 55104

NAME OF NURSE IN CHARGE

MARGIE KIRBY, MANAGER

HEALTH AND MEDICAL SERVICES

NAMES OF STAFF NURSES

Thelma Blakkestad; Helen Cartford; Mary Jane Hedlund;

Phyllis Martin; Beverly Plum and Helen Sigmeth

APPROVED:	Jawilliams M.D.	
~ 1- 3-83		D.
Date	Signature	
REVIEWED AND UPDATED:	Lawilliams MD.	
13-18-83 Date		D.
Date	Signature	
		D.
Date	Signature	
	M	.D.
Date	Signature	1

#### PERSONNEL TRAINING

The information contained in this section outlines the personnel training for Sperry, Computer Systems, Shepard Road haszardous waste storage facility in accordance with the requirements of 40 CFR 122.25(a)(12) and 264.16 and 270.14(a)(12). The Department Manager is responsible for reviewing all training requirements and insuring an annual review for all personnel in the Environmental Management Department that are responsible for handling hazardous waste in any manner.

#### H-1 JOB TITLES AND DUTIES

Figure H-1 (Page 250) shows the organization of Sperry's Environmental Management Group that handles our hazardous waste. There are six employees directly responsible for handling hazardous waste at the Sperry Park facility.

There are four additional people in our group that indirectly support the Sperry Park facility. There is also many other people within the company that support us including: hazardous waste coordinators for each chemical using department, security guards, move crew, facility maintenance, and truck drivers. All personnel receive training. Appendix H-1 (Page 251) describes the objectives, responsibilities, education and experience required for each of our job descriptions.

#### H-2 TRAINING


Each employee within the Environmental Management Department receives formal training through Professional Organizations established to provide the type of training required by regulations. Additional training is provided as changes occur in the regulations and a general review is provided at least once a year. This training is provided by Department Manager and Supervisors. Training records are kept in the files of the Department Manager.

Technicians are required to read all of the procedures and receive on the job training. After several months of training they sign off on a training record Appendix H-3 (Page 283). Before an employee is allowed to sign off shipping papers, they receive formalized classroom instructions, see Appendix H-3.

(Page 283) for certificates. Appendix H-4 through H-8 (Pages 298-387) describes training sessions Environmental management personnel give to support groups: hazardous waste coordinators, move crew, guards and truck drivers. These sessions are updated and presented yearly. Included are the sign off sheets of personnel receiving training.

#### H-3 EMERGENCY RESPONSE TRAINING

Appendix H-8 (Page 376) describes emergency response training Sperry has completed with sign off sheets of personnel participating.



#### APPENDIX H-1

ENVIRONMENTAL MANAGEMENT POSITION DECRIPTION

TITLE Environmental Management Technician B

MAJOR ORG. Defense Systems Division

DATE June 1979

MAJOR ORG. COMPONENT Industrial Relations & Services

LOCATION St. Paul

P.D. NO. 205670

REPORTS TO Environmental Management

EXEMPT NON-EXEMPT

Supervisor

#### Accountability Objectives:

Assists in the operation of all equipment used by the Environmental Management Group for complying with environmental regulations.

#### Principle Responsibilities:

- Assist in the operation and maintenance of all equipment used for waste treatment, including deionizing systems, fume scrubbers, sampling and test equipment.
- Take corrective action when necessary to insure that the equipment and instrumentation operated by the Environmental Management Group is properly maintained.
- Assist in the preparation of hazardous wastes for shipment according to established procedures.
- 4. Be familiar with the processes and operations of the departments which the Environmental Management Group provides services for. Initiate corrective actions when problems occur.
- 5. Assist in the housekeeping of the areas assigned.

#### Education and Experience:

Two years of college or technical school Environmental Technology, Chemistry, or equivalent education plus typically 0-1 year experience or equivalent education, training, and/or related work experience.

Name of Employees: Scot R. Sokola

Greg P. Weisjahn

TITLE ENVIRONMENTAL MANAGEMENT TECHNICIAN A

MAJOR ORG. Defense Systems Division

DATE June 1979

MAJOR ORG. COMPONENT As Assigned

LOCATION St. Paul

P.D. NO. 205669

REPORTS TO Environmental Management Supervisor

EXEMPT NON-EXEMPT X

#### Accountability Objectives:

Performs duties requiring practical knowledge and experience, assists in training subordinate technicians, and assists in the design, development, and problem analysis of the operational functions of the Environmental Management Department.

#### Principle Responsibilities:

 May perform all duties of lower classified technicians, direct the work and maintain or assist in training them as required.

 Operate all equipment used for waste treatment including deionizing systems, fume scrubbers, sampling and test equipment.

3. Provide routine maintenance of equipment to insure proper operation.

4. Assist with the design of systems to insure compliance with all environmental regulations.

5. Be knowledgeable of the hazardous material shipping regulations and be able to prepare hazardous materials for shipment according to established procedures.

6. Assist in clean up procedures in the event of a hazardous material

spill.

7. Responsible for presenting data and information required in system designs for equipment or procedure changes and updates.

8. Assist in housekeeping of the assigned areas.

#### Education and Experience:

Two years of college or technical school Environmental Technology, Chemistry, or equivalent education plus typically 2-5 years related experience or equivalent education, training and/or related work experience.

Name of Employees: Gregory A. Grinols Michael C. Medina William M. Polta



TITLE Environmental Management Engineering Assistant

MAJOR ORG. Defense Systems Division

DATE June 1979

MAJOR ORG. COMPONENT Industrial Relations and Services

LOCATION St. Paul

P.D. NO. 205668

REPORTS TO Environmental Management

Supervisor

EXEMPT NON-EXEMPT

#### Accountability Objectives:

Under minimal supervision, performs duties requiring practical knowledge and experience, trains subordinate technicians, and assists engineers in system design, development, documentation, procurement, and problem analysis of the operational functions of the Environmental Management Group.

#### Principle Responsibilities:

- Responsible for the operation, maintenance, repair, test, and calibration of all equipment and instrumentation used for the operation of waste treatment systems, including deionizing systems, fume scrubbers, sampling and test equipment.
- 2. Trains and provides technical assistance and directs the work activity of assigned subordinate technicians.
- Solves or finds solutions to problems relating to the operation of waste treatment systems and all other areas which could be a potential pollution problem.
- 4. Acquires and records data required to determine the need for new or revised systems or procedures, and generates the necessary drawings, lay outs, etc.
- 5. Analyzes and recommends methods of improving the efficiency of all the systems for which the Environmental Management Group is responsible.
- 6. Maintain close liaison with all departments that use the services of the Environmental Management Group and coordinate the activities relating to these operations.
- 7. Maintains records required as part of the regulations of the various government agencies relating the environmental control.
- 8. May perform duties of lower classifications as required.

#### Education and Experience:

Two years of college or technical school Environmental Technology, Chemistry, or equivalent education plus typically 5-7 years related experience or equivalent education, training and/or related work experience.

Name of Employees: Roger A. Ranzau

PAGE 3 OF 10

TITLE ENVIRONMENTAL MANAGEMENT SPECIALIST

MAJOR ORG. Defense Systems Division

DATE June 1979

MAJOR ORG. COMPONENT As Assigned

LOCATION St. Paul

P.D. NO. 205667

REPORTS TO Environmental Management Supervisor

EXEMPT NON-EXEMPT

#### Accountability Objectives

Performs technical work of a complex nature related to system design and development, documentation, procurement and installation of the system whether it is related to equipment or a procedure.

#### Principle Responsibilities:

- 1. Participates in the design and development of processes and procedures to insure compliance with all environmental regulations that affect the operation of the facilities.
- 2. Analyszes and recommends methods of improving the performance of an operation.
- Assists in the estimating of project costs, time schedules, personnel, and material requirements.
- 4. Prepares technical and progress reports on assignments.
- 5. Directs the work of technicians assigned and may train or assist training them as required.
- 6. Maintains liaison with other groups as required to complete assignments.
- 7. Must be knowledgeable about all pertinent environmental regulations.
- 8. Assist in clean up procedures in the event a hazardous material spill.
- 9. Assist with housekeeping in the assigned areas.

#### Education and Experience:

Two years of college or technical school Environmental Technology, Chemistry, or equivalent education plus typically 7 or more years related experience or equivalent education, training and/or related experience.

TITLE ENVIRONMENTAL MANAGEMENT ENGINEER, ASSOCIATE

MAJOR ORG. Defense Systems Division

DATE June 1979

MAJOR ORG. COMPONENT As Assigned

LOCATION St. Paul

P.D. NO.

REPORTS TO As Assigned

EXEMPT X NON-EXEMPT

#### Accountability Objective:


Assists other professional personnel through performance of assignments or experiments of limited scope and difficulty in the analysis of processes and procedures and is responsible for the completion of assigned tasks in an efficient and technically competent manner.

#### Principle Responsibilities:

- 1. Performs technical work of minor professional difficulty in the field of Environmental Management, including process control. Makes use of standard apparatus, methods and techniques. Evaluates and tests for conformance to specifications, reproducibility and economy.
- 2. Assists in the analysis of materials or data which may require the application of modified or nonstandard procedures under the guidance of immediate supervisor.
- 3. Evaluates data and prepares technical reports, and maintains log book on the progress of assigned duties.
- 4. May direct the technical work of technicians and other assistants and may train or assist in their training.
- 5. Maintain liason with other personnel to aid in the completion of assigned duties.
- 6. Must be knowledgeable of all pertinent environmental regulations.
- 7. Keep the department manager aware of any operational or housekeeping deficiencies.

#### Education and Experience:

Degree in Environmental Technology, Chemistry or equivalent education, plus typically 0-2 years related experience or equivalent education, training and/or related work experience.



TITLE Environmental Management Engineer

Defense Systems Division MAJOR ORG.

March 1980 DATE

MAJOR ORG. COMPONENT

As assigned

LOCATION

St. Paul

P.D. NO.

REPORTS TO

As assigned

EXEMPT NON-EXEMPT

#### ACCOUNTABILITY OBJECTIVE

Performs research and/or development assignments of normal scope and difficulty in the development of new or improved processes. Some evaluation, originality, or ingenuity is required.

#### ACCOUNTABILITIES

- 1. Performs technical work in the field of environmental engineering using both standard and nonstandard methods, techniques, and procedures to conduct investigations or applied research. Evaluates and tests for conformance to specifications, reproducibility and economy.
- 2. Analyzes problems and conducts investigations on environmental control process problems. Recommends methods of improving efficiency of operations. Assists in the planning of new projects by giving appraisals through the supervisor of developments or techniques in which the incumbent is particularly experienced.
- 3. Assists in the preparation of cost estimates, time schedules, personnel, facilities, and material requirements.
- 4. Prepares technical reports on assigned programs. May edit the reports of professionals assigned. Maintains engineering log book.
- 5. May exercise technical work direction over one or more assigned.
- Works in close liaison with other organizations to exchange needed information concerning problems with process control systems which directly affect environmental control.
- Should be familiar with government regulations and their application in the field of environmental engineering.

#### EDUCATION AND EXPERIENCE

Applicable degree or equivalent plus typically 2-5 years related experience, or equivalent education, training and/or related work experience.

Name of Employee: Mark E. Wilson

PAGE 6 OF 10

# SPERRYSLUNIVAC

#### POSITION DESCRIPTION

TITLE Senior Environmental Management Engineer

MAJOR ORG. Defense Systems Division

DATE April 1983

MAJOR ORG. COMPONENT Facilities Resources

LOCATION St. Paul

P.D. NO. 202122

REPORTS TO Manager of Environmental EXEMPT 🔀 NON-EXEMPT 🗌

Management Department

#### Accountability Objective

Plans and performs research and development assignments in the experimentation, design and/or analysis of new or improved materials or processes. Assignments are broad in nature, requiring appreciable originalit and ingenuity. Supervise individuals activities of those assigned to the incumbent.

#### <u>Accountabilities</u>

- Analyzes and formulates original techniques. Implements procedures and methods to ensure compliance with environmental regulations.
- Plans, organizes coordinates, and supervises the activities of those subordinates assigned.
- Prepares or assists in the preparation of cost estimates, time schedules, personnel and material requirements for the installation of equipment needed for meeting environmental regulations or for cost saving techniques.
- Prepares required technical and progress reports and maintains own log book and sees that log books and check lists of assigned personnel are properly maintained.
- Familiarizes and trains employees in the technical objectives 5. including local, state and federal regulation requirements.
- Maintains a close liaison with other departments, consulting and advising with respect to environmental management concerns.
- 7. Be knowledgeable of government regulations that affect the operations of Sperry.
- Insures that the area of operation under the supervision of the incumbent is in compliance with all applicable government regulations and company policies relating to environmental management.

#### Education and Experience

B. S. Degree in Environmental Technology, Chemistry or equivalent, plus five years related experience.

Name of Employee: Dan E. MacDonald

TITLE ENVIRONMENTAL MANAGER

MAJOR ORG. DEFENSE SYSTEMS DIVISION

DATE FEBRUARY 1983

MAJOR ORG. COMPONENT RESOURCES MANAGEMENT

FACILITIES MANAGEMENT

LOCATION ST. PAUL

P.D. NO.

REPORTS TO DIRECTOR, FACILITIES

RESOURCES

EXEMPT NON-EXEMPT

#### ACCOUNTABILITY OBJECTIVE:

This position is responsible for the management of the Environmental Management Department. As such, this responsibility encompasses the operational, functional, and regulatory management of all chemical and utility processes used in the development and manufacture of products and facility use for the Defense Systems Division and tenants such as the Semiconductor Division.

#### DIMENSIONS:

#### FINANCIAL:

The annual operating budget for the environmental section is approximately \$1,125,000. Our manufacturing, engineering, and Semiconductor operation is dependent on this group for the treatment and disposal of all chemical waste which is instrumental in enabling the manufacture of over \$300,000,000 of product each year and for the operation of equipment to produce high purity water required for the production of Semiconductors.

#### ORGANIZATIONAL:

- 2 exempt personnel (Chemical Engineers)
- 6 non-exempt personnel (Engineering Techs)

#### NATURE AND SCOPE OF JOB:

The Defense Systems Division in St. Paul operates in five separate facilities plus additional rental space in other buildings as required for its operation, as well as facilities in Clearwater, Florida and Winnipeg, Canada. As such, this position is responsible for the management and control of all procedural and operational elements affecting the environment. This includes hazardous waste disposal, waste conditioning, air emissions, etc.

Provide information to other divisions of Sperry Corporation on a consulting basis on environmental related matters.

#### PRINCIPLE RESPONSIBILITIES:

- 1. Manages the preparation of and/or performs technical tasks of unusual difficulty or complexity on all matters pertaining to the effect of our processes on the environment. This aspect required frequent involvement with customers, local, state and federal regulatory offices.
- Investigates, plans and designs equipment, principles and systems for accomplishing environmental treatments in accordance with established regulations and laws.
- 3. Must be available to give expert professional appraisal of new methods which would entail environmental aspects and the affect of same if incorporated into a product line.
- 4. Manages the development of solutions to specific technical problems involved in No. 3 above and designs a course of action to accomplish same.
- 5. Approves and/or prepares complex technical reports to provide environmental information required by law to all levels of government and in specific cases to potential customers where it is an item of the contract.
- 6. Prepares for approval and controls departmental capital and operating expense budget.
- 7. Provides consulting to Plant Engineering and other operating departments on all design criteria involving environmental impact elements for renovations and new construction.
- 8. Acts in an advisory capacity to division management in planning and coordinating all programs or processes impacting the environment.
- 9. In conjunction with the Energy Management Department, manage the ongoing Employee Energy/Environmental Awareness Program to aggressively promote environmental conservation in all DSD facilities.
- 10. Maintain familiarity with all levels of government regulations, implement and supervise with subordinates, the carrying out of same to insure our compliance to avoid work stoppage, punitive and criminal redress for compliance failure.
- 11. The incumbent is accountable for the implementation of governmental and company policies dealing with EEO and AAP compliance in organizations under the incumbent's span of control. Incumbent is further accountable to see that subordinate supervision is also made aware of Company Policies regarding EEO and AAP and that they conform to the requirements and intent of these Policies and Programs.



TITLE Environmental Manager

P.D. NO.

#### PRINCIPLE RESPONSIBLITIES: (Continued)

- 12. Work with industry associations to ensure that accurate information is available to lawmakers prior to the promulgation of regulations affecting our operations.
- 13. Participate on the Sperry Corporate Environmental Committee to provide corporate directions to the various operations within the corporation that are affected by government environmental regulations.

#### EDUCATION AND EXPERIENCE:

B.S. Degree in Chemical Engineering, or equivalent, plus seven or more years in related experience or equivalent education, training related work experience.

APPROVAL

R. J.

Martin, Incumbent

F T Michaud

# APPENDIX H-2

HAZARDOUS WASTE/MATERIALS MANAGEMENT INSTRUCTOR TRAINING

## LEADER GUIDE

# INTRODUCTION

- 1. OUTLINE COMPANY OBJECTIVES REGARDING SEMINAR
- 2. EXPLAIN THE FOLLOWING COMPLIANCE PROBLEMS
  - A. PENALTIES FOR NON-COMPLIANCE
  - B. INDIVIDUAL LIABILITY FOR PENALTIES AND PUNTATIVE DAMAGES
  - C. TR AINING REQUIREMENTS OF EPA AND DOT

(REVIEW REGULATIONS STRUCTURE USING THE FOLLOWING GRAPH)

	C	FR-49	} -	DOT	HAZA	RDOUS	MATE	RIALS	Uni	VERSE	ohdomern minuskustkustkustk	many many many many many many many many

(Using rectangle, explain the hazardous materials universe under DOT )
(Notes:



## CFR 49 - DOT HAZARDOUS MATERIALS UNIVERSE

EPA CLEAN WATER "REPORTABLE QUANTITY" 5000	300 HAZ SUB	
1000 100 10		

- 1. EPA AMENDS CLEAN WATER ACT TO REGULATE 300 HAZARDOUS MATERIALS AS "HAZARDOUS SUBSTANCES" BECAUSE IS ACCIDENTIALLY RELEASED POSE A THREAT TO HUMAN HEALTH AND THE ENVIRONMENT.
- 2. CREATES NEW TERM "REPORTABLE QUANTITY"
- 3. WHEN A RELEASE OF A "HAZARDOUS SUBSTANCE" EQUALS OR EXCEEDS'
  THE "RQ" IMMEDIATE NOTIFICATION TO EPA OR NATIONAL RESPONSE
  CENTER.
- 4. REPORTING RELEASE SETS INTO MOTION ESCULATING PENALTIES
- 5. DOT ADOPTS SAME "RQ" RESPONSIBILITIES IN 49CFR.
- 6. DOT ADOPTS DIFFERENT REPORTING RESPONSIBILITIES THAN THOSE OF EPA. (WILL BE COVERED IN DEPTH LATER.)

EPA
CLEAN
WATER
"REPORTABLE
QUANTITY"
5000
1000
100
101

-	CE	R49 -	DOT HAZ	ARDOUS MAT	ERIALS UNIVERSE	, Marie
	300 HAZ SUB	BATF 150 EXPL MATS	OSHA CANCER CAUSING AGENTS	NRC RADIO- ACTIVE MATERIALS		

- 1. EXPLAIN THE BUREAU OF ALCOHOL, TOBACCO AND FIREARMS REGULATIONS REGARDING REPORTING LOSSES OR THEFTS.
- 2. EXPLAIN OSHA REQUIREMENTS TO LABEL HAZARDOUS MATERIALS THAT ARE KNOWN OR SUSPECTED "CARCINOGENS"
- 3. Explain that Radioactive Materials are regulated by both the Department of Transportation and the Nuclear Regulatory Agency.
- 4. POINT OUT ADDITIONAL REGULATIONS FOR MULTIPLE IDENTIFICATION FOR ALL HAZARDOUS MATERIALS WILL BE COMING IN THE NEXT YEAR.

CFR49 - DOT HAZARDOUS MATERIALS UNIVERSE

EPA CLEAN WATER "REPORTABLE QUANTITY" 5000 1000 1000	300 HAZ SUB	BATF 150 EXPL MATS	OSHA CANCER CAUSING AGENIS	NRC RADIO ACTIVE MATERIALS		
10						

REVIEW OF THE EPA (RCRA) HAZARDOUS WASTE REGULATIONS:

- 1. FOUR CLASSES OF HAZARDOUS WASTE IGNITABLE-REACTIVE-CORROSIVE-TOXIC
- 2. NOT ALL HAZARDOUS MATERIALS ARE WASTE....HOWEVER?
- 3. THE GENERATOR MUST DETERMINE IS ANY WASTE DISPOSED OF CAN CAUSE A HEALTH HAZARD...AND EVEN THOUGH IT MAY NOT MEET THE CRITERIA OF A WASTE IT MUST BE REGULATED.
- 4. BASED ON THE MONTHLY ACCUMULATION OR GENERATION .. A GENERATOR MAY HAVE TO COMPLY WITH ALL THE REGULATIONS OR NONE.

5.

EPA CLEAN WATER "REPORTABLE QUANTITY" 5000 1000 1000

C	FR49 <u> </u>	DOT HAZA	RDOUS MA	CIERLALS UN	NIVERSE
300 HAZ SUB	BATF 150 EXPL MAT	OSHA CANCER CAUSING AGENIS	NRO RADIO- ACTIVE MATS	EPA HAZARDOUS WASTE (RCRA)	

EPA CERCIA AC

- 1. EXCISE TAX
- 2. H.W.S.N.
- 3. 'RQ' = 1 1 1b.

- 1. OUTLINE THE REQUIREMENTS OF THE SUPERFUND ACT
- 2. REVIEW THE THREE REQUIREMENTS OF THE ACT.
  - A. EXCISE TAX
  - B. HAZARDOUS WASTE SITE NOTIFICATION
    - 1. 55 GALS OF WASTE STORED OR DISPOSED OF ON SITE
    - 2. SITES SELECTED FOR DISPOSAL PRIOR TO RCRA
    - 3. MAJOR SPILLS ON SITE OR IN TRANSPORATION
    - 4. PCB STORAGE (OPTIONAL)
  - 3. REVIEW THE CONCEPT OF THE SITE NOTIFICATION
  - 4. REVIEW DOT'S NON-ADOPTION OF SUPERFUND "REPORTABLE QUANTITY"

Instructor's NOTE: AFTER THIS REVIEW...PROGRAM THE AUDIO/VISUAL PROGRAM - INTRODUCTION TO WAZARDOUS MATERIALS, SUBSTANCES & WASTES".

# QUESTION & ANSWER SESSION FOLLOWING PROGRAM

# POSSIBLE AREAS OF REVIEW


- 1. ANNUAL REPORT TO ANNUAL SURVEY
- 2. GENERATOR'S STATUS AS A CONTIGUOUS FACILITY
- 3. 10 WORKING DAYS FOR STORAGE PRIOR TO STORAGE PERMIT
- 4. Possible Generator's Monitoring Requirements



COVER & EXPLIAN THE EPA PROPOSED REGULATIONS FOR GENERATORS

RCRA CONTINGENCY PLANS & STORAGE REQUIREMENTS OUTLINED IN THE

JANUARY 3RD, 1983 FEDERAL REGISTER:



EXPLAIN:

WHEN A GENERATOR WILL GENERATE OR ACCUMULATE HAZARDOUS WASTE AT SPECIFIC SITES WITHIN A FACILITY OR PLANT AREA THE GENERATOR MAY ACCUMULATE UP TO 55 GALLONS AT EACH SITE. HOWEVER, WHEN THE 55 GALLON ACCUMULATION HAS BEEN REACHED, THE GENERATOR MUST MOVE THAT WASTE, WITHIN 72 HOURS, TO THAT LOCATION IN HIS PLANT THAT HAS BEEN DESIGNATED AS THE "HAZARDOUS WASTE STORAGE AREA". IF THE GENERATOR EXCEEDS 72 HOURS AT A SITE WITHIN HIS PLANT THAT IS NOT INCLUDED IN HIS RCRA CONTINGENCY PLAN, THEN THAT SITE WOULD NO BE SUBJECT TO ALL THE REGULATIONS OUTLINED IN SECTION 262.34 ACCUMULATION TIME.

#### SESSION #2

Review April 15th, 1981 FEDERAL REGISTER on Hazardous Waste Site Notification Program.

Review use of Hazardous Material Telephone Assistance Directory

Review use of Hazardous Materials & Waste Training Booklets, as applicable.

### 1982/83 HAZARDOUS MATERIALS SUBSTANCES & WASTE COMPLIANCE GUIDE

- I. Review Emergency Response Telephone Numbers on Page iii.
- 2. Review list if BATF regulated Explosive Materials on Page 2/4
- 3. Review EPA Hazardous Substances listed in II7.3 on page 226/228
- 4. Review EPA Hazardous Substance Reporting Responsibility in 117.21 on Page 230.
- 5. Review DOT Hazardous Substance Reporting Responsibility in 171.17 on page 18.

"REPORTABLE QUANTITY"
released in any
24 hour period into
Navigable Waters

20,000 lbs Chlorofoem

50 Drums of
CHLOROFOEM

BASED ON DOT REGULATIONS TRUCK LOADED WITH 50 DRUMS OF CHLOROFORM WOULD NOT BE REGULATED, THEREFORE IF ALL DRUM WERE RELEASED OR DISCHARGED IN ACCIDENT, NO NOTIFICATION TO THE NATIONAL RESPONSE CENTER REQUIRED BY DOT. BUT UNDER 117.17, EPA WOULD REQUIRE NOT NOTIFICATION BECAUSE THE DISCHARGE EXCEEDED 5000 POUNDS IN ONE TWENTY FOUR HOUR PERIOD.

STRESS THE NEED TO CHECK BOTH DOT AND EPS REGULATIONS WHEN DISCHARGE OF A HAZARDOUS MATERIAL OR WASTE ALSO MEETS THE DEFINITION OF A DISCHARGE OF HAZARDOUS SUBSTANCE.

REVIEW THE CHARACTERISTICS OF HAZARDOUS WASTE IN PART 2 6 1, SECTIONS 2 6 I . 3 I - SUBPART C.....AND THE GENERIC LISTINGS OF HAZARDOUS WASTES IN SUBPART D.

EXPLAIN THE DIFFERENCES BETWEEN THE DOT AND EPA DEFINITIONS OF HAZARDOUS MATERIALS AND HAZARDOUS WASTE:

EPA

DOT

FOUR (4) HAZARD CLASSES

IGNITABLE REACTIVE CORROSIVE TOXIC TWENTY ONE (21) HAZARD CLASSIFICATIONS

ORM-E

HAZARDOUS WASTE, LIQUID/ SOLID N.O.S. - O R M - E

- I. COVER THE REQUIREMENTS TO PROVIDE THE DOT INFORMATION ON SHIPPING DOCUMENTATION AND THE EPA CLASSIFICATIONS ON THE UNIFORM HAZARDOUS WASTE MANIFEST.
- 2. REVIEW THE COIRCUMSTANCES WHERE A GENERATOR WILL USE THE PROPER DOT/EPA SHIPPING NAME IN THE HAZARDOUS MATERIALS TABLE IN 172.101 49CFR ——"HAZARDOUS WASTE, LIQUID/SOLID, N.O.S. O R M E.
  - A. WHEN A HAZARDOUS WASTE DOES NOT MEET THE CRITERIA
    OF A DOT HAZARDOUS MATERIALS BUT DOES MEET THE
    CRITERIA OF A EP TOXIC HAZARDOUS WASTE.
  - B. WHEN A WASTE DOES NOT MEET THE CRITERIA OF A HAZARDOUS MATERIAL UNDER DOT NOR A HAZARDOUS WASTE UNDER EPA BUT THE GENERATOR WANTS TO TREAT IS AS A HAZARDOUS WASTE.

CRITICAL POINT: NEVER USE THE NAME "HAZARDOUS WASTE, LIQUID/SOLID N.O.S. - O R M - E, IF THE WASTE MEETS THE CRITERIA OF A DOT HAZARD CLASSIFICATION. A GENERATOR MUST USE A PROPER SHIPPING NAME THAT FULLY IDENTIFIES THE HAZARDOUS WASTE.


REVIEW AUDIO/VISUAL PROGRAM \_ "CLASSES OF HAZARDOUS MATERIALS & AND WASTES" QUAESTIONS & ANSWERS - SUMMARY AS NECESSARY

#### SESSION # 3

HAVE PARTICIPANTS TAKE "EMPTIES & LEAKERS" PRE-TEST

REVIEW EPA AND DOT REGULATIONS FOR "EMPTIES" AND "NON-EMPTIES".
REVIEW CHANGES IN DOT "EMPTIES" REGULATIONS:


- I. PREVIOUSLY COULD REMOVE DOT LABEL EVEN THOUGH CONTAINER HAS RESIDUE.
- 2. NOW, ALL EMPTIES WITH RESIDUE MUST BE TREATED SAME WAT AS WHEN FILLED:
  - a. SHIPPING PAPERS FOR COMMON CARRIERS ALWAYS.
  - b. SHIPPING PAPERS FOR PRIVATE & CONTRACT CARRIERS WHEN:
    - I . GLASS CARBOYS
    - Z. STILL CONTAINS "RQ"
    - 3. RAIL CAR WITH RESIDUE




REVIEW EPA "EMPTIES" & "NON-EMPTIES" AS THEY APPLY TO REGULATED AND SMALL QUANTITY GENERATORS" (Ref: 261.7 - 261.33(c) - 261.5)

REGULATED GENERATOR:

- I. ANY AMOUNT OF HAZARDOUS WASTE LISTED IN 261.33(e)
- 2. ANY CONTAINER WITH 2.5 CENTIMETERS
  OR ONE INCH RESIDUE LISTED IN 261.33(f)
  OR MEETING THE CRITERIA OF AN IGNITABLE,
  REACTIVE, CORROSIVE OR TOXIC WASTE.
- 3. ANY CONTAINER, UNDER 110 GALLONS WITH A RESIDUE OF 3% OR GREATER OF THE ORIGINAL CONTENTS OF IGNITABLE, REACTIVE CORROSIVE OR TOXIC OR LISTED ON 261.33(f)
- 4. ANY CONTAINER, OVER 110 GALLONS, WITH A
  RESIDUE OF 0.3% OR GREATER OF THE ORIGINAL
  CONTENTS OF THE CONTAINER OF IGNITABLE,
  REACTIVE, CORROSIVE OR TOXIC WASTE OR A
  WASTE LISTED IN 261.33(f).





## REVIEW DOT AMENDMENTS & REGULATIONS FOR OVER-PACKS AND LAB-PACKS

I. "RECOVERY DRUM" NO LONGER ACCETABLE.



- 2. "SALVAGE DRUM" MUST BE MARKED ON EACH OVER-PACK OF LEAKER.
- 3. ALL DOT LABELS, MARKING &
  CONSIGNEE'S NAME & ADDRESS
  MUST BE PLACED ON OVER-PACK.



JAY

EXPLAIN DOT/EPA REGULATIONS FOR LAB-PACKS: (Ref; 265.316 40 CFR & EXEMPTION DOT-E-8129)




1. LAB-PACKS ONLY ALLOWED IN DOT SPEC. PACKAGINGS:

37A-STC 5 GALLON PAIL 6J-STC 30 GALLON DRUM 17H-STC 55 GALLON DRUM

2. IN ADDITION TO ALL DOT/EPA

LABELS & MARKINGS - MARK

EACH OVER-PACK WITH DOT-E-8129




EXPLAIN REQUIREMENT FOR REUSE OF STC/NRC CONTAINER FOR WASTE

I. MUST BE SPECIFICATION CONTAINER REQUIRED BY REGULATIONS.



- 2. USE IN HIGHWAY MODE ONLY.
- 3. ALLOW TO STAND FOR 24 HOURS AFTER CLOSING & SEALING.
- 4. EXAMINE FOR LEAKS OR DAMAGE BEFORE LOADING ON TRANSPORTATION UNIT.
- 5. LOADING CARRIED OUT BY GENERATOR
- 6. UNLOADING CARRIED OUT BY TSD FACILITY.
- 7.IF CONTAINER OFF-LOADED BEFORE REACHING FINAL DESTINATION, NEW OR RECONDITIONED CONTAINERS MUST BE USED FOR WASTE.



EXPLAIN DOT & SUPERFUND (CERCLA) REGULATIONS & RULINGS FOR LEAKING CONTAINERS AT COMPANY'S DOCK OR PLANT AREA"

- I. VEHICLE WITH LEAKER "OUT-OF-SERVICE UNTIL LEAKER OFF-LOADED, REPAIRED, REPLACED OR OVER PACKED IN "SALVAGE DRUM".
- 2. DRIVER MAY MOVE TO NEAREST SAFE LOCATION RO CARRY THIS OUT, OR IT CAN BE OFF-LOADED AND HANDLED AT COMPANY'S DOCK
- 3. IF DRIVER LEAVES COMPANY FACILITY OR PLANT, COMPANY AND PERSONS KNOWLEDGABLE OF LEAKER ALSO SUBJECT TO DOT PENALTIES.
- 4. IF HAZARDOUS MATERIAL REGULATED UNDER "SUPERFUND" COMPANY
  OR PERSON KNOWLEDGABLE OF DISCHARGE ALSO SUBJECT TO PENALTIES
  UNDER CERCLA (SUPERFUND) IF DISCHARGE NOT REPORTED TO NATIONAL
  RESPONSE CENTER.
- 5. ESTABLISH COMPANY'S POLICY ON THE HANDLING OF LEAKERS ON CARRIERS VEHICLES COMING INTO COMPANY YARD OR AT DOCK.

REVIEW AUDIO/VISUAL PROGRAM - HANDLING EMPTIES & LEAKERS

HAVE SEMINAR PARTICIPANTS TAKE POST-TEST & REVIEW ANSWERS

QUESTIONS & ANSWERS - SUMMARY IF NECESSARY.

REVIEW THE DOT HAZARDOUS MATERIALS TABLE - 1 7 2 . 1 0 1 : FIRST COLUMN #1

- + = MUST CLASS HAZARDOUS MATERIALS OR WASTE AS SHOWN IN COLUMN #3 - EVEN THOUGH IT DOES NOT MEET THAT HAZARD CLASS DEFINITION.
- A= AS HAZARDOUS MATERIAL, ONLY REGULATED IN AIR MODE AS A HAZARDOUS WASTE, REGULATED IN ALL MOSED OS TRANSPORTATION
- W= AS A HAZARDOUS MATERIALS, ONLY REGULATED IN WATER MODE, AS A HAZARDOUS WASTE, REGULATED IN ALL MODES OF TRANSPORTATION
- AW= AS A HAZARDOUS MATERIAL, ONLY REGULATED IN AIR & WATER MODES, A HAZARDOUS WASTE REGULATED IN ALL MODES OF TRANSPORTATION.
  - E= WHEN THE HAZARD CLASS IS ORM-E, ONLY REGULATED (IN ALL MODES)
    WHEN A "RQ" AMOUNT IN ONE (I) CONTAINER. WHEN A HAZARDOUS WASTE
    ANY AMOUNT IN ONE CONTAINER IS REGULATED. WHEN "RQ" IN ONE (I)
    CONTAINER, INCLUDE "RQ" BEFORE OR AFTER NAME IN BASIC DESCRIPTION,
    AND "RQ" MARKINGS ON ALL CONTAINERS UNDER IIO GALLIONS.
  - E= WHEN "E" SHOWN FOR ANY OTHER HAZARD CLASS, EXCEPT ORM-E, HAZARDOUS MATERIAL OR WASTE REGULATED IN ALL MODES OF TRANSPORTATION. WHEN "RQ" AMOUNT IN ONE CONTAINER, ENTER "RQ" IN BASIC DESCRIPTION AND MARK "RQ" ON ALL CONTAINERS UNDER 110 GALLONS.
  - EA= ONLY REGULATED IN AIR MODE UNTIL "RQ" AMOUNT IN ONE CONTAINER, WHEN "RQ" IN ONE CONTAINER, REGULATE IN ALL MODES OF TRANSPORTATION A HAZARDOUS WASTE HOWEVER WOULD BE REGULATED IN ALL MODES OF TRANSPORTATION. WHEN A WASTE, DISREGARD "A"
  - EW= ONLY REGULATED IN WATER MODE UNTIL "RQ" AMOUNT IN ONE (I) CONTAINER. WHEN "RQ" OR MORE IN ONE CONTAINER, REGULATE IN ALL MODES OF TRANSPORTATION. DISREGARD "W" IF A HAZARDOUS WASTE WHICH WOULD BE REGULATED IN ALL MODES OF TRANSPORTATION.
- EAW= ONLY RE GULATED IN AIR AND WATER UNTIL "RQ" AMOUNT IN ONE CONTAINER. WHEN "RQ" OR MORE IN ONE CONTAINER, REGULATE IN ALL MODES OF TRANSPORTATION. DISREAGRD "AW" IF A HAZARDOUS WASTE AND REGULATE IN ALL MODES OF TRANSPORTATION.
  - COLUMN#2 REVIEW USE OF DOT PROPER SHIPPING NAMES AS HAZARDOUS MATERIAL OR WASTE.
  - COLUMN#3 - HAZARD CLASSIFICATIONS
  - COLUMN#3A- DOT IDENTIFICATION NUMBERS
  - COLUMN#4 DOT LABELS
  - COLUMN#5 A/B EXCEPTION & PACKAGING REQUIREMENTS
  - COLUMN#6 A/B QUANTITY LIMITATIONS IN THE AIR MODE
  - COLUMN#7 PLACARDING REQUIREMENTS & NUMERICAL DESIGNATIONS
  - COLUMN#8 CHEMICAL ABSTRACT SERVICE NUMBERS
  - COLUMN#9 EMERGENCY RESPONSE GUIDE NUMBERS

NEW DOT/EPA REQUIREMENTS FOR MUTIPLE IDENTIFICATION OF HAZARDOUS MATERIALS & WASTE (USE "FLAMMABLE LIQUID, POISONOUS N.O.S. ON PAGE #69)

20 DRUM WASTE - EQUAL PARTS OF PHENOL, CHLOROBENZE & MEK
"RQ" WASTE FLAMMABLE LIQUID, POISONOUS (OR POISON B), N.O.S.
(PHENOL-CHLOROBENZENE) FLAMMABLE LIQUID UN1992 - 20 DRUMS

WHEN A HAZARDOUS MATERIAL OR WASTE THAT IS A MXITURE OR SOLUTION OF DIFFERENT HAZARDOUS MATERIALS OR WASTE THAT MEET THE CRITERIA OF A FLAMMABLE LIQUID, FLAMMABLE SOLID, OXIDIZER OR CORROSIVE WHICH ALSO MEETS THE DEFINITION OF A "POISON B" MUSE BE IDENTIFIED UNDER BOTH HAZARD CLASSES.

IF A HAZARDOUS MATERIAL OR WASTE IS DESCRIBED UNDER AN N.O. . OR NOT OTHERWISE SPECIFIED SHIPPING NAME in the 172.101 TABLE, AND THE CHEMICAL OR TECHNICAL NAME OF THE MATERIAL IS NOT IN THE BASIC DESCRIPTION FOR A POSION B OR A HAZARDOUS SUBSTANCE...THEN THE NAMES MUST BE ADDED TO THE BASIC DESCRIPTION.

IF THE BASIC DESCRIPTION HAS MORE THAN ONE HAZARD CLASS IN IT, ENTER THE PRIME HAZARD CLASS AFTER THE BASIC DESCRIPTION FOR PLACARDING PURPOSES.

"RQ" WASTE FLAMMABLE LIQUID, POISONOUS N.O.S. (ACRYLONITRILE - CHLOROBENZENE) FLAMMABLE LIQUID UN1992

SELECT SPECIFIC HAZARDOUS MATERIAL OR WASTE SHIPMENTS FOR COMPANY'S PLANTS OR FACILITIES REPRESENT BY SENMINAR PARTICIPANTS.

#### REVIEW OF COLUMN 3A:

- 1. I.D.Number now required on all shipping papers and manifests and portable tanks, tank cars and cargo tanks. The I.D. number will be required on all containers or packaging under 110 gallons on July 1st, 1983.
- 2. I.D. NUMBER ARE NEVER DISPLAYED ON PLACARDS FOR RADIOACTIVE MATERIALS POISON A OR EXPLOSIVE A. IF BEING SHIPPED IN PORTABLE TANKS, CARGO TANKS OR TANK CARS...THE I.D. PANEL WILL BE AFFIXED NEXT TO THE PLACARDS.
- 3. I.D. NUMBERS ARE NEVER REQUIRED ON A TRUCK OR TRAILER IN THE HIGHWAY MODE AND IN FACT WOULD BE IN VIOLATION IF MORE THAN ONE HAZARDOUS MATERIAL OR WASTE WERE ON THE VEHICLE.
- 4. I.D. PANELS ARE USED WHEN A TRANSPORTER OR CARRIER WILL USE A UNIT THAT IS PERMENANTLY PLACARDED WITH THE "GENERIC HAZARD CLASS" PLACARDS BECAUSE THE CARRIER IS IN "DEDICATED OR EXCLUSIVE USE" SERVICE. IN THESE INSTANCES...THE SHIPPER OR GENERATOR MUST NOT ONLY PROVIDE THE I.D. PLACARDS...BUT MUST ALSO AFFIX THEM TO THE UNIT.

USING SAMPLES, EXPLAIN THE METHODS OF PLACARDING UNITS WITH GENERIC PLACARDS AND PANELS.

"RQ" FLAMMABLE LIQUID, POISONOUS N.O.S.

ACRYLONITRILE UN1093

ALDRIN UN2761

FLAMMABLE LIQUID UN1992

EXPLAIN THAT I/D/ NUMBERS ARE NEVER USED FOR "CONSTITUENTS" CHEMICAL TECHNICAL NAMES WHICH ARE REQUIRED AS PART OF THE BASIC DESCRIPTION. THE I.D. NUMBER IS SHOWN AFTER THE BASIC DESCRIPTION BUT MUST ONLY SHOW ONE I.D. NUMBER WHICH WOULD BE SHOWN IN COLUMN 3A, AFTER THE PROPER DOT SHIPPING NAME IN COLUMN 2.

EXPLAIN WHY THE I.D. NUMBER IS CRITICAL...BECAUSE OF IT'S USE BY EMERGENCY RESPONSE TEAMS AND FIRE FIGHTERS. (USE DOT EMERGENCY RESPONSE GUIDE TO SHOW IMPORTANCE)

#### SESSION 5 - LABELS, MARKINGS AND PLACARDING HAZARDOUS MATERIALS & WASTE

(HAVE PARTICIPANT TAKE PRE-TEST ON LABELS, MARKINGS AND PLACARDING )
REVIEW COLUMN 4

- 1. COLUMN 4 OUTLINES LABELS REQUIRED FOR ALL CONTAINERS UNDER 110 GALLONS OR CONTAINERS OVER 64 CUBIC FEET BUT NOT MORE THAN 640 CUBIC FEET.
- 2. IN SOME CASES MORE THAN ONE LABEL IS REQUIRED EVEN THOUGH IT IS NOT SHOWN IN COLUMN 4.

(REVIEW: CFR 49 - SECTION 173.400 - LABELING REQUIREMENTS PAGE #152 - POCKET COMPLIANCE GUIDE)

3. DEPENDING UPON THE HAZARDOUS MATERIAL OR WASTE...ADDITIONAL MARKING REQUIREMENTS MAY EXIST FOR PACKAGING.

(REVIEW CFR49 - SECTION 172.300 - MARKING REQUIREMENTS PAGE #145 - POCKET COMPLIANCE GUIDE)

(REVIEW AUDIO/VISUAL PROGRAM - LABELS, MARKINGS AND PLACARDING HAZARDOUS MATERIALS, SUBSTANCES AND WASTE)

(INSTRUCTOR'S NOTE: REVIEW SCRIPT FOR AUDIO/VISUAL. BECAUSE, OF IT'S

LENGTH AND COMPLEXITY...INSTRUCTOR MAY STOP PROGRAM

AT SPECIFIC SECTIONS AND REVIEW EACH SECTION IN

CFR 49 REPRINT. THIS IS THE INSTRUCTOR'S OPTION)

(AT END OF THE AUDIO/VISUAL - HAVE PARTICIPANT TAKE POST-TEST AND SEE RESULTS BEFORE AND AFTER SESSION)

QUESTION AND ANSWER SESSION

(NOTES:

#### SESSION 6 - SHIPPING PAPERS AND MANIFESTS FOR HAZARDOUS MATERIALS, SUBSTANCES AND WASTE:

(HAVE PARTICIPANTS TAKE PRE-TEST ON SHIPPING PAPERS AND MANFESTS).

REVIEW THE DIFFERENCES BETWEEN A HAZARDOUS MATERIAL SHIPPING PAPER AND A HAZARDOUS WASTE MANIFEST. (THIS WILL VARY DEPENDING UPON STATE REQUIREMENTS AND STATE MANIFESTS) (REVIEW SECTION 172.200 IN POCKET COMPLIANCE GUIDE ON PAGE 139.)

EXPLAIN DOT REQUIREMENTS FOR EXACT INFORMATION IN SPECIFIC SEQUENCE ON HAZARDOUS MATERIAL OR SUBSTANCE SHIPPING PAPER.

EXPLAIN DOT/EPA REQUIREMENTS FOR COMPLETE INFORMATION ON HAZARDOUS WASTE MANIFEST WHICH WOULD INCLUDE ALL TRUE SIGNATURES.

EXPLAIN REQUIREMENTS OF "SUPERFUND" ONE POUND "REPORTABLE QUANTITY" NOTIFICATION TO THE NATIONAL RESPONSE CENTER AND THE ONLY WAY IT MAY BE INDICATED ON A HAZARDOUS MATERIALS SHIPPING PAPER OR A HAZARDOUS WASTE MANIFEST. (CORPORATE POLICY WILL DICTATE WHETHER THE COMPANY WILL USE THE "RQ" ONE POUND WARNING ON SHIPPING PAPERS OR MANIFESTS)

REVIEW AUDIO/VISUAL PROGRAM ON "SHIPPING PAPER AND MANIFESTS FOR HAZARDOUS MATERIALS, SUBSTANCES AND WASTE".

(HAVE PARTICIPANT TAKE POST-TEST AND REVIEW RESULTS).

QUESTIONS AND ANSWERS SESSION

(NOTES:

#### SESSION 7 - HAZARDOUS MATERIALS, SUBSTANCES & WASTE & THE DRIVER

THIS SESSION WILL COVER THE DRIVER'S RESPONSBILITIES FOR:

- 1. FEDERAL MOTOR CARRIER SAFETY REGULATIONS OUTLINED IN CFR 49 PARTS 390-397.
- 2. "CARRIAGE BY PUBLIC HIGHWAY" IN SECTION 177 IN CFR49.

#### DRIVER'S RESPONSBILTIES: (TRY TO DRAW OUT FROM GROUP)

- 1. ACCEPTING ONLY PROFERLY DOCUMENTED AND PACKAGED, MARKED AND LABELED HAZARDOUS MATERIALS, SUBSTANCES AND WASTE.
- 2. PROPER PLACARDING ON VEHICLES
- 3. PROPER LOADING AND STOWING OF HAZARDOUS MATERIALS AND WASTE ON ALL VEHICLES OR UNITS.
- 4. COMPLIANCE WITH THE DOT FEDERAL MOTOR CARRIER SAFETY REGULATIONS WHEN TRANSPORTING HAZARDOUS MATERIALS OR WASTE.
- 5. EMERGENCY ACTION AND RESPONSES WHEN DEALING WITH ACCIDENTS, INCIDENTS OR EMERGENCIES INVOLVING HAZARDOUS MATERIALS, SUBSTANCES OR WASTE.
- 6. DRIVER LOG RESPONSIBILITIES
- 7. ANY OTHERS THE DRIVERS MENTION


(HAVE PARTICIPANTS TAKE THE PRE-TEST FOR DRIVERS)

REVIEW AUDIO/VISUAL PROGRAM ON "HAZARDOUS MATERIALS & MASTE & THE DRIVER)

(HAVE PARTICPANTS TAKE POST-TEST AND COMPARE RESULTS - DISCUSS RESULTS)

QUESTIONS AND ANSWER SESSION

Hazardous Wastes/Materials Management Instructor Certification



This Certifies That TOCET

Has Enrolled in and Completed The

Hazardous Wastes / Materials Management Compliance Seminar

and this Certificate represents a sincere effort on their company's behalf and on their own behalf to comply with the U.S. Department of Transportation Hazardous Materials Regulations, and the **Environmental Protection Agency Hazardous Waste** Regulations.

Robert J. Kéegan, President

Dr. Daniel Coopel, V. P. & Training Director Hazardous Wastes/Materials Management Instructor Certification

AIS Mana

AIS Mana


ARANSPORTATION

ARANSPORTATION SKILLS PROGRE

## This Certifies That dan e. macdonald

Has Enrolled in and Completed The

Hazardous Wastes / Materials Management Compliance Seminar



and this Certificate represents a sincere effort on their company's behalf and on their own behalf to comply with the U.S. Department of Transportation Hazardous Materials Regulations, and the **Environmental Protection Agency Hazardous Waste** Regulations.

& Training Director

APPENDIX H-3

TRAINING CERTIFICATES

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name	(Print) Po	568 V	MARTIN
Signa	ture Se	5~ 1	Martin
Date	4/13/	84 /	
Life	Number	19705	

#### HAZARDOUS MATERIAL HANDLING

#### TRAINING CERTIFICATION

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name	(Print)_	$-\mathcal{V}$	OGER	J	Ma	ETIN
Signa	ature (	Son	$\mathcal{R}$	MA	stin	
Date	4/13/	84/				
Life	Number	.	970	5		

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name (Print)	Dan MacDonald	
Signature	Dan & moclowell	AN-
Date 4/13	1/84	
Life Number	\$ 55686	

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name	(Print)	Dan MacDonald	
Signa	ture	Dant Machonelt	de gripamini de la companya por la companya por la companya por la companya por la companya por la companya p
Date	4/12/	184	,
Life	Number	55686	

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name	(Print) _	MARK	WILSON	
Signa	iture <u>Z</u>	Tack G.	While	
Date	4/	12/04	٠	•
Life	Number	55968		•

#### HAZARDOUS MATERIAL HANDLING

#### TRAINING CERTIFICATION

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name	(Print)	MARK	WILKON	
Signa	ture <u></u>	M2	Wilse	
Date	4/12/8	· · · · · · · · · · · · · · · · · · ·		,
Life	Number	55968	,	

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name	(Print)	Grea	Gring	s <i>15</i> · · ·	
Signa	ture C	Nue 1	Min	یگ	,
Date	4/1	184		CONFORMATION SCRIPTION	,
Life	Number	<u> 587</u>	<u> 28 -                                  </u>	entermonal and an angle of the	

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name	(Print)	Greg	G	- <i>(Nol</i>	S	
Signa	ture 9	\u_	<b>'9</b> L		الم	
Date	4/12/	184		,		
Life	Number	5812	8		•	

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name (Print)	William M. Polta
Signature _	William h. fatte
Date	4-13-84
Life Number	062487

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name	(Print)	1/1/lia	n 17.	Pe/49	m nongge
Signa	iture	William .	R. Sile		
Date	4-13	-81	٠		
Life	Number 2	162487		•	-

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division; St. Paul.

		Annual Property of the Parket		
Name	(Print)	KOGE	R. MANTZ	AU
	ستسوي	5 .		
Signa	ture			
Date	4/12	124		>
	and the second second			
Life	Number	6273	<u> </u>	

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name (Print) ROGER RANZAU

Signature Roger Range ...

Date 4/12/84

Life Number 62737

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name	(Print)	Michael	<u>( : </u>	Medina	and of the state of the state of the state of the state of the state of the state of the state of the state of
Signa	ture	Willy Me	<u>Lui</u>	·	onner of the second
Date	拉萝	# 4-13	-84	······································	
Life	Number	6417	<u> </u>	· · · · · · · · · · · · · · · · · · ·	

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name	(Print)	M	ichael	C.	Melina
Signa	iture _	Neily	Melini		
Date	4-13	-54	·		
Life	Number	6413		<del>.</del>	

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name (Print) Scot R Sokol	۲.	gantani and and Alaina	
Signature Left R Solida		Constitution of the Consti	and the second
Date 8/17/84	:		
Life Number 65779			

#### HAZARDOUS MATERIAL HANDLING

#### TRAINING CERTIFICATION

I certify that I have been trained on the job and understand that processes and procedures (ECP's) as they relate to my position in the Environmental Management Department of Sperry, Defense Systems Division, St. Paul.

Name (Print)	Grea Weishin
Signature,	Loudieisku
Date 4(13	1 Series
Life Number	0000

I certify that I have received training on the requirements of the Department of Transportation and U.S. Environmental Protection Agency that pertain to hazardous material handling.

Name (Print)

Signature

Date

-98-84

Life Number <u>900()</u>

#### HMI

The Hazardous Materials Institute Kansas City, Missouri

Certifies that

has participated in
The Institute's 1983-84 Seminar Series on

# HANDLING HAZARDOUS MATERIALS AND WASTES

Completion of this intensive training program on the safe, legal preparation, shipment and transportation of hazardous materials and wastes is indicative of a sincere effort to increase knowledge of and achieve compliance with the federal hazardous materials and wastes regulations.

Edward C. BLIM INSTITUTE DIRECTOR

#### ATTENTANCE ROSTER

Date: 5/7/84	
Purpose: Hazardous Material Training	·
Instructors: R. J. Martin	M. E. Wilson
D. E. MacDonald	

Name	Clock Number	Department
Mily Miling	64127	Environmental Management
Greg Ginols	58728	Env mant
mul allem	55464	ENU Men
Scot Sokola	65.779	Fix minor
Bis Potts	62487	Free Port
Latherplan	90010	Enci Mam 7
	,	
	·	•



awards this certificate to



## Roger Jr Martin

for participation in

The Management and Disposal of Hazardous and Chemical Wastes

Paul Klaas

President, J.T. Baker

H. H. Morton

Director, Safety Training

JUN 22 1984


Certified

(flut Sine ).
Instructor

Lany a. Parker

J.T.Baker

Instructo



## THE OPERATIONS COUNCIL of American Trucking Associations, Inc.

Certifies that

ROGER J. MARTIN

has participated in The Operations Council's 1982-83 Seminar Series on

# HANDLING HAZARDOUS MATERIALS AND WASTES


Completion of this intensive training program on the safe, legal preparation, shipment and transportation of hazardous materials and wastes is indicative of a sincere effort to increase knowledge of and achieve compliance with the federal hazardous materials and wastes regulations.

au Dome

Ed Bum

PAUL T. DOMER, EXECUTIVE DIRECTOR—TOC

EDWARD C. BLUM, TRAINING DIRECTOR



## THE OPERATIONS COUNCIL of American Trucking Associations, Inc.

#### Certifies that

MICHAEL MEDINA

has participated in The Operations Council's 1982-83 Seminar Series on

## HANDLING HAZARDOUS MATERIALS AND WASTES

Completion of this intensive training program on the safe, legal preparation, shipment and transportation of hazardous materials and wastes is indicative of a sincere effort to increase knowledge of and achieve compliance with the federal hazardous materials and wastes regulations.

PAUL T. DOMER. EXECUTIVE DIRECTOR—TOC

EDWARD C. BLUM, TRAINING DIRECTOR



awards this certificate to



### Dan HacDonald

for participation in

The Management and Disposal of Hazardous and Chemical Wastes

Paul Klass

President, J.T. Baker

M. H. Norton

Director, Safety Training

JUL 15 1831

Certified

Instructor

Long a Packer

JT.Baker CHEMICALS This Certifies That GREGORY A. GRINOLS

Has Enrolled in and Completed The

Hazardous Wastes / Materials Management Compliance Seminar

and this Certificate represents a sincere effort on their company's behalf and on their own behalf to comply with the U. S. Department of Transportation Hazardous Materials Regulations, and the Environmental Protection Agency Hazardous Waste Regulations.

Robert J. Keegan, President

Dr. Daniel Cooper, V. P. & Training Director

THE TRANSPORTATION SKILLS PROGRAM FINE TO SAME 
This Certifies That WILLIAM M. POLTA

Has Enrolled in and Completed The

Hazardous Wastes / Materials Management Compliance Seminar

and this Certificate represents a sincere effort on their company's behalf and on their own behalf to comply with the U. S. Department of Transportation Hazardous Materials Regulations, and the Environmental Protection Agency Hazardous Waste Regulations.

Robert J. Keegan, President

Dr. Daniel Cooper, V. P. & Training Director

THE TRANSPORTATION SKILLS PROGRAM PRINCES

This Certifies That ROGER ARTHUR RANZAU

Has Enrolled in and Completed The

Hazardous Wastes / Materials Management Compliance Seminar

and this Certificate represents a sincere effort on their company's behalf and on their own behalf to comply with the U. S. Department of Transportation Hazardous Materials Regulations, and the Environmental Protection Agency Hazardous Waste Regulations.

Robert J. Keegan, President

Dr. Daniel Cooper, V. P. & Training Director

#### HMI

The Hazardous Materials Institute Kansas City, Missouri

Certifies that

Mark Wilson

has participated in The Institute's 1983-84 Seminar Series on

# HANDLING HAZARDOUS MATERIALS AND WASTES

Completion of this intensive training program on the safe, legal preparation, shipment and transportation of hazardous materials and wastes is indicative of a sincere effort to increase knowledge of and achieve compliance with the federal hazardous materials and wastes regulations.

Edward C BILLIM INSTITUTE DIRECTOR

#### HMI

The Hazardous Materials Institute Kansas City, Missouri

Certifies that

has participated in The Institute's 1983-84 Seminar Series on

# HANDLING HAZARDOUS MATERIALS AND WASTES

Completion of this intensive training program on the safe, legal preparation, shipment and transportation of hazardous materials and wastes is indicative of a sincere effort to increase knowledge of and achieve compliance with the federal hazardous materials and wastes regulations.

Edwarde Slun

EDWARD C. BLUM, INSTITUTE DIRECTOR

### ATTENIANCE ROSTER.

Purpose: HAZARDOUS WASTE CO	ORDINATOR TRAININ	C ·
Instructors: Roger Martin		
Dan MacDonald		
en de la companya de la companya de la companya de la companya de la companya de la companya de la companya de		
Name .	Clock Number	Department
Mil Mokesto	19070	JAR
object of terrebe	52889	Fab
GET KACKA	61608	ME
Dave West	19640	Failure Andresis
ULDOM SIRIYOVARAKDI	064001	И
Faroul SOS	50065	Insp-Engn.
De Buel	97884	T-R
SECURAN BANK	390-/5	P.C.FAB
Kain Jennings	55681	MOS-5/D
Bill felt	62487	Environmental
Norm Repo	1297	maint.
In Wieden	4431	Stores
Ron Bornet	63278	Occ. Health Prog

Revision A 9/7/84

Page 308A

#### ATTENTANCE ROSTER

Date: 2/2	22/83	
Purpose:	HAZARDOUS WASTE COORDINATOR TRAINING	1
•		
Value 20		tanta yang katapatan katapatan katapatan katapatan katapatan katapatan katapatan katapatan katapatan katapatan
Instructor	s: Roger Martin	
*	Dan MacDonald	

Name	Clock Number	Department
Nightigoria	, 428	-f.a.
	55563	Ros. Tas).
Rinkinga	39948	PC Fab
Soutent	25692	7-8
ERNil	16635	Ree Jusque
D. FERN	13530	T-BIEd
I ama Whitman	- 19116	FAC. MAINT.
Darline Johnson	121233	P.C. assy
James & Pulai	3 3572/	P.C. FAB
Illan Frant	13208	P.c. Yale
Dan Lugdel	19661	M Fab
Bruce Bahls	12905	Re Furb
Tom Burge	251490	Factory Sugar
WagnerPatrick	20599	PCASSI
RON MARTIN	9876	P.C.ASSY (SUB ASS)
John Sitnen	592.76	MAINT
JA Reliela	35776	1350
MDRewill	19740	1350
Koger Rama	62737	1232
Mike Medina	(44)	1737

Х


## ATTENTANCE ROSTER

Date: September 24, 1981

Purpose: Hazardous Waste Coordinator's Training

Instructors: Roger Martin Dan MacDonald

Name		
	Clock Number	Department
Jour Handruck	53535	EM
Jan Bolista	55776	1350
C. Heima,	428	Final any 2123
John Fehts	13363	CORE MATRIX 2125
Susan L. Capaul	52/27	Stores
Mayorie Howland	18835	Protolyne
1 Day Dre	53468	PC. FAX
Dan Jeisse	39:409	// "/
Tom Burger	51490	Fretory Sugget
Denne E Lucias	2572/	P.C. FAB
A found	15506	MITOLIA
B 2 Buhs	12905	Reforbishmen
Bier Poth	62487	Environmental
Roya Roser	62737	ENGLIS MENTAL
Mike Medine	64127	Faviron wental
V John Bother	59276	Maint
Howard Sweet.	62109	Failure Andria
	·	



Certifies that


# SPERRY-UNIVAC CORPORATION

has enrolled personnel in The Operations Council's

## HAZARDOUS MATERIALS TRAINING AND COMPLIANCE SEMINAR

conducted at MINNEAPOLIS.

Their attendance is indicative of a sincere effort to achieve total compliance with U.S. Department of Transportation hazardous materials regulations.



Saul Dome Cout ( Classe ROBERT I. KAROAN, TRAINING DIRECTOR

PAGE 309

### LNIVAC

#### INTERCOMMUNICATION

E. T. Michaud

TO: R. J. Martin

R. P. Puncochar

R. W. Nicholson

FROM (NAME & EXT):

Dan MacDonald &

Mark Wilson/4653

LOCATION & DATE:

Univac Park/3-31-77

DEPARTMENT & M.S.:

Plant Engineering/UlN14

SUBJECT:

HAZARDOUS MATERIALS

SEMINAR

CC:

Dan MacDonald and Mark Wilson attended, as representatives of Sperry Univac, the Hazardous Materials Training and Compliance Seminar given by The Operations Council of American Trucking Association, Inc. It was presented on 25 March '77 in Roseville by Bob Keegan of The Operations Council's Training Services Division. The seminar studied on ways the new laws CFR#49 and PL93.633, which go into effect 1 July 1977, regulate the handling of hazardous materials covering the areas of: classes of hazardous materials, shipping documentation, packing, labeling and marking, and placarding. He used examples, audio visual presentations, and question and answer periods on each of the major categories of the laws explaining how they should be complied with. He also informed us of the heavy fines and possible civil actions that can take place if the regulations are not complied with.

We thought the seminar was well conducted and informative. It brought our attention to several areas of concern within Sperry Univac D.S.D. in the Twin Cities. First, our procedure for transporting hazardous materials between plants; secondly, how waste hazardous materials are shipped from Univac; thirdly, since PL93.633 states persons handling and not the company handling hazardous materials will be fined. all personnel involved should be trained.

In shipping hazardous materials between plants what Univac is responsible for must be clearly detailed and a procedure written up so all involved can be educated. It should include labeling, paper work, weight, quantity, placarding and Wintz's responsibilities. The same procedure will be completed and written up for waste hazardous material being shipped from Univac plants and correct training/procedures initiated.

The seminar did leave us with many questions in our day to day duties. With the heavy fines stipulated by PL93.633 who should sign the certification? Since we generally don't fill the waste barrels, should we have that responsibility? What guarantees us if we do sign and are fined while trying to do our jobs, that we will be reimbursed? Should we start buying reconditioned barrels, buy new ones, or continue as we are? Who will initiate this new program and train all people involved? Will we have to weigh each barrel before it leaves the plant or give approximate weights? Will we be responsible to have placard available or not? What kind of



31 Mar '77

paper work is necessary between plants and who will supervise for all interplant shipments to be done correctly? Can we get copies of the law, so we can comply when there are questions? These questions and many more will need answering, proper procedures written up, and people involved educated before July 1, 1977.

Dan MacDonald

Plant Engineering

Mark Wilson Plant Engineering

Mark & likeson


APPENDIX H-4

TRUCK DRIVER TRAINING



ECP	37016		REV	_0
PAGE	1	ΩF	7	

**************************************				
	PAGE	1	OF	7
ENVIRONMENTAL CONTROL PROCEDU	RE		- VVVVII in a second and a state of the stat	
DETAIL DESCRIPTION TRUCK DRIVER'S TRAINING MANUAL	REF	indiction (from the first section 1991)		<u>Sobolómičkiloborov v rokrá gy</u>
D. MacDonald 6/11/81 R.J. Ma	arlu			DATE . 6/11/81
• Training Manual				
Italiilig Manual				
Table of Contents				
I. Introduction				
Regulations				
A. CFR 49 - Department of Transportation Reg	gulation	s		
B. CFR 40 - Environmental Protection Agency				
C. Penalties and Fines	•			
II. General Duties				
A. Interplant shipment of chemicals				
B. Chemical pick up from vendors				
C. Interplant shipment of waste chemical				
D. Personnel				
III. Loading and Unloading				
A. Inspection of containers				
B. Securing containers	_			
C. Shipping papers	Ţ.			• •
1. Hazardous Material Transfer			100	
2. Minnesota Hazardous Waste Manifest			•	
3. Bill of Lading				
D. Compatible chemical loading				
E. Placarding truck				
IV. Accidents Procedure		•		•
A. Dock accidents				•
B. Accidents on the road				
V. Radio Instruction				
		-		
	i		•	



€CP 37016 REV.

ENVIRONMENTAL	CONTROL	<b>PROCEDURE</b>
---------------	---------	------------------

DETAIL DESCRIPTION

- TRUCK DRIVER'S TRAINING MANUAL

1161

NOTHER Mee Donald

B/11/81

6

APPENDIXS

- I. CFR 49 Part 172.200 172.406 and 177
- II. CFR 40 Part 263
- III. Schedule
- IV. "Waste Chemical" label
- V. Hazardous Material Transfer ECP 37004
- VI. Minnesota Hazardous Waste Manifest
- VII. Hazardous Material Bill of Lading
- VIII. Chemical Compatibility Guideline Placarding Guide
  - IX. List of approved signatures for shipping
  - X. List of necessary telephone numbers
  - XI. List of vendor telephone numbers and addresses
- XII. Chemical and Hazardous Material Emergency Response Procedure



ECP	3/010	R	EV	
PAGE	3	OF	7	

ENVIRONMENTAL CONTROL PRO	CEDURE
DETAIL DESCRIPTION TRUCK DRIVER'S TRAINING MAN	JAI
Wan MecDonald 6/11/81	Mastin 0/1/81
Hazardous Materials	Training

I. Introduction - Discussion of Regulations

All shipping of hazardous materials are covered by the U.S. government regulations CFR (Code of Federal Regulations) 49 issued by DOT (Department of Transportation) and CFR 40 issued by EPA (Environmental Protection Agency). The regulations are very specific on hazardous material handling. Penalities for non-compliance of these regulations are included in these regulations.

CFR 49 covers all aspects of Hazardous Materials transportation. It includes: 1. Penalties - Methods of enforcement

- 2. Law making
- 3. Exemptions
- 4. List of Hazardous Materials Part 172
- 5. Shippers Requirements Part 173 (Appendix I)
- 5. Shipping by:
  - A. Rail
  - B. Aircraft
  - C. Vessel
  - D. Public Highway Part 177 (Appendix I)
- 7. Shipping containers specifications Part 178
- 8. Specifications for tank cars

CFR 40 covers all aspects of waste hazardous material handling. All regulations covering transporters is covered in Part 263. This regulation incorporates CFR 49 by reference. It covers:

- 1. EPA transporter identification number
- · 2. Manifest system
  - 3. Recordkeeping
- 4. Waste discharges and clean up

These regulations have stiff penalities. The maximum penalties set by CFR 49 - (107.343) for a "person who knowingly violates a requirement." is \$10,000 for each violation. If it is a continuing violation, each day is: a separate violation. For a willful violation of regulations the violation is considered a criminal offense and the penalty is not more than \$25,000 and not more than 5 years of imprisonment. Knowingly would be an accidental violation of regulations. A willful violation would be a case where a person sets out to violate the law on purpose.

Penalties set by CFR 40 part 117 for a violations for a civil penalty is up to a \$5,000 fine per discharge. If the violation was found to be a willful one a fine of \$250,000 can be set. If there is a failure to notify a reportable quantity a \$10,000 fine or a one year imprisonment or both. Regulations also states that the discharger is liable for the cost of clean up, injury to people and damage to property.



ECP	37016	REV	
PAGE	4	OF	7

	No. 19956	
ENVIRONMENTAL CONTROL PROCEDU	JRE	
DETAIL DESCRIPTION	REF	
TRUCK DRIVER'S TRAINING MANUAL		
Wan Mee Donald 6/11/8/ APPROVA)	Martin	6/11/8/

#### II. General Duties - Truck Drivers

Generally the duties include transporting all interplant shipments of chemicals. This includes transporting all new chemicals between facilities and all waste chemicals going to Shepard Road for waste disposal. The chemical truck will also be used to pick up chemicals at vendors warehouses A chemical dock coordinator will be responsible for determining what goes on and off the truck. Inventory control will inform the chemical dock coordinator of the need for a chemical pick up. The chemical coordinator at Shepard Road will schedule the route for the day.

#### III. Loading and Unloading

The truck driver is responsible to see that the chemicals are properly loaded, secured and unloaded. All containers should be inspected and checked that they have the proper shipping name marked on container and that all labels needed are attached. No leaking containers should be allowed to be loaded onto the truck. All containers should be secured on the trailer so they cannot shift during transportation.

With all shipments of hazardous materials, very specific and properly filled out paperwork must be provided. The truck driver has several responsibilities in handling this paper work. When a load of hazardous materials is picked up, the truck driver should get a Hazardous Material Transfer (HMT) and make sure it is properly filled out and matches what is placed on the truck. The procedure for checking the HMT is shown in Appendix V.

If everything is correct, the carrier (Truck driver) signs in the carrier slot. When the load leaves the dock, the white copy of the HMT should be with the truck driver in the cab. The golden rod copy is kept by the originator, the yellow and pink copies go with the containers in the truck. At its distination the receiver gets the pink copy and Environmental Management gets the yellow copy.

If any material is loaded with a "Waste Chemical" label (appendix XI) on a container, a Minnesota Hazardous Waste Shipping Paper (Appendix VI) must accompany the shipment. This form must also be filled out correctly. Make sure all appropriate blanks are filled in. See Appendix VI for completion of Minnesota Hazardous Waste Manifest.

When picking up hazardous materials from vendors, they must provide the driver with a Hazardous Materials Bill of Lading (Appendix VII). It must be filled out completely, the same as HMT. Check the numbers of containers description, labels and certification and then sign the paper leaving the appropriate copy with the vendor.

The chemical dock coordinator will be in charge of making sure there are no imcompatible chemicals placed on the truck. This manual includes a guide



ECP	3/(	710	KE	٧.	and the control of th
PAGE	5	_	) E		7

ENVIRONMEN	TAL CONT	ROL PF	OCEDU	RE	
DETAIL DESCRIPTION	RUCK DRIVER'S	TRAINING	MANUAL	REF	
Dan Michon	A	DATE 6/11/81	APPROVAL	Martin	6/1/8/

(Appendix VIII) that shows which chemicals are incompatible. Refer to it if there are any questions.

The chemical dock coordinator will also be responsible for instructing the driver which placards to use on the truck. Refer to the opposite side of the chemical guide (Appendix VIII) provided. It explains how the trucks should be placarded.

#### IV. Accidents Procedure

By law at least one person must supervise the loading and unloading of hazardous materials. This is required in case of an accident. If an accident occurs, notify the chemical dock coordinator immediately. A spill should be contained if possible.

Also the area of the spill should be cleared of all personnel not involved. Use the Chemical and Hazardous Materials Emergency Response Procedure (Appendix XII) for reference on what to do and how to handle the accident.

At all times when traveling on the road the paper work for the load must be on the seat next to the driver or in a pouch on the driver's door. This is in case of an accident and the driver is indisposed. If an accident such as an overturn, leak or fire occurs, radio or telephone to get instructions on what to do immediately. Keep area clear of personnel not involved and warn all others of the hazards. Give required information to any officials that arrive on the scene to help in taking care of the incident.

VI Instructions for use of the Motorola Pageboy.

The motorola pageboy is a voice and tone receiver unit which enables personnel to be reached in the Twin City Metro Area.

Each pageboy unit has an individual ID on the top of the unit, for example "Pager 23". A message encoded for Pager #23 will only be heard by that unit.

All requests for pageboy activation should be made to the BMS Room Ext. 4812, Ext 2101, or Ext. 4548 at Univac Park, Eagan. If there are any questions concerning the message received on the pageboy, call one of those numbers.

Operation of the Pageboy:

- 1. Each day insure that the unit is fully charged and/or has a freshly charged set of batteries in it prior to operation.
- 2. Turn the unit on and a squelch/static noise can be heard. Depress the reset button and the unit is now in a quiet mode and ready to receive messages.
- Upon receipt of the message for the pageboy, and electronic tone will be



E	C	P	 <u>37016                                    </u>	 _REV	•	into enterior
_		_				

ENVIRONMENTAL CONT	ROL PR	OCEDUR		
DETAIL DESCRIPTION TRUCK DRIVER'S	TRAINING I	MANUAL	REF	NAME OF THE PARTY
ENGINEER	DATE	APPROVAL		DATE

heard followed by the specific voice message. After completion of the message the squelch (static noise) will return as a reminder to depress the reset button. The unit is now ready to receive future messages.

4. If there are any problems or if the pageboy needs repair, return it to the Environmental Manager. Do not attempt to repair the unit. Sperry Univac has a repair agreement with Motorola.



ECP_	37016	ŘEV.
PAGE		OF

<b>ENVIRONMEN</b>	TAL CON	ITROL PI	ROCEDUI	RE	- CALLED CONTROL CONTR
DETAIL DESCRIPTION	TRUCK D	RIVER"S TRA	INING MANHA	REF	
Von Marko	rell	DATE /8/	APPROVAL	Martin	DATE 7/6/8/

## Appendix X

Personne1	Pager	Phone Number
Roger Martin	535	456-4654
Dan MacDonald	915	647-4714
Jack Ziemet	. 536	456-4664
Bill Polta	905	647-4656
Mark Wilson	565	456-4220
BMS Room (Paging)		456-4812
Medical (Shepard Road)		647-4081
Medical (Univac Park)		456-2560
Medical (Midway)	¥ X	641-7870
Tony Parker		641-7793
Jerry Bryse		647-4426

#### ATTENTANCE ROSTER

Date: 2/1/84						
Purpose: Truck Driver	Training	namin-verdimmumumumileev-umvõtammileev-lunrammumumumumilellij <sup>k</sup> liitilijaskijassanevensiilm				
Instructors: Dan Mac Donald						
Name	Clock Number	Department				
Thomas Hartmun		Spare Cinter Transport				
	·					

#### ATTENTANCE ROSTER

Date:_	Apr	il 27	198	3					•	
Purpos	e:	HAZA	RDOUS	MATERIAL	TRUCK	DRIVER	TRAINING	and the second s		uumususu825
		6						November (1988)		
Instru	ctor	. S : D	an Ma	cDonald		et semme Perfective Attendant II (1900-1904). Here and the semme Perfective Attendant II (1900-1904).	•			

Name	Clock Number	Department
Jan Coth		Spare Center Dre.
	The state of the s	
	.)	
1		
	All Andrews	



UNIVAC PARK, P.O. BOX 3525 ST. PAUL, MINNESOTA 55165 TELEPHONE (612) 456-2222

## CHEMICAL TRUCK DRIVERS TRAINING

THIS DOCUMENT CERTIFIES THAT I HAVE COMPLETED APPROXIMATELY 16 HOURS OF HAZARDOUS MATERIAL TRAINING FOR HAULING CHEMICALS.

THIS TRAINING WAS PROVIDED FROM ENVIRONMENTAL MANAGEMENT ECP 37016. INCLUDED WAS TRAINING REQUIRED FOR CFR 40 PART 264.

ATTENDEE'S

TIMOTHY L. STOFFEL

CARY C. Young

INSTRUCTOR DAN MACDONALD

APPENDIX H-5
TRAINING MOVE CREW AND JANITORS



ECP	3/016	<u> </u>	REV	·
DAGE	1	OE		

ENVIRONMENTAL CONTROL	PROCEDURE	
DETAIL DESCRIPTION	REF	
Training Move Crew and Janitor	s O	A A A A A A A A A A A A A A A A A A A
Dan Mac Donald 12/	2/81 AST Mastin	DATE 12/7/8/


- I. Introduction
- II. Waste Pick up
  - A. Only move crew moves waste chemicals
  - B. Waste Chemical Label
    - 1. Must be completely filled out
    - 2. Must be signed
    - Show Appendix I (Waste Chemical Label)
  - C. Waste Chemical Containers
    - Must get containers from Environmental Management personnel
    - Do not reuse chemical container.

#### III. Shipping Requirements

- A. Dedicated truck for hazardous materials
  - 1. Items shipped on truck
    - a. Hazardous materials
    - b. All empty containers for hazardous materials
  - 2. Truck drivers trained
- B. Thing to watch for when loading
  - Labeling of containers
  - Hazardous Material Transfer completed and signed
  - 3. Waste chemicals Minnesota Waste Manifest
  - 4. Do not load leaking container on any truck.
- C. Chemical Dock Coordinator

#### IV. Spill Control Procedures

- A. Contact Guards at Emergency Telephone number
  - 1. Shepard Road X4400
  - 2. Midway X3000
  - 3. Univac Park X3000
- B. Contain spill if it can be done safely
- C. Keep area clear until other personnel arrives
- D. Environmental Management will clean up. Have chemical knowledge and equipment to handle.



ECP	<u>37016B</u>	REV	
	•		

ENVIRONMENTAL CONT	ROL PR	OCEDUR	entra personal de la constanta	
DETAIL DESCRIPTION  Training Move Crew and	Janitors		REF	
ENGINEER Den MacDonald	DATE 12/7/81	APPROVAL	**************************************	DATE

#### HAZARDOUS MATERIALS TRAINING

Move Crew and Janitors

#### I. Introduction

In this training session you will learn how to handle hazardous materials in your job. You need to take extra care when handling these materials. The move Crew serves as an important part of our hazardous material handling procedures.

#### II. Waste Pick Up

Move crew provides an important service for Environmental Management when you follow the correct procedure when moving hazardous waste to our area's for disposal. Only the move crew is allowed to move waste chemicals within our facilities. The waste chemical must have a waste chemical label attached and completely filled out before the container is moved.

Empty waste containers are obtained from Environmental management personnel. Reuse of chemical containers for waste disposal is not allowed.

#### III. Shipping Requirements

A dedicated hazardous materials truck now moves all hazardous materials between facilities. It also moves all empty hazardous materials containers. The truck drivers received training in hazardous materials.

When loading the trucks you need to watch for several things. All containers need proper labeling. All materials moved on to truck must have a completed and signed hazardous material transfer (HMT). All waste chemicals must have a Minnesota Waste Manifest. Leaking containers cannot be moved on a truck.

A chemical dock coordinator from the Environmental Department will dispatch hazardous materials truck. He is also responsible for supervising the loading and unloading of chemicals at facilities.

#### IV. Spill Control Procedures

A spill control procedure is implemented to handle a spill of hazardous material. In case of a spill, contact the Guard on the emergency telephone number:



ECP	37016B	REV

ENVIRONMENTAL	CONTROL	PROCEDURE		
DETAIL DESCRIPTION		RE	F	
ENGINEER	DATE	APPROVAL	. DA	¥TE

Shepard Road X4400 Midway X3000 Univac Park X3000

Contain a spill if you can do it safely. Keep area clear of other personnel until more help arrives. The Environmental Management group is set up with equipment and trained personnel to handle a hazardous material spill.



ECP	37016B	REV	<u>).</u>
	A		

ENVIRONMENTAL	CONTROL	PROCEDUR		
DETAIL DESCRIPTION			REF	- Carlo
ENGINEER .	DATE	APPROVAL		DATE

#### **APPENDIXS**

- I. Waste Chemical Label
- II. Hazardous Material Transfer
- III. Minnesota Waste Manifest

# TRAINING SYNOPSIS STATEMENT

TRAINING TITLE

CHEMICAL HANDLER CERTIFICATION

Total training time -- about 3 1/2 hours

CORPORATE SQUARE

TRAINING GOAL:

To provide sufficient training for employees who must transport hazardous materials through sommunally used hallways.

JOB CLASSIFICATION OF TR	AINEES :	particular contraction of the second	
MOVE CREW/ JANIT	ORS / CRIB		Training Frequency
METHOD USED:			
- WORK EXPERIENCE	·	OTHER TRAINING (	e., VENDOR SCHOOLI
CLASS/GROUP LEARN	ING .		
O ON THE JOB TRAININ	<b>G</b>	OTHER (SECIFY)	
I INDEPENDENT STUDY		AND THE PROPERTY OF THE PROPER	
PROCESS DESCRIPTION:			
SLIDE CASSETTES:			
	<ul><li>Hazardous Material</li><li>Hazardous Material</li><li>Safe Handling and</li><li>Waste Management S</li></ul>	Identification S Storage of Commy	ystem essed Gases
FILM:	- Danger Zone Your B	ack	
PROFICIENCY MEASUREM	ENT TECHNIQUES:		
ORAL INTERVIEW		r Evaluation	SIMULATION EXERCISE
O PERFORMANCE TEST	1 WRITTE	TEST	STUATIONAL CESERVATION
INSTRUCTOR'S NAME AND	QUALIFICATIONS:	A STATE OF THE STA	
Ronald W. Berndt Tom Gehl	- Sr. Industrial Hyg: - Industrial Hygiene	iene Engineer DS Engineer intern	D DSD
REMARKS			

17		OPERATIONS, T	RAINING RECORD		
MSTRUCTOR'S NAME RONALD W. BERNI	DT/TOM P.		<b>8</b> . /	DATE	3/4/83
CHEMICAL TRANS		,			7/4/03
HOURS OF INSTRUCTION					
PARTICIPANTS NAME	MUMBER EMPLOYEE	ORGANIZATION	SUPERVISOR'S	ANIL	PHONE
O. We Feel			NAME	STATION	NUMBER
211		1350	5IM FUQUA	ceois	6351
501	08795	/350	Li Fuger	665	6351
9 P. 1/2	80166	/35%	Jim Fugue	25	4351
A Pupus	80/58	1380	Jim Hugue	015	<u>(435)</u>
The state of the s	464	1350	die 7	DIS	435/
	61629	1350	SIM POQUA	ec015	6351
Remark There	55829	/350	OM FOODA	CLDIS	6351
Jun July	80136	1350	Fly C Red		456-2179
Je biden	4688	1350	Just trans	1355	1 -6351
	-		P. U		
•					
				-	
					September 1
	White the same of			A Company of the Comp	
·		*			,
					2
		:			
		. Occasion production and the control of the contro			
					A STATE OF THE STA
				/ /	Overstander of the state of the
					- Administration of the second
				·	
UDI-2721 (REV 12/73)					

**LINIVAC** 

# TRAINING SYNOPSIS STATEMENT

TRAINING TITLE

CHEMICAL HANDLER CERTIFICATION

Total training time -- about 3 1/2 hours

CORPORATE SQUARE

TRAINING GOAL:

To provide sufficient training for employees who must transport hazardous materials through sommunally used hallways.

JOB CLASSIFICATION OF TRAINEES		
1	•	Training frequency
MOVE CREW/ JANITORS /	CRIB	
D WORK EXPERIENCE	Отнея	Training (i.e., vendor school)
CLASS/GROUP LEARNING		
On the Job Training	<b>□ от</b> нея	(SPECIFY)
INDEPENDENT STUDY		
PROCESS DESCRIPTION:		
SLIDE CASSETTES:		
- Ra - Sa	zardous Material Transp zardous Material Identi fe Handling and Storag ste Management Slide	fication System
FILM: - Day	nger Zone Your Back	
PROFICIENCY MEASUREMENT T	ECHNIQUES:	
ORAL INTERVIEW	TRODUCT EVALUA	TION SIMULATION EXERCISE
D PERFORMANCE TEST	EST MARITEM EST	O SITUATIONAL DESERVATION
INSTRUCTOR'S NAME AND QUA	LIFICATIONS:	•
	. Industrial Hygiene En dustrial Hygiene Engine	
REMARKS	at Nazara (a managang managang managang managang managang managang managang managang managang managang managan Managang managang ma	

PERRY LUNIVAC



OPERATIONS TRAINING RECORD					
INSTRUCTOR'S NAME	NATIONAL STREET		and compressions and analysis analysis and analysis and analysis and analysis and analysis and analysis and analysis and analysis and analysis and analysis and a	CATE	/4/83
RONALD W RERNDI DESCRIPTION OF TRAINING				0	4/63
CHEMICAL TRANSPO	ORT TRAINI	NG 			
3 1/2					
PARTICIPANTS NAME	ruhber Karake Karake	MOTTALINAGRO	SUPERVISOR'S NAME	MAIL STATION	PHONE NUMBER
DANIEL MESZAGE	6/502	1950	J. Figua	CLOS	6351
Bru Kleen	_6/69	96		CEDIS	<u>6351</u>
Jim Wallblan	55753	1350	R. Voigt		
Cloreny R.	18564	1358	R. Voist		
EMI KRUEGE	C 6184	1350	U. FUQUA	2015	6351
Bab Shloesse	6/60	1350	J FUQUA	CCDIS	6351
,				·	
		• • • • • • • • • • • • • • • • • • •			
	0	atterior atterior and representations and atterior and atterior and atterior and atterior and atterior and att			
		<u> </u>			
t			- T		
483,000	·				
		_			
entantik kumunka Mentantik (Apaki), kanama-panaman		Annual Control of the			•
- ·					
				,	
Annewalabanian anna anna anna anna anna anna an			-		
	_			and the second s	
manaraninining nggapadga-apan panananananananananan (nggapan manananananananananananananananananan					

UDI-2721 (REV 12/73)



#### TRAINING SYNOPSIS STATEMEN

		MICLEI
TRAINING TITLE	AREA	-
1		ļ
<b>.</b>	<u>_</u>	
CHEMICAL HANDLER CERTIFICATION	PLANT 8	
TRAINING GOAL:		, , , , , , , , , , , , , , , , , , ,

To provide sufficient training for employees who must transport hazardous materials through communally used hall-ways.

JOB CLASSIFICATION OF TRAINEES	TRAINING FREQUENCY
MOVE CREW /JANITORS /CRIB	
METHOD USED:	
WORK EXPERIENCE	OTHER TRAINING (i.e., VENDOR SCHOOL)
D CLASS/GROUP LEARNING	
ON THE JOB TRAINING	OTHER (SPECIFY)
I INDEPENDENT STUDY	
PROCESS DESCRIPTION:	
	aterial Transport Rules aterial Identification System
- Hazardous M	aterial Identification System ing and Storage of Compressed Gases ement Slides
- Hazardous M - Safe Handel - Waste Manag	aterial Identification System ing and Storage of Compressed Gases ement Slides
- Hazardous Marian - Safe Handel: - Waste Manage FILM - Danger Zone PROFICIENCY MEASUREMENT TECHNIQUES:	aterial Identification System ing and Storage of Compressed Gases ement Slides
- Hazardous Marian - Safe Handel: - Waste Manager FILM - Danger Zone - PROFICIENCY MEASUREMENT TECHNIQUES: - ORAL INTERVIEW - PROFICE -	aterial Identification System ing and Storage of Compressed Gases ement Slides Your Back
- Hazardous Marken - Safe Handel: - Waste Manager FILM - Danger Zone  PROFICIENCY MEASUREMENT TECHNIQUES:  - ORAL INTERVIEW - PROFICE -	aterial Identification System ing and Storage of Compressed Gases ement Slides  Your Back  ODUCT EVALUATION SIMULATION EXERCISE
- Hazardous Ma - Safe Handel: - Waste Manager FILM - Danger Zone  PROFICIENCY MEASUREMENT TECHNIQUES:  ORAL INTERVIEW OPERIOR INTERVIEW OPERFORMANCE TEST INSTRUCTOR'S NAME AND QUALIFICATIONS: Ronald W. Berndt - Sr. Indust Roscoe Evavold - Manager of	aterial Identification System ing and Storage of Compressed Gases ement Slides  Your Back  ODUCT EVALUATION SIMULATION EXERCISE  RITTEN TEST SITUATIONAL OBSERVATION

Total training time -- about 3 1/2 hours.

ERRY & UNIVAC



	ASTRUCTOR'S NAME	OPERATIONS	TRAINING RECORD	
	RONALD W. BERNDT			6-21-83
1	CHEMICAL TRANSPORT TRANSPO	AINING	٠.	
	3 1/2	n.	Meil Stothops SI	e.ft
	PARTICIPANTS NAME EMPLOYEE NUMBER	ORGANIZATOM	PARTICIPANTS NAME HUM	OYEE ORGANIZATION
	Greg Nelson 61/98	1350	51521	29
	michael Times 704	1350	51521	27
	Mornin Paice 57514	1350	5.1521	27
	JOE CAPKO 16904	<u> 1350</u>		27
	Manufford & 3 De 3	1350		27
	BRUE LA FOUTHINE WAT	<u> </u>	BPLT# SHAFT SIS	29
	Bance Tyl 3268	1350	V0726	25
	Don. Buried 55857	/3 578	UOT26	3
	ene 72.4-1115	1350	CCD 15	25
	DAUE HELD 80151	/3 <i>5</i> 0	CCD 15	26
(	Querry Carlin 58070	1350	CC & 15	26
K	golim Drag 55629	1350	CC\$ 15	24
	game Atak 6494	1350	CC\$15	26
~	Tan Caprice 6/629	1350	CC215	21
5	Charmae Rume	27771	PITTERIB	25
	92 Fugue 1536	1350	CC\$ 15	27
Ć	Roy D. Belle 52549	1350		23
4	Lay Mashtal 55805	/350	CCB 15	20
	Rophael Mechtel 7  R.J. Knester 15382	· · · · · · · · · · · · · · · · · · ·		
	RJ Knester 15382			27
		4		
		No.		·
-	UDI - 2721 (REV 12/73)		PA	AGE 333

SPERRY LUNIVAC

TRAINING SYNOPSIS STATEMENT

TRAINING TITLE

AREA

CHEMICAL HANDLER CERTIFICATION

PLANT 8

TRAINING GOAL:

To provide sufficient training for employees who must transport hazardous materials through communally used hall-ways.

JOB CLASSIFICATION OF TRAINEES	TRAINING PREQUENCY
MOVE CREW /JANITORS /CRIB	<u> </u>
METHOD USED:	
□ WORK EXPERIENCE	OTHER TRAINING (i.e., VENDOR SCHOOL)
CLASS/GROUP LEARNING	
ON THE JOB TRAINING .	OTHER (SPECIFY)
INDEPENDENT STUDY	
PROCESS DESCRIPTION:	
- Safe Hande	Material Identification System eling and Storage of Compressed Gases agement Slides
PROFICIENCY MEASUREMENT TECHNIQUES:	
ORAL INTERVIEW	PRODUCT EVALUATION SIMULATION EXERCISE
☐ PERFORMANCE TEST 🛛	WRITTEN TEST
INSTRUCTOR'S NAME AND QUALIFICATIONS	
	strial Hygiene Engineer DSD of Occupational Health Programs DSD ental Management DSD Tim Morris - Safety
REMARKS	Engineer - Semi-Conducto

Total training time -- about 3 1/2 hours.

ERRY-LUNIVAC SERVICE S

1		OPERATIONS TRA	AINING RECORD		AMPANANA TITOTONIA NA TITOTONIA
INSTRUCTOR'S NAME  RONALD W. BERNDT  6/8/83					
RONALD W. BE		MP 4 4814 870			
CHEMICAL TRA	MASKOKT	TWINING			
3 1/2	800 a Mar				uunuu kan aadan kuun Meedele ka ka ka ka ka ka ka ka ka ka ka ka ka
PARTICIPANTS NAME	MARBES EMBTOLEE	ORSANIZATION	PARTICIPANTS NAME	employee Rumber	Organization
Squee Minte	\$1004	Flort Dervices			
Muly Bring	5/2/1	" "		A AMERICAN CONTRACTOR	
Marlin Mars	55767	" "			
DALCOK.	3778	111			
Dick Sur	80125	11 31	·	-	
Chic GORKE	37754	10.10.			FO
1	55760	PANT SENEE	The state of the s		
ALBARAETI	23/69	Plunt Der			
Bruce Fredricks -	8009	1550			
Gene Kovacs	35990	^			
Eles Pelman	37553	# 350	•		
24502	283CC	1550			- Control of the Cont
BALL Voist	7741	1350			
B. Garcia	80018	10			
MO Newell		11			
	8 8 8				
	· ,				) 
		·	·		
			A Control of the Cont	77777	open mentet still filt de die der de die de die die die die de de die die
			·		·
	- 1000 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 -				The second secon
			1		

UDI-2721 (REV 12/73)

SPERRY LUNIVAC

## TRAINING SYNOPSIS STATEMENT

TRAINING TITLE

AREA

CHEMICAL HANDLER CERTIFICATION

PLANT 8

TRAINING GOAL:

To provide sufficient training for employees who must transport hazardous materials through communally used hall-ways.

JOB CLASSIFICATION OF TRAINEES	zayımangınanzıraya bigilikli kalmidisi anındığı anındığı zazayını azazının kazam	Tricon Number of the Community of the Co	TRAINING FREQUENCY
MOVE CREW /JANITORS	/CRIB	·	
METHOD USED:			
WORK EXPERIENCE		OTHER TRAINING	ia., VENDOR SCHOOL)
CLASS/GROUP LEARNING			
ON THE JOB TRAINING		OTHER (SECIFY)	
I INDEPENDENT STUDY			
PROCESS DESCRIPTION:			
- Sa - Wa	fe Handeling ste Manageme nger Zone Yo	nt Slides	of Compressed Gases
	o tage 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
ORAL INTERVIEW		T EVALUATION	SIMULATION EXERCISE
O PERFORMANCE TEST	S) wante	n test	I SITUATIONAL DESERVATION
INSTRUCTOR'S NAME AND QUAL	JFICATIONS:		
Ronald W. Berndt - S Roscoe Evavold - M Dan Mac Donald - E	lanager of Oc	cupational Hea	
REMARKS	e in the second	inmit II Mitti (Mindemoonti i kim II kissada limit magaa aygi kili yaa ga хүү алгаар	Engineer - Semi-Conducto

Total training time -- about 3 1/2 hours.

-ERRY \$-UNIVAC



	OPERATIONS	TRAINING RECORD	*	dd 1996 ac ann an gwyngol eith y mae ag 1996 ac an am y amber 2000 ac an am ar an ar an ar ar ar ar ar ar ar a Can ar ar ar ar ar ar ar ar ar ar ar ar ar
RONALD W. BERNDT	N Steel and Association (Control of the Control of		DATE	
RONALD W. BERNDT DESCRIPTION OF TRAINING		and the second s	1.6/	<u> </u>
CHEMICAL TRANSPORT	TRAINING			b.
3 1/2 PARTICIPANTS NAME EMPLOYEE	## SD C A A A A SD C C C C C C C C C C C C C C C C C C		EMBLOYEE	
A A	ORGANIZATION	PARTICIPANTS HAME	RUMBER EMPLOYEE	NOITASINASRO
Weller Cheshing 554	16 :			
Julie Bally 8000		·		
May Hange 65300			-	
2 7/12 254/8	p.			
FBALL 37081		· ·		,
•	·	`		
·				. **
			·	
			3	
				-
	-		`	
·				
				- Andrews
	A			
	,			
		_		

337

PACE

SPERRYSLUNIVAC
----------------

## TRAINING SYNOPSIS STATEMENT

TRAINING TITLE

Chemical Transport Certification Program TRAINING GOAL:

Sperry Park

To train move crew on proper and safe methods of handling and moving hazardous chemicals.

JOB CLASSIFICATION OF TRAINEE		
L Move Crew	•	TRAINING FREQUENCY
METHOD USED:		
WORK EXPERIENCE	OTHER TRAIL	NING (i.e., VENDOR SCHOOL)
CLASS/GROUP LEARNING		
DAINIART BOL SHT NO	OTHER (SPEC	iifY)
O INDEPENDENT STUDY		
PROCESS DESCRIPTION:		
Move chemicals from	m stores to work areas	
PROFICIENCY MEASUREMENT T	TECHNIOLIES:	
ORAL INTERVIEW	PRODUCT EVALUATION	SIMULATION EXERCISE
		I SITUATIONAL DESERVATION
INSTRUCTOR'S NAME AND QUA	LIFICATIONS:	
Ronald W. Berndt Dan Mac Donald		•
REMARKS		
	•	

**FUNIVAC** erndt/Roscoe Evavold/Tim Morris/Dan MacDonald 05/13/83 ON OF TRAINING mical Handler Certification OF INSTRUCTION MOVIE - BANGER ZONE YOU back SILDE - HARARDONS MATERIAL TRANSPORT RULES, HMDF. Safe Handling of Compressed Gases employee Humber employee Humber PARTICIPANTS NAME ORGANIZATION PARTICIPANTS HAME TooleRIB 1350 1350 TOOL CEIB 1350

UDI-2721 (REV 12/75)



## TRAINING SYNOPSIS STATEMENT

TRAINING TITLE

AREA

Chemical Transport Certification Program

TRAINING GOAL:

Inform employees of proper chemical handling procedures.

JOB CLASSIFICATION OF TRAINEES	,	TRAINING FREQUENCY
METHOD USED:		
WORK EXPERIENCE	O OTHER TRAINING	G (i.e., VENDOR SCHOOL)
CLASSIGROUP LEARNING	- white programmes and the contract of the con	*
ON THE JOB TRAINING	O OTHER (SPECIFY)	÷ .
INDEPENDENT STUDY		
PROCESS DESCRIPTION:		
•		
PROFICIENCY MEASUREMENT TE	CHNIQUES:	
ORAL INTERVIEW	E PRODUCT EVALUATION	SIMULATION EXERCISE
O PERFORMANCE TEST	Q WAITEN TEST	SITUATIONAL DESERVATION
NSTRUCTOR'S NAME AND QUALI	FICATIONS:	
John Davis - Safet Ron Berndt - Indus	y Engineer trial Hygienist	
REMARKS		,
This training was	scheduled so that the sup	pervisors who would

have employees in training could give their impressions of

the training.

4.

OPERATIONS TRAINING RECORD

R. W. BERNDT, B. CORNWALL, J. C. DAVIS, D. MACDONALD, T. MORRIS  8-23-82					
DESCRIPTION OF TRAINING CHEMICAL TRANSPOR	T CERTIF	ICATION PROGRAM			
HOURS OF INSTRUCTION 3 HOURS			e saat daa saa saa saa saa saa saa saa saa saa	i mara na mara na mara na mara na mara na mara na mara na mara na mara na mara na mara na mara na mara na mara	A STATE OF THE STA
PARTICIPANTS NAME	employee Humber	Organization	PARTICIPANTS NAME	HUMBER EMPLOYEE	ORGANIZATION
Em Bern St	63278	Occupational Halth			
Vicki Chowingrd		Occupational Health			
Norm Ray	1297	Sailtie malt.			
Da Tweed	19740	11 11			
David Pates	37333	Skills Engineering			
Golph Voit	7741	Failer mis			;
Bonas Leis	22301	Occupational 4	KL714		
			·		
					A Part of the Art of t
					The Control of the Co
			,		
					4
					ese most and the substantial and the substanti
**************************************					
			A STATE OF THE STA		,
A STATE OF THE STA					, and the second
	<u> </u>				
			·		
		***			
			·		
UDI - 272: (REV 12/73)	1			PAGE 3	<u> </u>

#### OUTLINE

#### INTRODUCTION:

JOHN & RON

- 1. CHEMICAL HAZARDS SLIDES
- 2. CHART AND CARD NON COMPATIBLE
- 3. SAFE HANDLING

Cylinders Drums

4. SAFE DRUM HANDLING - SLIDES

ROGER & DAN

- 5. WASTE PICK UP.
- 6. SHIPPING REQUIREMENTS TRUCK.
- SPILL CONTROL PROCEDURES.

JOHN & RON

8. FIRST AID.

ROGER & DAN JOHN & RON

9. QUESTIONS

3:30 Monday, Tuesday, Wednesday - July 6, 7, 8, 1981

EQUIPMENT:

SLIDE PROJECTOR TAPE PLAYER SCREEN

JCD/pyg

## DRUM HANDLING SAFETY

## Response sheet

l.	( ) Your foot ( ) Your body	•	6.	( ) Cross hands a ( ) Don't cross h	nd feet ands or feet
2.	( ) Hands toget ( ) Hands apart	her	7.	( ) Body close ( ) Body far away	
3.	( ) Bare hands ( ) Wear gloves		8.	( ) Body ahead ( ) Body behind	
4.	( ) Pull ( ) Push	· .	9.	( ) Yes ( ) No	
5.	( ) At chime he ( ) Higher than	ight chime height	10.	( ) At chime heig ( ) Higher than c	ht hime height
		Review	Sect	ion	
<b>9</b>	Breaking drums ( ) Yes ( ) No		3.	Palletizing drums ( ) Yes ( ) No	
2 .	Rolling drums ( ) Yes ( ) No		4.	Dumping drums ( ) Yes ( ) No	
	***************************************	DRUM HAND	LING	skills	. 1222 - 1223 - 1223 - 1223
**	. •	· ·	,		
1.	Breaking drums - Hands apart - Shoulder: o		3.	Palletizing drums - Bottom chime - Shoulder low, drum - Watch for pin	high close to
2.	Rolling drums - Proceed slo - Body close - Don't cross	owly and ahead hands or feet		Dumping drums - Body moves fo drum - Hands on top chimes	

k4616B-7

StAR 3:30 FA Finish - 4:40 PA

Ronald W. Berndt

#### ATTENDANCE ROSTER

Date: 6 Jul 8/	
Purpose: Chemical Handling Class - Move Crew/Janitorial Crew	
Training requirements according to 40 CFR264.16	To Love Control
Instructors: Dan E. MacDonald	

Roger J. Martin

Clock Number	Department
53857	MOUE CREW
37769	more crew
37524	Jantise
6185	<u> </u>
37553	1357
61694	1350.
DO016	1350
803 9	1380
80020	1350
61073	1350
55753	1350
8000 T	1350
61544	1350
80005	(3.50)
80021	1350
61486	1350
6/657	1350
55825	
58074	1310
24268	1350
	53857 37769 3753 / 61677 37553 61694 50016 80020 61073 55753 8007 61544 80021 61544 80021 61544 80021 61557

ı	<i>[</i>		<b>&gt;</b> 1
Date: (	200	$\mathcal{L}$	) (

Purpose: Chemical Handling Class - Move Crew/Janitorial Crew

Training requirements according to 40 CFR264.16

Instructors: Dan E. MacDonald John C. Davis

Roger J. Martin Ronald W. Berndt

Name	Clock Number	Department
BOB MERCK	58321	MOVE CREW
Don. Dahm	61652	Jantor
Jeny 5 Samuelson	61540	Move Crew
Acin Mulligan	6/66 (	Janeta
SC HOPP	30026	1350
alguid Store	61076	1350)
Levy Cachine	80044	conp son
Tiene too	61422	. 1350
al Slepters	61458	1350
Mohsch ho	64 98	39973
Or Me Farand	50427	1350
Buchaur	80023	1350
al factl	58030	1350
Peter Cook	50924	1350
I Bath	6/690	1350
Thurses golf for	16325	1350
mike tim	58049	1350
Donks River D	80010	1352
1) / ansfor	55758	1350
Till the	61479	

Date: 6 Aug 8/					
Purpose: Chemical Handling		ing to 40 CFR264.16	<del>(11111)</del>		
			economic <sub>olo</sub> s		
Instructors: Dan E. MacDon: Roger J. Mart:		John C. Davis			
Roger o. Marc.	<b>1.</b> I 1	Ronald W. Berndt	in the second se		
Name	Clock Number	Department			
Jelenn Gross	55829	den Tabor			
DON Erichan	22262	cub			
by trammo	6/681	Den labor			
This Hermann	8995	Jan to			
Bd. Schloersen	61659	They lake			
Gett Birelt	1043	Gen. Liba			
Jerry Small	6/645	1350	42/		
Horand Hopp	80027	1350			
Les Bachman	61688	Corp			
audrey Carlson	58072	4			
Lake Hilm	6164 9	Peritor			
Euge Donner &	61664	eng ly			
GEORGE BORNH	38813	CORP. SO.			
			Michael		

Trpose. Criting and 212	ling class and di	e Crew/Janitorial Crew ng to 40 CFR264.16
		John C. Davis
nstructors: Dan E. MacD		Ronald W. Berndt
Roger J. Ma		1/03/04/05/11
AN ame	Clock Number	Department
When Doubne	m 28/80	dantor
General & Rich	0 52640	Mone Crul
The Fork	1 37754	// ((
M. E. a ent Trong	35990	1)
a Character.	33169	Janton
Lett & WLace	4 61517	Move Crew
Mad Klink	1 61663	1
A davie	12415	11
Aren & Davi	61458	
Shorley Brins	15/211	Janitor
Duk Warneshe	61573	Jan
Charles a. Mart	1 55767	Janeter
mad & more	L 61585	1 fanta
Prie Course	80036	fail
Bill Garcia	80018	Vanitor
James Sealer	mbo 59574	Janitor
Klaca C. Shelle	<del></del>	Janitor
Steve Mohr	80046	Janitor
Mart their	41169	Sintatur Engineer
in/lest when	6/637	SAME AS ABOVE

Date: 7/7/8/				
Purpose: Chemical Handling Class - Move Crew/Janitorial Crew				
Training requirements according to 40 CFR264.16				
Instructors: Dan E. MacDonald John C. Davis				
Roger J. Martin Ronald W. Berndt				

Clock Number	Department
61860	Familiar
61462	Jan Tor
5/938	1350
80032	Sanitor
61623	Manitor
61159	later
37781	1350
67494	/350
61562	1350
3708/	1350
CHARLE IN	1350
p1450	1350
124/52	1350
? 1	
;	The state of the s
İ	
	61660 61462 51938 60032 61159 37781 61494 601562 37881

Date: 7/8/8/
Purpose: Chemical Handling Class - Move Crew/Janitorial Crew
Training requirements according to 40 CFR264.16
Instructors: Dan E. MacDonald John C. Davis
Roger J. Martin Ronald W. Berndt

Name	Clock Number	Department
Duce Blies.	6/695	Cartino D
for Ran	80025	11
Earl Trueger	61584	
Jerry D. Bellen	36381	Caritar
Para Malnoti	61674	Daniter
J. Grundtner	80017.	Jan tor
Samuel Combait	14/4	JANITOR
Rapha Malto	55765	PIZ Sev
L. Mashington	31607	Puriter
WE Judin	SPER	More Colin
Brut a 15100	32662	DIST SERV.
That Below	50038	en torial
m. Moreles	3/203	Fronte of
R & Kaster	15382	May Coul
Wate In Their	080045	Janitor
John Whatnan	19116	EAC. MAINT.
Thomastila	11196	Steinter

#### APPENDIX H-6

TRAINING HAZARDOUS MATERIALS COORDINATORS



ECP_	37016C	RE\	/. <u> </u>
PAGE	1	OF 2	

ENVIRONMENTAL COI	NTROL PF	ROCEDUR		
DETAIL DESCRIPTION HAZARDOUS MATERIALS COORDINA	TOR TRAINING	(B)	REF	
Dan E. MacDonald	2 DATE 3/28/83	ASPBOTALL V	Nortu	4/4/83
				7 /

- I. Introduction Environmental Management
- II. Coordinators Duties
  - A. Waste Chemical Labeling explain how to properly fill out label.
  - B. Regulations explain new regulations.
  - C. Enforcement.
- III. Information Systems MAPPER
  - A. Information Available
    - 1. Hazardous Material Information.
      - a. Shipping Information Rid Type B
      - b. Safety Information Rid Type I
    - 2. Hazardous Waste Dock Log
      - a. Solvent Separation
    - 3. Hazardous Material Inventory
    - . Access JHMDF, 100, DATA
- IV. New Chemical Ordering Procedure
  - A. Order Form
  - B. Chemicals in system requisition to Inventory Supply
- V. Inter-Plant Truck-Hazardous Material
  - A. Hazardous Material only.
  - B. Truck driver trained on hazardous materials.
  - C. Hazardous materials dock coordinator.
- VI. Spill Procedure
  - A. Call Emergency Number x3000



ECP_	37016C	RE	v. <u> </u>	
0401	- 2	٠. '	)	

ENVIRONMENTAL CONT	ROL PE	OCEDUR		
DETAIL DESCRIPTION HAZARDOUS MATERIALS COORDINATO	REF			
ENGINEER Dan E. MacDonald	DATE 3/28/83	APPROVAL	<u>a</u>	DATE

### <u>APPENDIX</u>

- I. WASTE CHEMICAL LABEL
- II. RID TYPE B
- III. RID TYPE I
- IV. RID TYPE C
- V. HMDF ACCESS
- VI. NEW CHEMICAL ORDER FORM

======LNVAC

ECP 27016C REV.

PAGE \_\_\_\_\_OF\_\_\_\_6

	ENVIRONMENTAL	CONTROL	PROCEDUR	COMMENTS OF THE PROPERTY OF TH
ĺ	DETAIL DESCRIPTION	2		REF
ì	**	A	an Marian dimension and	

Hazardous Materials Coordinator Training

ENGINEER MacDonald

13/4/8/ APPROV

DATE

#### Itinerary

- I. Introduction
  - A. Regulation Hazardous Materials
  - B. Review Updating old procedures
  - C. Explain new procedures
  - D Introduce Environmental Management Personnel
- II. Hazardous Material Disposal
  - A. Hazardous Material Coordinators Duties (Hand out)
  - B. Facilities used
  - C. Hazardous Material Disposal Procedure
  - D. New Methods Disposal
- III. Ordering New Checmicals
  - A. Follow DSD Procedure M.M.
  - B. Information inputed HMDF
  - IV. Hazardous Material Interplant Truck
    - A. Dedicated Hazardous Material Truck
    - B. Pick up from vendors
  - V. Spill Procedure ECP 37009
    - A. Contact Guards in Event of Spill
    - B. Or Environmental Management
    - C. Have equipment and personnel to clean up
  - VI. Requirements of Coordinators
    - A. All personnel using hazardous materials must have training and must be recorded. Rooster 1 week new chemical.
    - B. Will be sending out old list chemical usage need it updated and returned.
    - C. Help in communicating new chemicals and new processes.

VII. Conclusion

Application of April 1985	an Maria	**************************************	ango.			2 88	B. 5	8%	/AC
THE PERSON NAMED IN				1	-ander those	8 BE	8	#%	LLE
*******	phones:	4 100	. AD	5	The same of the same of	Committee of the	₩.	₩ ₩	Second Courses

ECP	3701	6CR	EV	
PAGE	2	OF	6	*

EN	/IRONMENTAL	CONTROL PI	ROCEDUR		
DETAIL	DESCRIPTION			REF	
Haza	rdous Materials	Coordinator To	ainino		
ENGINE	m () m2	DATE /2/8/	APPROVÁL		 DATE

#### .I. Introduction

This training session is for all Hazardous Materials Coordinators. The EPA (Environmental Protection Agency) and DOT (Department of Transportation) have implemented new hazardous material regulations. All personnel that handle these materials must have training because of the regulations. In this training session we review our old procedures and their revisions on the disposal, ordering and shipping of hazardous materials. I explain the new procedures on the MAPPER information system and hazardous material spills.

The personnel in Environmental Management are:


Roger Martin, X4654 UP, pager 19
Dan MacDonald, X4714 SR, pager 13
Mark Wilson, X4625 UP, pager 54
Greg Grinols, X4625 UP, pager 54
Bill Polta, X4656 SR, pager 24
Roger Ranzau, X4656 SR, pager 32
Reid Oines, X4625 UP, pager 68
Mike Medina, X4656 SR, pager 24
Mike Gold, X4625 UP, pager 54

#### II. Hazardous Materials Disposal

The duties and policy for Hazardous Material Coordinators is in the packet, handed out. Each coordinator should review the packet. By following these procedures you help in making the disposal of hazardous waste easier. Univac's own pretreatment systems at Shepard Road and Univac Park treats process rinses, acids, and alkalines. We treat 150 GPM at Shepard Road and 30 GPM at Univac Park. The systems generate sludge at a rate of 924 drums/year at Shepard Road and 20 drums/year at Univac Park. A facility in the Chicago area treats and landfills our chromic acid. Shepard Road has 120,000 gallons/year and Univac Park has 2,700 gallons/year at a cost of 48¢ gallon.

Landfilling sludges and caustic solvents cost \$55/drum, plus \$33 for the container cost. The hazardous material secured landfill in use for these materials is in Chicago area. A secure landfill in Alabama buries our PCB capacitors, cyanide solutions and A-20 stripper at a cost of \$129/drum plus \$33 for the container.

A solvent recovery facility disposes of our chlorinated, flour-inated and organic solvents. Univac receives a refund when the solvents are at least 40% recoverable. We get a credit of \$.18/pound for freons down to \$.08/pound for methylene chloride and trichloroethane. The organic solvents like isopropy alco-



ECP	<u>37016 c</u>	) 	REV	ar aman Salliosavatar
PAGE	3	OF	6.	

	ENVIRONMENTAL	CONTROL P	ROCEDUR		Control of the contro	N. S. A. S.
	DETAIL DESCRIPTION			AEF		
The second second	ENGINEER	DATE	APPROVAL		g g	DATE

hol, acetone, MEK, toluol and xylol a \$.50/gallon refund is received. Unnecessary mixing of solvents should be prevented at all times. A mixture of flammable and chlorinated solvents cost \$100/drum for disposal. Incineration of a mixed flammable solvents cost \$15-\$30 when not recoverable. High temperature oils used in soldering operations cost \$30/drum for incineration.

A crankcase oil program is in effect for Univac and Univac employees. Employees can bring in used crankcase oil to be dumped. A local asphalt company burns the oil and pays us for it. The funds received for the oil is put into the employee's recreation fund. A drop off point is at each plant.

Hazardous material disposal procedure must be followed. The waste chemical label must be filled out completely. The hazardous material coordinators are the only personnel authorized to sign the waste label. You are the only personnel covered by Sperry Insurance as the authorization indicates.


A new procedure is included in your packet explaining how to gain access to a chemical data system. The system is a MAPPER program. Using the procedure you can call up on a computer terminal all information needed to fill out the waste chemical label. Occupational Health also has a parallel data system. If information for a hazardous material is not in the system give us a call and we can get you that information.

Developement of a new MAPPER system has begun. It will track and tabulate the disposal of hazardous materials. With this system we can tell which departments are not doing a good job of separating their wastes.

The Environmental Department is always looking for better methods of disposal, reuse or reclaimation of our wastes. We are investigating a chrome regeneration system which plates out the copper. Methods for recovery of metals from our sludge and scrap PC boards are being pursued.

#### III. Ordering New Chemicals

The procedure for ordering hazardous materials, is in the revision stage to make it work better. When ordering hazardous materials use the New Chemical Information form. The form when used with the procedure will inform Occupation Health and Environmental Management of a new chemical coming into our facilities. We can then have safe handling method for employees and methods for disposal of these materials. The procedure also allows us to get the necessary information



ECP 37016C REV	
EPL	·

PAGE	4	ΩF	6	

ENVIRONMENTAL CONT	ROL PR	OCEDUR		
DETAIL DESCRIPTION			AEF	
ENGINEER .	DATE	APPROVAL	•	DATE

into the MAPPER system.

#### IV. Hazardous Materials Interplant Truck

A dedicated hazardous material truck started in August. The truck moves all hazardous materials between plants. It also picks up chemicals from vendors. The Environmental Management department is the dispatcher for the truck so when you need its service call us. Whenever you have something to ship, use a Hazardous Materials Transfer (HMT). The information needed to fill out the HMT is in the MAPPER system.

#### V. Spill Procedure ECP37009

A procedure for hazardous material spills is included in the information handed out, it should be reviewed. In the event of a spill contact the guards at:

Shepard Road X4400 Midway X3000 Univac Park X3000

or Environmental Management department at:

Shepard Road X4656 or X4714 Midway call Shepard Road X4656 or X4714 Univac Park X4625 or X4654

Environmental Management has the equipment and the personnel with the training for handling a hazardous material spill.

#### VI. Requirements of Coordinators

As coordinators, we want you to do three things when you return to your department. First have a training session with all personnel in your department handling hazardous waste materials. All personnel receiving training must sign an attendance roster included with packet handed out. Send the attendance roster back to Roger Martin at UlN14 when training is completed. Secondly, we will send an old list of your chemical usage, we want you to update it and send it back to Roger Martin at UlN14. Thirdly, would you help us in communicating all new chemicals and new processes to us.

#### VII. Conclusion

In conclusion, Univac is doing an excellent job of protecting the environment. Continue to help us to do a good job. With your authorization as a hazardous materials coordinator,



ECP 37016C REV. .....

		A.V.					PAGE	5	0	F	6.
ENV	RONM	ENTA	L CON	ITROL	PR	OCEDUI	RE				
DETAIL D	ESCRIPTION .		472.				AEF			and the second s	
NGINEER	<b>*</b>	The state of the s		DATE	7	PPROVAL		owledita—pupa	o o	A(A)	DATE
	,		,		<u>,                                     </u>					·	
	Univac Willful	Will lv wr	stand	behind	You	unless	someth	ning	is	done	
	W 40 40 40 40 40 40 40 40	- A - A - A	A 10 4 4				ę				
		•									
								*			
	3			•		•					
						-					
			•				•				
			<del>-</del> .	•					•		·
•	•	-		-							
										* **	
			ø						•		,
•											•
٠.											
											:
			• ,								
	·										
	•										

UD1-3938



ECP 37016C REV.

ENVIRONMENTAL	CONTROL PROC		
DETAIL DESCRIPTION Hazardous Materials	Coordinator Train	ning Ref	
ENGINEER .	DATE . APP	ROVAL	DATE

#### APPENDIX

- I. List Environmental Management Personnel hand out
- II. Wast Chemical Coordinator duties hand out
- III. Statement of policy PM-4.5.18 hand out
- IV. Disposal Procedure ECP 37001 hand out
  - V. Waste Chemical label transparency
- VI. Mapper System HMDF ECP 38017
- VII. Mapper Mode 382, 1B transparency
- VIII. Mapper sample screen mode type B transparency
  - IX. HMDF Access transparency
  - X. Dock Log transparency
  - XI. WRR Analysis transparency
  - XII. Emergency Response Procedure ECP 37009 hand out
- XIII. Attendance Roster hand out

# SPERRY UNIVAC DEFENSE SYSTEMS DIVISION WASTE CHEMICAL COORDINATOR DUTIES

#### 1.0 PURPOSE

The purpose of the Waste Chemical Coordinator is to have at least one representative from each cost center that uses chemicals, knowledgable about rules and regulations concerning hazardous chemical handling procedures.

#### 2.0 DUTIES

- 2.1 Act as a coordinator for the cost centers assigned by the department manager and the Environmental Management Department with regard to hazardous material control.
- 2.2 If authorized in writing according to Sperry Univac policy, P.M.-4.5.18, certify that the contents of waste chemicals containers are as stated on waste chemical labels, UD1-2744 or UD1-3635 and insure that the label is properly completed and attached to the container.
- 2.3 Instruct all of the personnel affected in the cost centers represented in the policies and procedures of hazardous material handling.
- 2.4 Have extensive knowledge of all of the chemicals and processes used in the areas of responsibility.
- 2.5 Encourage conservation and good housekeeping practices in the areas of representation.

## HAZARDOUS MATERIAL COORDINATOR

Al de la contraction de la con		net territori (1909) gamma al de 1909 minorano de la cista de 1909 agrama para la competencia ministra procesa				en en en en en en en en en en en en en e
DEPARIMENT	NO.	Manager	PLAKT	1st SHIFT	2nd SHIFT	3rd SHIFT
Urfice Services	1330	W. W. Becker X4647 UlQ13	Al1	E. J. Grosam		
ant Services	1350	M. L. Levinski X4648 UlQ14	SR M	J. D. Belisle N. M. Repp J. H. Whitman	R. D. Goddard J. L. Fugua G. T. Braum	
ers Turk			OP SR	L. T. Handwerk R. W. Voigt M. D. Newell	F. E. Redepeni	Lug
			UP SR	R. K. Sporre J. L. Botnen		
Transportation Services	1360	J. L. Zeimet X4664 UlP14	All	J. L. Zeimet		enge gegende and and and and and and and and and and
P.C. Fab Production	2111	S. R. Kulyas X4594 S1F22	SR	B. M. Bahr D. A. Jersak D. L. Thorkildso	M. M. Keske B. Perseke	D. E. Richards R. Mansager
Metal Fab	2121	S. R. Kulyas X4694 S1F22	SR M	D. L. Lingofelt H. H. Conrad	C. E. Kalka	
Sembly	2122	M. C. King X4349 S1F17	SR	R. K. Martin G. M. Jenson D. J. Johnson	R. L. Radloff B. A. Bernloch	I
Final Assembly	2123	R. J. Sherlock X4302 S1F17	SR SR	C. J. Nicosia L. E. Swenson		
Core Matric	2122	M. C. King X4349 S1E09	SR	B. Alsleben		
material Control	2312	C. O. Babb X4774 S1RI5	AL	G. J. Bryse D. Pozega	· Company and the company of the com	
ripping	2350	R. F. Green X4562 S1L18	Al:	D. D. Hywald		
dvanced Memory	2640	M. C. King X4349 S1E09	SR	G. O. Bide W. R. Patrick		
. C. Lab Production	281	8. Teply 12972 UIK16	UP	D.M. Manikowski N. P. Dohm		
Film Memory Dep.	283	R. E. Tice X4501 S1A01	SR	M. W. Neuman D. A. Camek	G. E. Dubrall	D. F. Fern
Mfg. Techniques	284	C. J. Bukkila X4156 S1A01	S	L. C. Zierhut	the second secon	
YK-44 Pre-Production	262	O C. J. Bukkila X4156 S1AO1	SI	D. B. Erickson		
			A STATE OF THE STA		PAGE	360

## HAZARDOUS MATERIAL COORDINATOR

DEPARIMENT	NO.	MANAGER	PLANT	lst SHIFT	2nd SHIFT	3rd SHIFT
Factory Support	2842	W. H. Kircher X4727 SlL18	A11	T. Burger		
rnototype Mfg.	2860	R. S. Cerar X2890 U2T20	OP	W. J. Nelson	M. A. Hogland	
furbishment	2862	O.M. Kelzenberg X7656 M1F34	M	H. H. Conrad B. L. Bahls	produce the second seco	
cototype Cust. Sup.	2862	O.M. Kelzenberg X7656 M1F34	M	H. H. Conrad B. L. Bahls		
istomer Repairs	2870	R. L. Chapman X4673 S1F02	SR	R. W. Zamudio		
Documentation Service	4370	K. A. Behnke X3860 UlK13	AII	R. M. Eng		· · · · · · · · · · · · · · · · · · ·
Reproduction Service	4371	P. L. McCarthy X3978 UIK13	UP .	R. M. Eng		
Projecto/Microfilm Serv.	4372	D. P. Radle X3701 UOP15	UP .	R. M. Eng		• •
ublication Service	4375	D. P. Radle X5701 UOP15	UP	R. M. Eng	and desired to the second seco	
uplicating Services	4376	P. L. McCarthy X3978 U1K13	All	R. M. Eng		
icrofilms Services	4341	D. W. Laminen X3979 UIK13	UP.	R. M. Eng		Po-po-
<sup>p</sup> C Artwork Lab	4330	R. E. Langer X3808 U2S20	UP.	D. C. Finstren		De la companya de la
Chemical Engineering	4350	R. E. North X4574 U2P22	OP*	E. R. Quam		and of the state o
Material Eng.	4351	D. A. Domrose X4542 U2P12	UP*	<b>.</b> .		And the second s
_lect. Comp. Eng.	4351	K. L. Asplund X3701 U2P22	UP	E. R. Quan		
SI/Hybrid Developmen	t 7325	D. M. Meyer x2787 U1W22	UP	J. A. Carow		
A Leal Sciences	4440	S. J. Lins X2979 UZP26	UP		on the control of the	900 P
'OS Processing	726	J. P. Victorey X4140 Y11B1	7 UP	V. Thompson P. I. Weyandt	J. A. Strempke	K. Jennings
	Ť	•		<u> </u>	<u>.                                      </u>	•

## HAZARDOUS MATERIAL COORDINATOR

	varana da manda lakiji muuda ja			W. W. W. W. W. W. W. W. W. W. W. W. W. W		· . · ·
DEPARTMENT	no.	MANAGER	PLANT	lst SHIFT	2nd SHIFT	3rd SHIFT
enotomask Lab	7372	N. Garaffa(Jr.) XZ716 ULX26	UP	E. J. Hillman	R. Reller	
polar Lab	7355	E. D. Haygood X4238 U2X26	UP	M. Schow N. P. Decker L. A. Heuer	L. O. Smith	T. Syrstad
Luspection Engineer	6406	L. R. Quam X4343 S1F02	SR	F. M. Sos	·	pleasuring of proposed states of the states
ceiving Inspection	6521	N. J. Tillges IA949 S1P17	SR	G. Hill E. Dzielsky	D. Timm	
ilure Analysis	6432	J. M. Gorres X4630 SIF07	SR	D. West U. Siriywasakdi	-	
ores	2311	C. O. Babb X4774 SIK15	UP SR SR SR	K. C. Wieden S. L. Capaul		
Co			M	1 .		
Clearwater Restricted	·			E. Bailey J. Conover		en en en en en en en en en en en en en e
· · · · · · · · · · · · · · · · · · ·				N. Huu R. Laatsch L. Lee		
	شعرت میشده به چارد.			C. Mattiz R. Owens M. Roofner C. Sisco		grigoria de la composição de la composiç
				J. Tanner B. Brown	Annual Property of the Control of th	
learwater Authorized			to in the second second	L. Becraft L. Knapp		
			Bergermann (Alberta and Alberta  R. Nepowada J. Willert M. Ayers L. Smith H. Dawkins			
		e de la companya de l	mayor binara changa a changa a changa a changa a changa a changa a changa a changa a changa a changa a changa a	D. Tisher M. Andrews C. Thomas D. Rivers		
	o gargetine de demonstrative de la constante de la constante de la constante de la constante de la constante d		· ·		PAGE	362

Date: 12/	/7/83	
Purpose: Wa	aste Chemical Coordinator Train	ling
Instructors:	Roger Martin	
_	Mark Wilson	

Jen Janear 15268 Material Engineering	Name .	Clock Number	Department
Istan Janaan 15268 Material Engineering	Vellarous	19535	Materal Engineering
	Stan Janear		Material Engineering
	V		0 3
	•		
		N. C. C. C. C. C. C. C. C. C. C. C. C. C.	

# WASTE COORDINATORS MEETING

DAN MAC DONALD ROSER MARTIN

Nane

Group

3/30/83

James Roy Headbarry
Nech P Drekere
Mike Schow
Del Finstven
LARRY ZIERHUT
RALF ENG
X SUSand Capaul
X Bill Melson
Elward Hillman
RICHARD DEAN
Tom SYRSTAD
Jamy Smith

Bipolar Opento

Bipolar - 7352

Bipolar - 7352

C.C. 4330 Design Eng. Services

AMT - CC 284/

- CC 4370-71-72-75-76

Stones Plt-1

Inoto Type 1860

Phatomack

Physical Sciences CC 4440

Phatomack

Bipolar

Bipolar

Bipolar

# DAN MAC DONALD ROSER MARTIN

and the second	WASTE COORINATOR	S METING	3/	19/83
	NAME		JAME DE	
	Lord Dans	Tools +	Sujejela	23/2
<u> </u>	Dewell Bryen		Supplies	
	Sty must	Cur Res	m 29	70
	Morrace Hoglind		28	
	Wile Helmann	The second of the second of	1	
	MIKE BUKKISA		CIRCUITS	
	Harles Course	I Taile	Atab-3	
	Bob Bornlock	Size P.C. /	755y 2120	
	Mary Kilomot			
	If Digit		Mut.	
			Control of the Contro	
		P. A. Sandaria		And the second
			Taller and the second second	
			<u> </u>	
			Page 365	

Date: 2/22/	83	
Purpose: HA	ZARDOUS WASTE COORDINATOR TRAINING	
Instructors:	Roger Martin	
À	Dan MacDonald	

	Name	Clock Number	Department
<b>S</b>	Nintoliania	428	7.a-
V		55563	Rose Trest.
J	Zmhan	37348	PC Fab
V	An Bent	25692	7-8
	ERMil	16635	Re. Lup
) V	DFERN	13530	7-Bird
V	ana Whitmen	19116	FAC. MAINT.
V	Darline Johnson	21233	P.C. asy
2-12T	Denne E Pelais	2572/	P.C. FAB
X	7/1- 4574 X 100 1	13208	P.C. Yale
Or 12 B	Dan Lundels	19661	MFal
O. A.	Bruce Bahls	12905	Refurb
	Tomburan	51490	Factor Sugar
	Daniel Patrick	20599	PCASSA
. [	RON MARTIN	9876	P.C.ASSY SUB ASSY
	I ledy Cotner	59276	MAINT
v	JA Relich	35776	1350
-	MDRewell	19740	1350
ا کسر	Roses Ramas	62737	1232
	Mile William	ausz	1137
	The state of the s	•	

<u>s</u> : -,	HAZARDOUS WASTE CO	· ·	
Instruct	ors: Roger Martin	nit papaning	
	Dan MacDonald	ng undanolds poet della granda della supplication d	
Special control of the special control of the			
	Name (	Clock Number	Department
XIMX	Wokeste	19070	420
1 Show	bet I terreke	52889	Fab
V DE	TKACKA	61608	MF
V Day	e West	19640	Failure Andysis
JOEN S	SRIGORALANDI	864001	И
1/ Fan	oul 505	50065	Insp-Engn
`/	De Buel	97886	T-R-
V Se	LAN BANG	39045	P.C.FAB
	in Jennings	55681	MUS-5/D
Bull	1 Potes	62487	Environmental
1 Da	m Renn	1297	maint.
1 K	Dieden	4431	Store
Par	Round	63278	Oc. Health Prog
V.			

Date:	2/23/83						
Purpose	HAZARDOUS WASTE COORDINATOR TRAINING						
-	•						
Ins truc	tors: Roger Martin						
	Dan MacDonald						

Name	Clock Number	Department
Bud QUAM	10834	MFL. ENG
D.M. Manikowski	13493	PCLAB
NeIL Dohm	39946	P.C. Lab
John & Barnet	1338	Transpertation
La Hondreal	53535	E MAINT
James Gerson	51496	Facilities Comm.
Vames Carow	5/305	HYBRID
Randytern	63389	F. MAINT.
V Book Vot	7741	7. MAINT
676.20	6(277	F. MAINT
VIII Religion	3755 3	F MAINT
The May and the	62878	MOS
XV prog Sheish	64210	MCS
W-Cliften	2/5/5	leating
X Vicki Thompson	64325	mos
- Aller Andrews Control of the Contr		
		·

	COORDINATOR TRAINING	
nstructors: Roger Martin		
Dan MacDonald		
Name	Clock Number	Department
Om Henroll	14453	Troppie (2360
Sond Hale I	52549	Troffic (2360)
Robert & Radlett	. 15197	PC Acev
Daniel a Dema	1 39409	PC Fab
r		
\$ p.		
•		
	·	
	·	
and the state of t		

# HAZARDOUS MATERIAL WASTE COORDINATORS TRAINING

- I. INTRODUCTION ENVIRONMENTAL MANAGEMENT (ROGER)
- II. COORDINATORS DUTIES (ROGER)
  - A. LABELING (VIEW GRAPH)
  - B. REGULATIONS
  - C. ENFORCEMENT
- III. INFORMATION SYSTEMS MAPPER (DAN)
  - A. INFORMATION AVAILABLE
    - 1. HAZARDOUS MATERIAL INFORMATION
      - A. RID TYPE B (VIEW GRAPH)

SHIPPING INFORMATION

- B. RID TYPE I (VIEW GRAPH)
  SAFETY INFORMATION
- 2. HAZARDOUS MATERIAL DOCK LOG
  SOLVENT SEPARATION (VIEW GRAPH)
- 3. HAZARDOUS MATERIAL INVENTORY (VIEW GRAPH)
- B. ACCESS JHMDF, 100, DATA
  (VIEW GRAPH)

- IV. NEW CHEMICAL ORDERING PROCEDURE (DAN)
  - A. ORDER FORM (VIEW GRAPH)
  - B. CHEMICAL IN SYSTEM REQUISITION TO INVENTORY SUPPLY
- V. INTER-PLANT TRUCK (DAN)
  HAZARDOUS MATERIALS ONLY
- VI. SPILL PROCEDURE (DAN) (VIEW GRAPH)
- VII. QUESTIONS (DAN, ROGER)

APPENDIX H-7

GUARD TRAINING



ECP	37016D		REV	-
BACE	1	ΩE	3	

ENVIRONMENTAL	CONTROL	PROCEDURE
---------------	---------	-----------

DETAIL DESCRIPTION GUARD TRAINING

Den moch Dan E. MacDonald

DATE 1/19/83

REF

INTRODUCTION - ENVIRONMENTAL MANAGEMENT, I.

#### Α. PERSONEL:

Roger Martin - Manager at Univac Park

#### UNIVAC PARK:

Mark Wilson - 1st Technician Greg Grinols - 2nd Technician (covers Shepard Road) Mike Gold - 3rd Technician Reid Oines - 1st Technician

#### SHEPARD ROAD:

Bill Polta - 1st Technician Mike Medina - 3rd Technician Dan Mac Donald - 1st Engineer

(HAZARDOUS TRUCK INTERPLANT AND MIDWAY) Roger Ranzau - 1st Technician

#### PURPOSE AND FUNCTION

- Pollution Control Regulations Water, Air and Land Discharges
- Operate Waste Water Treatment Systems
- Disposal of Hazardous Waste
- Spill emergencies

#### COVERAGE - ROUTINE ITEMS II.

- DEFINITION ROUTINE ITEMS Any alarm for Waste Treatment Systems and Tanks or any occurance in Environmental Management area. (Prints of building)
- CALL ORDER WEEK DAYS
  - Univac Park x4625 Call Labs
    - Shepard Road x4656

- Shepard Road x4714 1st Engineer

- Univac Park x4656 1st Manager

Page Technician - All have pagers.

UD1-3938



ECP	37016D	REV
PAGE_	2	OF3

ENVIRONMENTAL	CONTRO	L PR	OCEDUR		A THEOLOGY
DETAIL DESCRIPTION GUARD TRAINING	14 mm (422207)			REF	
ENGINEER  Dan E. MacDonald	DAT 1/	E 19/83	APPROVAL	т	DATE

#### CALL ORDER - WEEKENDS

- Emergency call list board
  - a. Call technician on duty
  - b. Page technician on duty
  - Start calling down list of Environmental Management personnel
- 2. Shepard Road guards will have to call Univac Park to find out who is on duty.
- 3. A technician does visit Univac Park and Shepard Road once per day on weekends.

#### III. HAZARDOUS MATERIAL EMERGENCY

- DEFINITION FROM ECP 37009 A spill or occurance involving any hazardous material outside of plants, this includes all bulk deliveries and fuel oil. Inside the plant any occurance involving a material with a hazard code rating of 2 or above should be treated as an emergency.
- B. HAZARD CODE DIAMOND Explain: (Diamond Label)
- C. CALL HAZARDOUS MATERIAL EMERGENCY COORDINATOR

  - Any reported spill form call emergency number x3000 (get: name of person, location, nature of spill, material)
  - List of emergency coordinators
- D. EXPLAIN EMERGENCY PROCEDURE ECP 37009
  - 1. Keep people clear
  - Get help
  - 3. Communication
  - 4. Procedure at each Guard Station
- HIGH POTENTIAL AREAS FOR SPILL (Plant Layouts) Univac Park Shepard Road Midway
- SPILL OFF OF UNIVAC PROPERTY Receive call on x4812 Univac Park Call Hazardous Material Emergency Coordinator immediately



ECP	37016D	REV
PAGE.	3	OF3

ENVIRONMENTAL	CONTROL	PROCEDUR		
DETAIL DESCRIPTION GUARD TRAINING		adjys a lamosoojiki	REF	
ENGINEER Dan E. MacDonald	DATE 1/19/	APPROVAL		DATE

- IV. CONCLUSION STRESS WHERE GUARDS CAN HELP
  - A. REPORT UNUSUAL OCCURANCES
    - 1. Round
    - 2. Reports to Guard Stations
    - 3. If in doubt Call
  - B. IF SPILL OCCURS
    - 1. Communications
    - 2. Help keep people clear of area
    - 3. Back up support

APPENDIX H-8
HAZARDOUS MATERIAL CONTROL PROGRAM

	•	11				
Accordance from Assessment						e de la companya della companya della companya de la companya della
	2 T		CONTRACTOR OF THE PARTY OF THE	8	466	A SERVICE AND A

THAINING TITLE MATERIAL CONTROL PROGRAM

## TRAINING SYNOPSIS STATEMENT

PLANT 1

INSTRUCT EVERYONE IN PROCUREMENT CO HAZARDOUS MATERIAL REQUISITION PROC	CEDURE.
OB CLASSIFICATION OF TRAINEES	TRAINING FREQUENCY
METHOD USED:	
□ WORK EXPERIENCE □ 01	THER TRAINING (i.e., VENDOR SCHOOL)
CK&Lass/group learning	
On the Job Training O	other (specify)
PROCESS DESCRIPTION:	
PROFICIENCY MEASUREMENT TECHNIQUES:	
☐ ORAL INTERVIEW. ☐ PRODUCT EV.	ALUATION SIMULATION EXERCISE
[] PERFORMANCE TEST	TEST XX SITUATIONAL OBSERVAT

UO1-3907

REMARKS

PAGE 377

SPERRY LINIVAC

	14 (2 SS) 14 (1	OPERATIONS TRA	INING RECORD		
INSTRUCTOR'S NAME	11 0	1KO Jacobs	ester Ens Tra	A DATE	2-29-82
DESCRIPTION OF TRAINING			J.		
HAZALDOUS	MATEL-141	^	*		Action and Community Commu
PARTICIPANTS NAME	EMPLOYEE	ORSANIZATION:	PARTICIPANTS NAME	EMPLOYEE NUMBER	ORGANIZATION:
PARTICIPARIS RAME	NUMBER				
M.C. FALLELL	28682	Procurement	Market Ma		· ·
Tazzon:	63449	16			
L leave	40967	l c			· · · · · · · · · · · · · · · · · · ·
El Peterson	20461	11		*	
A.R. Lancolle	22580	U.			
trudgohison	15423	*			Name of the state
BRMEL	22107	le.			
Tom Goerges	37570	,,		-	
Leo Stark	28694	1/			•
Mary Warnest		11		,	
11/1 -	62164	/ 1			
Chillo Mosta	,	/t			
In anyon	21142	. 10			
B Buney	33312	11		<del></del>	
John Hunter	७३५७९			,	
Tom Reents	1				
R.W. Corego	5087	1			
ne your	22128	11			
Jen Sign	55490				
a Hortuga	2838	28 "			
1 Double	25573	. /1			
Deva Pens	en 6274	3 . 16			
R Swenson	38489				Donney-Agentum Market M
RACE	6392				
Mala	14942				
	1 /40/	11		PAGE	378

SPERRY LINIVAC

A STATE OF THE STA	_	OPERATIONS TRA	INING RECORD	DATE	
INSTRUCTOR'S NAME	mar tin	Posice E	avold	1/-	3-82
	RAINING 3 3 3 - de US	Chemical	Control 1	? my rin	
MOURS: OF INSTRU	THONGS		The state of the s	V	
PARTICIPANTS	NAME EMPLOYEE NUMBER	ORGANIZATION•	PARTICIPANTS NAME	EMPLOYEE	ORGANIZATION
Ron Berg	X 63278	Occ. Health Arg.			·
Tend Se	elapha 64421	11 1/ //			while the second second second second second second second second second second second second second second se
Ruk	6773)	ENW MENT			
	58563	RYI.			
Bulmi	lev 20167	Sub Assem. P.E.			
trud: Int	NS PN 15423	PLACH ASING			
Section 1	<u>wx</u> 38870	P.C. FAZ ENG.			
/2c3	ulut 9470	AMT			9
- Song	Jel 19661	1111-			
1000	12905	REFUVE			
V Alle CANI	(CD 15200	ME FLI			b.
3 B 1 M	16635	Re Ving	, in the second		
7.73	275/6	Inv. Seul.			
E. L	505 500 65				
//	Kent 12745				
( PILL)	Z780S	A 2			
20 J	18 59281	FACT SUPP.			
12 L. M	18672	7-BIL			
Rati	16/22	Deposition		to the same of the	The second secon
Calent	21708				
GWA	NEEN 3994	A PC FAB			
DE MA	16553	PC Fab		, .	4
= W.G.	en 646	KEC.			

SPERRY LINIVAC

INSTRUCTOS'S NAME	satin	Roscoe	EVAVOID	DATE.	3-8L
DESCRIPTION OF TRAINING		homical Co		,	
HOURS OF INSTRUCTION		4	V		•
PARTICIPANTS NAME	EMPLOYEE NUMBER	ORSANIZATION	PARTICIPANTS NAME	EMPLOYEE NUMBER	ORGANIZATION
D. E. MacDonald	55686	Ear. Agent. 1232			
REGAN MILLETE	37/69	P.C.FAB 2810		·	and the supplemental th
C.O. Ball	4935	Store	- California de la Cali		
Colol Sol	18461	Fichely Sunset			
CHET KALKA	61608	MF			Fig. 1. The second seco
Greet East	18124	Sel 1884			
Mike Bukkil	63649		,		
Kalny Kiel	<b>S</b> 9119	PCFab PE			
Keun Holland	63306	PLA			
the 2 Digo	22492	FAO			
Elmi From	13632	F#			
			and the second second second second second	n de la companya de l	
The second of th					
THE COLUMN TWO IS NOT THE OWNER OF THE COLUMN TWO IS NOT THE COLUM					
			<b>.</b> .		

		2.6			
and the second second			1 1 1	<b>11</b>	
	=== 9			M 1	

## TRAINING SYNOPSIS STATEMENT

HAZARDOUS MATERIAL CONTROL PROG			
RAINING GOAL: INSTRUCT EVERYONE CONCERNED ABO REQUISITION PROCEDURE.	OUT THE REVISE	) HAZARDOUS MATERIA	
	<b>.</b>		
	-	•	
OB CLASSIFICATION OF TRAINEES	•	TRAINING FREQUENCY	
METHOD USED:	and the second second second second second second second second second second second second second second second	in a second control of the second control of	
WORK EXPERIENCE	OTHER TRAINING	(i.e., VENDOR SCHOOL)	
XX CLASSIGROUP LEARNING	esterninggggmannings	ng dipantanan at at at a sama ng ng ng ng ng ng ng ng ng ng ng ng ng	Approximately and the second s
ON THE JOS TRAINING	OTHER (SPECIFY)		•
☐ INDEPENDENT STUDY	411114111111111111111111111111111111111		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
PROCESS DESCRIPTION:			
			• .
		· · · · · · · · · · · · · · · · · · ·	
PROFICIENCY MEASUREMENT TECHNIQUES:	WISSEA REPORTED STREET AND ADDRESS OF THE ST	-	,
G ORAL INTERVIEW	DUCT EVALUATION	SIMULATION E	XERCISE
D PERFORMANCE TEST D WAS	TTEN TEST	EXSTUATIONAL (	)BSERVATIO
INSTRUCTOR'S NAME AND QUALIFICATIONS			
ROGER J. MARTIN, ENVIRONMENTAL	MANAGEMENT		
DOVED T MARITIN, PINVERCINITALE	T TATAL TO THE SHAPE OF THE SAME OF THE SA	and the second s	

SPERRY & UNIVAC

	1	OPERATIONS TRA	HIMING KECOKD		
INSTRUCTOR'S NAME  EKEVHVOLD	1/R.	J MARTIN			9-52
DESCRIPTION OF TRAINING	7	ATERIAL CON	ROL PROGRAM		
HOURS OF INSTRUCTION	<u> </u>				
PARTICIPANTS NAME	ENPLOYEE	ORGANIZATION	PARTICIPANTS HAME	EMPLOYEE NUMBER	ORGANIZATION
MARY MICHAUD	63/3/	PC LAB			
Das Petersu	37382	PC LaB			
Bill HELSON	19515	PROTO TYPE			
MARK WILSON	55968	ENU MEMT		· .	
REID DINES	64128	ENV MEMT			
Lynn Kterow	<u> 23865</u>	Env. Mant.			
Dana Rodges	1	SO Mot Control	- The state of the		
2. J. 9 EP27					
Welly Herman	g	Stores			
Jamis Hardens	19116	FAC. MAINT.			
Sund Winder	37553	<b>,</b>	A STATE OF THE STA		
Sol Vint	7741	11			
Han Waver	3.3538	Robtins			
and Short	63184			·	
El. Helluan	16827	Photoinach			
Joh T. Ryan	57157				
Sould B Haribar	4 13 493	1.			
the bottom	22362				
WW Reicht	18544	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
Marge Koglind	19935	Proto typ	A respective to the second sec		
	<u>,</u>				
				PAGE	382

SPERRY & UNIVAC

F K EVAVOL		OPERATIONS TR		DATE //	-9-82
ESCRIPTION OF TRAINING  HAZARD  OURS OF INSTRUCTION	TIN Dus M	ATERIAL COR	HROL PROGRA	ı	
PARTICIPANTS NAME	EMPLOYEE HUMBER	CREANIZATION	PARTICIPANTS NAME	EMPLOYEE HUMBER	NOTTAZINASNO
AND SPORKE	63389	1350			
NORM REPP	1297	1350			
LICHELE COLON	63368	7372	·		
_	<del>61353</del>				
		2860/2865			
an year	K. J. Hilliam base beganning				
- ·				· .	
					And the second s
					en en en en en en en en en en en en en e
*					
					dan dan dan dan dan dan dan dan dan dan
economic Cities of the control of th					
Production of the Control of the Con					
			·		

Λ.

DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION OF TRAINING DESCRIPTION DESCRI	INSTRUCTOR'S NAME		4 50 8	NING RECORD	DATE //- /	0-82
PARTICIPANTS NAME CONFICE ORGANIZATION PARTICIPANTS NAME RUMBER ORGANIZATION  PARTICIPANTS NAME CONFICE ORGANIZATION PARTICIPANTS NAME RUMBER ORGANIZATION  PARTICIPANTS NAME CONFICE ORGANIZATION  PARTICIPANTS NAME RUMBER  PARTICIPANTS NAME RUMBER  ORGANIZATION  PARTICIPANTS NAME RUMBER  ORGANIZATION  NUMBER  NUMBER  ORGANIZATION  NUMBER  NUMBER  ORGANIZATION  NUMBER  NU	DESCRIPTION OF TRAINING	<u>in End a</u>	y es a	, Que		
PARTICIPANTS NAME  PUBLISHER  L. B. Wajish 38043  With Vision 428 time Carry  R. L. Stant 7137 Pare H.  Bran 67517 Too Sept.  D. Rolling 5053 Reper  With 5053 Reper  D. Jamon 6180 2123  L. Land 25492 T-BIRD  L. Land 3581 Frame  L. Kreek 22128  L. Kreek 22128  L. Kreek 22128  L. Kreek 21212 Tobboom  L. Kreek 22128  L. Kreek 21228  L.	HOURS OF ASTRUCTION					
L.B. (Lajik 38043 ""  Nich Kiraia 428 Finel Corry  Rich Alent 2137 Per H.  Bran 4761 Expec.  Sold 1984 Expec.  Ather 50157 Zon Sept.  Ather 50157 Zon Sept.  Ather 50153 Repel  Ather 50153 Repel  Ather 50153 Repel  Ather 50153 Repel  Ather 5015 Ton Sept.  Ather 5015 Proto  Ather 501	PARTICIPANTS NAME		ORGANIZATION	PARTICIPANTS NAME	EMPLOYEE RJBBNJN	ORGANIZATION
C. B. (haid 38043  Nichtlieria 428 Einel Cray  Por Milland 200.79 Prototope  R. J. Shent 2137 Pres H.  Bran 6761 Expect.  Dela 1885 Exped  J. M. G. 1584 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan Ventus 50153 Exped  Quitan 1860 2123  L. Con C 25692 T-BIRD  A Kaland 3588 Francis  D. J. Gurall 14453 Alighing  Of Rasse 11212 T-BIRD  Val Harborn 8174 Rota Contain  Pres. Milan 39983 Mal. Nymit.			When Hat	ntercompositumes sono summente proprieta de la constanta de la constanta de la constanta de la constanta de la		
Michilland 20179 Prototype  R. A. Sunt 2137 Pare H.  Bran Gtol Exped  Small 1844 Exped  Outher Tend 50153 Exped  P. Hamon 6180 2123  L. Land 25692 T-BIRD  A. Kind 3588 Promod  F. Kycek 22122  L. Kycek 22122  L. Kasac 11212 T-BIRD  V. Ball Harbon 8174 Rute Control  Pid. Milon 3983 Met. Nymt.	AT CONTRACT	1	a 11			0
Rom Molland 20179 Prototype  R. M. Stent 7137 Pare H.  Bran Gettl Expect  Solf 1885 Expect  Del 1984 Expect  Quilm Tenta 50153 Expect  Del 25292 T-BIRD  March 5025 Met 7th  Del 11- 24755 Proto  Reference 1588 Francis  F. Kycek 22128  I Kashe 11453 Shipping  M Kashe 11-21 T-BIRD  Vial Marbon 8174 Ruta Contro  Pid. Milon 3988 Met. Nymt.	n - 1 1/2	1	Final Corner			
R. J. Stant 2137 Pare H.  P. Bran (2761 Expect)  Sold 1984 Expect  D. L. J. 1984 Expect  Quitmu Ventur 50153 Rxpect  D. Zhamon 6180 2123  L. Clark 508 M. + Fik  D. L. 1985 Proto  P. Kelent 3588 Promon  F. Kycek 12126  D. J. J. 14453 Shipping  Of Rease 11212 T. BIRD  Vale Howlow 8174 Pata Contro  Pad. Milong 3982 Med. Nymt.	P Macon O		20 state see			
Bran GTE Expect  Self 1885 Exped  IMS - 6/5/7 Ino. Serv.  D Rock 1984 Exped  Quithus Tenter 50/53 Exped  P. Zhanon 6180 2123  Lend 25492 T-BIRD  Lend 5028 Mit File  DI This 24255 Proto  R Kelant 3588 Procument  F. Kycek 22128  O Mywall 14453 Shipping  O Rasse 11212 T-BIRD  I let Harborn 8174 Rute contri  Ind. Milang 39982 Med. Mynt.	RY Heart	1/-	Pare H.			
Just 6/517 Ino. Serv.  District 1984 Expel  Quitum Venden 50153 Expel  District 25/92 T-BIRD  Stand 3588 Promode  F. Kycek 22/28  I fund 14459 Shiping  I factor 114459 Shiping  I harbon 8174 Pate Contil  Dat Markon 8174 Pate Contil  District 35982 Med. Ngmt.	Regan				Angeliji Maria Maria	
Description 8174 Pute Contil  Jack 1984 Exect  Outher Feel 50153 Expel  Dilling 5035 Expel  Dilling 5035 Mit File  Dilling 24755 Proto  Excel 22128  I Kycek 22128  I Reserve 11212 T-61KeV  Jack Harbon 8174 Pute Contil  Dilling 38982 Met. Nemt.	KCI 0	(40KK)	کری			
District Sois Reper District Sois Reper District Sois Reper District Sois Reper District Sois District Sois District Sois District Sois Promoder District Sois Promoder District Sois Promoder District Sois Shipping of Rease 11212 Tolked Under Tolked Under Tolked Sois Promoder District Distri	Turk	6/5/7	Ino. Serv.			
Dilmon 6180 2123  Land 25292 T-BIRD  Land 508 Mit Flk  Dilling 24755 Proto  K Kahan 3588 France  D Hewell 14453 Shipping  It Reader 11212 T-BIRD  Val Harbon 8174 Rate Contro  Lind. Milon 3982 Mar. Mynt.	NO X	1584	Expel			
Delimen 6180 2123  Lend 25692 T-BIRD  Minch 5008 Mit The  Diffic 14755 Proto  Rechard 3588 Framed  F. Kycek 22128  Of Junel 14453 Shipping  A Racke 11212 T-BIRD  Val Harbon 8174 Rute Contro  Del Milan 3988 Met. Ment.	a.H. F. A.				i .	
Lond 25692 T-BIRD  March 5008 Mit Flk  DITTO 24755 Proto  Khand 3588 Promise  F. Kycek 22128  O Mywall 14459 Shipping  M Rasse 11212 T-BIRD  Ilal Harbon 8174 Puta Contil  Dod. Milem 39982 Mar. Mynt.	021					- April 1
Della 508 Mit Fle  Della 1455 Proto  E Kahad 3588 Francis  F. Kycek 22128  O Hewall 14459 Shipping  Of Racke 11212 T-BIRD  Vlat Harbon 8174 Rute control  Did. Milon 39987 Med. Mynt.	Att. L		T-BIRD			
DE Vistoria 3588 Promode F. Kycek 22128 1.  D. M. Gundl 14459 Shipping 15 Racke 11212 T-BIKEN 1212 Mund		mit File				
F. Kycek 22128 11 Delgwall 14453 Shipping We Race 11212 T-BIRD Val Harbon 8174 Reta Contil Did. Milam 39982 Med. Ment.	20614-		PLOTO	A CONTRACTOR OF THE PARTY OF TH		·
De James 14453 Shipping It Rache 11212 T-BIRD  Val Harbon 8174 Data Contil  J. J. Milon 3983 Med. Ment.	PKI	1 3581	Premi			3
Defende 14453 Shipping It Rashe 11212 T-Bled I dat Harbon 8174 Data Contil Did. Milom 39982 Med. Ment.	F Kreek	12126	÷ , p:			
Let Harbon 8174 Deta Contil L.J. Milam 39982 Met. Ment.	10 2/		Shoping			
J.J. Milon 39982 Med. Mynt.	is Race	1/2/2	T-BIRDT	- Anna Anna Anna Anna Anna Anna Anna Ann		
DC Honel 19740 Tool Mant.  MD Revel 19740 Tool Mant  LC DAVIS 62958 Safety	, Sal Harto	m 8174	Duta contil			
OCHONNIL 63060 MFL Mant MD Revel 19740 Cont Mast IC DAVIS 62958 Safety	J. J. milen	39982	Merc. Mynt.			
10 Revel 19740 Cont Mont	TO CHONELL	63060	m+L mant			
JC DAVIS 102958 Safety	AMD Aniel	119740	Good Man I		·	
T	JC DAVIS	62958	Safety			

SPERRY & LINIVAC

-unitation.	- NO.	OPERATIONS IN	AINING RECORD	DATE	
TRUCTOR'S NAME	uL; E	Env. ngh. &	Tree Org	aus 1	11-10-82
SCRIPTION OF TRAINING	N	Canada Can	In Our		
URS OF INSTRUCTION			J	Assessed to the second	(lent)
	21.10a A415		PARTICIPANTS NAME	EMPLOYEE	ORGANIZATION
PARTICIPANTS NAME	employee Number	Organization-	PARITURE	RJBBUJA	
1. Milan	2,95	punkasing			
	!	FINAL ASSY	V		
	1	T-BIRD			
	1 / 1	T			
SAI HOENE	1	PROTU. MI-G-			
GAPY CAIN		MATE MOT			
Vin litte	62487	Env. Mont.			
JOHN LEHTO	13363	POWDER COAT	·		The Community of the International Control of
		NHL MGMT			
· · · · · · · · · · · · · · · · · · ·	1	1			
	1	Insp. Eng.			
J. A. A.	63776	) <i>b</i> .			
HARRY Sibley	1 16754	MAT-Mginn	7	-	
,					
				•	
*					
	-				
Approximate the state of the st			· · ·		
and the second s		And the state of t			
				-	
					· •
I	ı		· <u> </u>		7



#### DISTRIBUTION LIST

S. R. Kulyas

B. M. Bahr

D. A. Jersak

D. L. Thorkildson

D. Parham

H. Friant

B. Perseke Jick Man E. L. Arne G. C. Nilson D. O. Brown

D. O. Brown

R. R. Johnson



#### INTERCOMMUNICATION

TO: Distribution List

FROM (NAME & EXT): R. J. Martin - X4654

St. Paul - 1 Sept 83 LOCATION & DATE:

DEPARTMENT & M.S.: Env. Mgmt. - Uln14

cc: E. T. Michaud

SUBJECT: Hazardous Chemical Use

Environmental regulations require us to maintain very close control on the disposal of chemicals used in your department.

It is timely to meet with you to explain the latest regulations and how they affect Sperry.

We have scheduled a meeting in room L18A at Shepard Road at 2:30 on September 7.

The liability of improperly handling waste chemicals could impact everyone that is in a position of responsibility for specifying, ordering or using hazardous materials. This could affect each of you.

Therefore, it is extremely important for you to attend the meeting. Please mark your calendar.

It is expected that the supervisors and managers listed above will invite anyone else that is not included on the list but should be in attendance.

Martin

Man/ager

En vironmental Management

/Imk





#### INTERCOMMUNICATION

TO: S. R. Kulyas D. L. Lingofeldt CVE. Kalka J.M. Klempka

cc: E. T. Michaud

FROM (NAME & EXT): R. J. Martin - X4654

St. Paul - 1 Sept. 83 LOCATION & DATE:

DEPARTMENT & M.S.: Env. Mgmt. - Uln14

SUBJECT: Hazardous Chemical Use

Environmental regulations require us to maintain very close control on the disposal of chemicals used in your department.

It is timely to meet with you to explain the latest regulations and how they affect Sperry.

We have scheduled a meeting in room LISA at Shepard Road at 1:30 on September 9.

The liability of improperly handling waste chemicals could impact everyone that is in a position of responsibility for specifying, ordering or using hazardous materials. This could affect each of you.

Therefore, it is extremely important for you to attend the meeting. Please mark your calendar.

It is expected that the supervisors and managers listed above will invite anyone else that is not included on the list but should be in attendance.

Martin

Manager

Environmental Management

/lmk

φ,	HTEND PC F	AB	<	2 1d	PS	evi:				ND					9	17/	73		
	ಕು	درو	<u>ي، ري</u>	Ż	<b>4</b> 5				2 -					3 =				: 4 <b>=</b>	
				= .			(	7 <sub>Ce</sub>	-/	. /									
	NAME	Ī-	2≤	. / 7		LAI	PZ.	ATI	VG.	LA	M	Sr	411	=7-		Z		ENS	10,
	(PLEASE PRINT)				<b></b>			970, 6										,	
		ρ	50	V.	MA	21000	1						1		П		4	F	
2	DENNIS BROWN	7	200		EN	Nica	4	leas G	455	27	658		7				-	46	Z
<u> </u>	Betty Perseke	1	00	6		Jer.	11 1	How			٠ ٢			4			4	170	<i>' 3</i>
	DENNIE E. RICHARDS	7	A	<b>,</b>	20	7.		RA	14	20	(m) 4			3			2	<b>S</b> Z	2
5	Richard MANSAGOT	);	<b>S</b> (	1	راباد		ρ	la r	1	J	/		-	3			4	99	1
6	Helon Freant	ز	00		5/2		2	أط		1.42							4	132	3
7	Germend & Trileon	A	00					F- 6	2	5 1			$\coprod$				1	153	3/
	Daniel a Jersek				9	<u> </u>								$\perp \mid$			Ш	$\perp \downarrow$	Ш
9	Leuran Bane	L	A	4			2	1	<i>a</i>	ZZ.	YE A							4-4	尘
0	DON THORKILDSON				15			7	70	90 /s/	3.4	7		4			1	14	2
11				Ш					ļ				Ш	$\perp \mid$				$\perp \downarrow$	
12									1					$\perp \downarrow$				$\square$	┵
13			: : ;	Ц			1						$\perp \downarrow$	$\downarrow \downarrow$				$\square$	$\perp \downarrow$
14			-	Ш	11								_	4		_	Ш		Ш
\$			6			·,									44	_			
18						1	<u> </u>			Ш			$\perp$			_		H	+
17		1		Ц			-		1							_			_
18:										-  -						_	Ш	$\vdash$	
19 .		1				100	1	Ш											_
20		-				-	_			1				-				H	_
21				Ų i		1 4 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		· [6] [6]	H							╢-	<b></b> -		+
22			$\bot$	-			1		$oxed{+}$	╫	-		-	-		_#_	$\vdash$	H	_
23				_	$\dashv$		-		$\vdash$	$\dashv$			-	H		+	╁	H	+
24	Barrier - 그는 그들은 하는 그 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등 등	-				+	-	+		+	-		+				$\vdash$	H	<u> </u>
25		-				-	#	╁┼	H								$\vdash$	H	_
26		╫		-		╅┈	+	-	$\vdash$	H	-			$\vdash$		-	++	H	+
27	The state of the s	$\parallel$		-		+-	╫	╁┼	╁	╁┼			$\vdash$	H		-	+		十
28		-   -	+	+		_	-	++	H				$\vdash$			-	$\forall$	H	$\vdash$
29			$\forall$				╫		H	H			$\vdash$				$\dagger \dagger$		$\vdash$
30									H	+			$\Vdash$				T	$\prod$	$\sqcap$
31			$\dagger$						$\dagger \dagger$	+	- <del></del>	$\vdash$		$\vdash$			$\dagger \dagger$	H	$\sqcap$
32		╫	$\dagger \dagger$				╫	1.	$\dag$				П			1		$\prod$	T
33							-	1.	+		1	i.					$\prod$		П
35			$\dagger$	1		-		11	$\prod$	11		1	$\sqcap$	T			$\prod$	$\prod$	
36			T	7			╽.			77	1	1	П						
37					$\sqcap$			11	$\prod$	11	1								
38		1	$\top$		$\sqcap$		1	T	11	$\sqcap$			П	$\top$			II		П

.....

9/7/83

- 1. Completely fill out orange "Waste Chemical" label, soon to be yellow "Hazardous Waste" label.
- 2. Accurate list of "Coordinators" and engineers.
- 3. Inform me when changes occur.
- 4. Chemical ordering procedure.
- Review what is available before ordering a new chemical.
- 6. Use products already in use, heptane, for chloroethane etc. "Employee and community Right To Know legislative 3000 PN's.
- 7. Waste, use ID from master list.
- 8. Specific containers for each waste.
- 9. Different departments using similar products.
  - we will get you together
  - 12 types of freons
  - 5 antifoam
  - 5 rust inhibitors
  - 8 types of M.C. (including cold degreaser).
- 10. Be selective about accepting samples do not take it unless you have a need.
- 11. Scrap samples soon after it is used.
- 12. Cost of disposal is \$80/drum. Could be credit.
- 13. Superfund up to 32c/gallon if not recycled.
- 14. Reuse of solvents and oils, recycling possible at less cost.
- 15. Half full drums not being filled.
- 16. Use safety cans for waste not original containers rinse original containers 3 times before discarding.
- 17. Current liabilities.
- 18. Water usage.

HTTENDANCE METAL FAB PRODUCTION SUPERVISORS YENGINGERS SHIFT ENTENSION NAME (PLEASE PRINT POSITION R.F. TERHAGR 4.55 Links 1994 **一种人类的人类的人类的人类的** 20. The state of the s THE STATE OF THE PROPERTY OF THE PARTY OF TH 

#### DISTRIBUTION LIST

M. C. King
G. O. Eide Peach (Jacobaya)
G. M. Jensen
D. J. Johnson
R. K. Martin
W. R. Patrick
RM L. Radloff
B. L. Alsleben
L. M. Merck
Rox Susatha

data Napar



### INTERCOMMUNICATION

TO: Distribution List

FROM (NAME & EXT): R. J. Martin - X4654

LOCATION & DATE: St. Paul - 1 Sept. 83

DEPARTMENT & M.S.: Env. Mgmt. - Uln14

cc: E. T. Michaud

SUBJECT: Hazardous Chemical Use

Environmental regulations require us to maintain very close control on the disposal of chemicals used in your department.

It is timely to meet with you to explain the latest regulations and how they affect Sperry.

We have scheduled a meeting in room LISA at Shepard Road at 2:30 on September 8.

The liability of improperly handling waste chemicals could impact everyone that is in a position of responsibility for specifying, ordering or using hazardous materials. This could affect each of you.

Therefore; it is extremely important for you to attend the meeting. Please mark your calendar.

It is expected that the supervisors and managers listed above will invite anyone else that is not included on the list but should be in attendance.

R. J. Martin

Manager

Environmental Management

/Imk

-		<u>.</u>	ATTEND	A 113		R		OP	b			,											
.:		<u></u>	SUR PASS	msi Msi	s=	<u> </u>	<u></u>	عري	-015	oæ	<u>\$</u>								-				
_			Sub Asser AND Peo	Due	70	_بر	Ē	SGIA	JEEP	25	2 =					3		<u> </u>	181	<u>73</u>	4		
`						' =			A	 ₹ <i>€</i> 7	- = A c	wor	12								<del></del>		
- ~			NAME	72,	17	-10	C)		1e					5	<u></u>	F1	-		E	<u>zt</u>	<u>.</u>		
~			(PLEASE PRINT)																		T.A.		
			ROBERT L. KARLSEF	5	ZZZ	0y			EV	112	96	-8	NA		2	_				17		Ш	
ž			WAYNE PATHICK	15		4	\$50°		SE			64		o <sub>r-</sub>	P	1			4	71		2	
$\sim \frac{1}{3}$		1	Darlene Johnson	S	ac	Q H			_	-		101	2		1	4	1		4	4			
- 4			ROW GUENTHER	PRO	0	<u> </u>	G.		32	43	'+4	7\$S	/		$\perp$	4		-	13	7/ -	4		
5			MIKE KING	PRE	20	11	AN	A56	C.	\$	4/2	3 4	55	<b>y</b>		4	$\dashv$	1	14	44	#	Z	
· 6			RON MARTIN	SU	00	e u	15	عو	\$	423	#S	<b>s</b>	(Da	UB1	€ Î	FAE	975		$\vdash$	47	42	P	
7			Gales Eile		1	P	+			#	6				•	-		+	H		7		
( B			BETTY ALSLEBER			8	Н.		$\dashv$	لمتساس	0	H		1					-	4	3	2/	
9			GERALLIME SCRIEN	15	e u	PER	VY.	Sak	+	+	40	Λť	`	///	4	ZG	4	-	-		T	11	
10							$\vdash$		+	╂	$\dashv$	H	-		$\vdash$	+	$\dagger \dagger$	1			$\sqcap$	1	
11						H	╁┼	-		+	+				$\vdash$		$\dagger\dagger$	†		П	$\sqcap$	T	
. 12						3 .	$\dagger \dagger$			-		††		${ m T}$		$\sqcap$	$\dagger \dagger$	1	ŀ	П	$\sqcap$		
13										$\top$	T				Ħ			1				$\coprod$	
14								$\top$			$\sqcap$										$\prod$		
15:						ا جا ا	$\Pi$				П					$\prod$				Ш	Ц		
16 €\ 15	-														Ш				<u> </u>	$\downarrow \downarrow$	$\coprod$	4	
· ).	-			u d Gai- Gai-									Ŀ	<u> </u>					↓_	$\coprod$	4	4	<u> </u>
19					ķ			-					_	_	$\coprod$	1			#_	1	1		
78			TO SEE SEE SEE SEE SEE SEE	5 P			$\perp \downarrow$					4	_	1	$\perp \downarrow$	$\perp$			╬	$\perp$	$\dashv$	++	
21				- 💐							11	1	╄-	-	+	+	-	-	#-	╫	+	+	+
. 22					Ш					-			-	╢-	$\perp$	$\dashv$	+	$\vdash$	+	++	+	$\dashv \vdash$	1
23							2				+	$\frac{1}{1}$	-	╬	+	+	$\vdash$	H	#	++	+	++	+
24	ļ							-	-   -		+	+	-	-	+	╁	$\vdash$		╫	$\dagger \dagger$	$\dagger \dagger$	$\dashv \uparrow$	+
25	i					$\dashv$		-	-	H	+	$\dashv \uparrow$	+-	-	+		H	H	1	+	$\dagger \dagger$		<del></del>
26	1				╁	+	$\perp$	+	╢	╁┼	+	$\dashv t$	$\dagger$	╫	$\dagger \dagger$	$\dagger$		$\vdash$	╫	廿	$\prod$	$\Box$	
27						-	+			$\dagger \dagger$	+	$\dashv \uparrow$	$\dagger$	╫╌	$\dagger \dagger$	十			$\top$	$\top$	+1	Ш	
( ) 21				-   · ·			+			$\dagger \dagger$	+-	+	T	╫	11	$\top$	$\sqcap$	П		11			
25	-	-								$\dagger \dagger$	$\top$		1	1									
	-   -				-					$\dagger \dagger$													
31	-	<u> </u>								П									$\perp$				Ш
O:		1															Ц		_	$\downarrow \downarrow$	$\perp$	-	
3:																		1	1	$\perp$	<del> </del>	-	1
	\$			i. k										$\bot$			$\coprod$	11	$\bot$	$\perp$	1	#	$\vdash$
		i i					$\prod$							_	_	$\sqcup$	$\coprod$	#	_	$\bot$	$\vdash$	#	┼┼-
	7				$\prod$					$\perp$	Ш		Ц.	4	$\bot$	$\sqcup$	$\coprod$	+	$\bot$	_	4	++	$\vdash$
									_	_	-	-	-	#	_	igert	+	+	$-\!$	+	+	++	++-
	19				_	$\coprod$	$\prod$				$\sqcup$	-	-	_#-	4	+	+	+	+	_	++	+	+
	1			II.	- [			11	1	1	ļ  :	11					Ţļ				$oldsymbol{\perp}$	$\bot \!\!\! \bot$	Ц.

.

#### SUB-ASSEMBLY

- 1. Review chemicals purchased vs. chemical disposed.
- 2. Discuss need for using waste labels:
  - Completely filling out
  - Use descriptions from wastes list
  - Certify (do not sign before checking)
- 3. Check list of coordinators and engineers.
- 4. Inform us when changes are made.
- Chemical ordering procedure.
- Review what is available before ordering a new chemical, not a big problem with Sub Assembly.
- 7. Use a product that is a big use item if possible rather than discept chemicals., i.e., check rid 5.
- 8. Specific container for each waste.
- 9. Inform everyone in the department that uses safety cans they must keep waste separate, identify safety cans.
- 10. Reduce the use of chlorinated solvents, eliminate if possible.
- 11. We are reviewing chemicals used by different departments using similar but not the same chemical, i.e:
  - 12 types of freon
  - 5 rust inhibitors
  - 5 antifoam
  - 8 types of M.C. (including cold degreaser)
    See if types can be reduced
    Reduced inventory less stress for storage space
    See sheet dated 5/3/83

- 12. Be selective about accepting samples. Do not take one from a vendor unless there is a real need. Do not take one just to be a nic guy. Scrap as soon as information is obtained.
- 13. Reuse of oil.
- 14. Cost of disposal -
  - \$80.00 for incineration
  - Up to 32c/gallon for state superfund if not recycled.
- 15. Use safety cans for waste.
  - Not original containers
  - Rinse containers three times before disposing solvents
  - Empty completely.
- 16. Current liabilities.
  - Ecolotec
  - Andover
  - Sperry Vickers
  - Bristol
  - · SLC





#### INTERCOMMUNICATION

TO: R. J. Sherlock

C. J. Nicosia

L. E. Swenson

W. R. Miller

FROM (NAME & EXT): R. J. Martin - X4654

LOCATION & DATE St. Paul - 1 Sept. 83

DEPARTMENT & M.S.: Env. Mgmt. - Uln14

SUBJECT: Hazardous Chemical Use

cc: E. T. Michaud

Environmental regulations require us to maintain very close control on the disposal of chemicals used in your department.

It is timely to meet with you to explain the latest regulations and how they affect Sperry.

We have scheduled a meeting in room L18A at Shepard Road at 9:00 on September 9.

The liability of improperly handling waste chemicals could impact everyone that is in a position of responsibility for specifying, ordering or using hazardous materials. This could affect each of you.

Therefore, it is extremely important for you to attend the meeting. Please mark your calendar.

It is expected that the supervisors and managers listed above will invite anyone else that is not included on the list but should be in attendance.

R. J. Martin

Manager

Environmental Management

/lmk

		F, NA		A	35	S <i>E</i>	m E	318			···········													
	,	F,NA Pradue AND	ו סוַ־דּג	ر	S .	12	-21	150	2 <u>2</u> e	<u></u>									9	6/	83	<u> </u>		
		AND	Eυ	<u> </u>	<u> </u>	1	5		-		2			TI .		=	3 =		1			4		
<u> </u>				-				-						$\bot$										<u> </u>
		NAME (RLEASE PRINT)	JAME POSITION															-		Ex	7 <i>E</i>	<u> 215</u>	10)	U_
		(PLEASE PRINT)		4		T .T				7-7	1	<del></del>	T		77		ΤΪ	.						<del>,                                     </del>
1		Bill Miller	1	Ź		17	4				_				-	<u> </u>	7	1						+
2		DICK SHERLOCK		\$	1		9-1	-jv			46	7/	4	╬	+	/r				$\vdash$	26	30		-
3				+	$\vdash$	H					+	++	<u> </u>	$\parallel$	+	+	$\dashv$			$\vdash$	_	+	$\vdash$	-
4				+		$\vdash$	+			$\dashv$	+	+	-	+	+		$\dashv$	+		$\vdash$	++	+	$\vdash$	+
5	i	THE THE PARTY OF T	-	<u> </u>		$\frac{1}{1}$				+	$\dashv$		+		-	$\vdash$	-			<del>                                     </del>		_	Н	+
6				+	$\vdash$	+	$\dashv$				+	+	<u> </u>	$\parallel$	+		+	+		$\vdash$	++	+		+
7				+	+	++	+			+	+	$\dag \uparrow$	+	$\parallel$	+	$\vdash$	$\dagger \dagger$	+			+	T		T
8				+	+	$\dagger \dagger$			$\vdash$		+	$\dagger \dagger$	$\top$	$\parallel$	-	H	$\dagger$	$\dagger$		$\sqcap$	+		$\dag \uparrow$	+
9			i //	+	1.								T		╁		$\top$	-			$\sqcap$	$\sqcap$	$\sqcap$	T
10				1	$\vdash$							$\dagger \dagger$			1		П						П	
11			_	$\dagger$	$\Box$	T					1	1			+						$\Box$			T
13		John State Committee Commi			1	-		:	1		П			-								1		
14			4,	$\top$				: :			П		1										$\prod$	
15				1				-		-   -		$\sqcap$	1										П	
16				-		<i>i</i> 0.																Ш		
_ 17					П			1.4.4									T					Ш		
<b>)</b> .8					П						$\prod$											Ш	$\coprod$	
18			茅			(0)								;							Ц		$\coprod$	<u> </u>
20			 														1						$\downarrow \downarrow$	_
21				1				ļ.: 				$\perp \downarrow$		$\perp$	4		_				$\coprod$	14.	$\downarrow \downarrow$	_
22		Season of the se					L	ļ	_	Ш	$\coprod$		_	-	_	#	1	$\coprod$		<b> </b>		-	$\coprod$	$\bot$
23							-		_		$\prod$		1	-	_	+	$\downarrow$		<u>  ·                                     </u>		$\vdash$	$\coprod$	$\perp$	+
24					$\perp$	1		C.1		<u> </u>	$\coprod$		$\perp$	-   -	_	+	$\perp$	igert		<del> </del>	H	+	$\dashv$	+
25					$\perp \downarrow$	_	$\coprod$				$\sqcup$	$\dashv$	1	-		$\dashv$	+	$\sqcup$					-	
26		7-00-000-00-00-00-00-00-00-00-00-00-00-0		$\dashv$		+	-	ļ			$\dashv$		_	_  -	4	-	_	H	<u> </u>	╂—	$\vdash$	ootnotesize +	-	$\dashv$
27	1			$\downarrow$	-	_	$\coprod$	ļ:	-	igwdapprox	$\dashv$	+	$\perp$		+	1	-	┼┼	-	₩-	╀	ightarrow	+	+
28				$\dashv$	$\dashv$	$\perp$	$\vdash$		╀	$\vdash$	$\mathbb{H}$	$\dashv$	+		$\dashv$	-	+	ightarrow	-	+	$\vdash$	+	$\dashv$	
29			- July 19		+	+	$\vdash$		-	$\perp$	$\perp$			-	-	+	+	+		#-	+	$\dashv \uparrow$	$\dashv$	+
30								-	-	╫	+	•			+	+	+	+		-	H	+	+	
31					+		╫	-	-	╁		-	+	╢	-	+	+	╁		╫╌	+	$\forall$	$\dashv$	$\vdash$
32			11	_	+	H	$\dashv$	-	╢-		+		$\vdash$	╌╢╴		+	$\dashv$	++	+	#-	H	+	-	$\vdash$
<b>∕</b> 33						H		-	$\parallel$	+		-	+		$\dashv$			+	+-	╫	++	$\dagger \dagger$	+	-
34				$\dashv$		${\sf H}$	$\prod$	+-		+	+		$\dashv$	-		+	$\forall$	++	+-	#	++	+	+	H
35				-		H	+		-	+	+	-	$\dag \dagger$	$\dashv$		-	+	$\dagger \dagger$	+	#	1	+	+	$\parallel$
7 - 36		*	-#			H	$\dagger \dagger$	+	#	$\dagger \dagger$	+		H		1	1	$  \uparrow  $	$\dagger \dagger$	+	1	$\prod$	$\dagger \dagger$	+	$\sqcap$
37		,		$\dashv$	+	+	+	+	$\parallel$	$\dagger \dagger$	+		$\dagger \dagger$			+		$\dagger \dagger$		#	$\dagger \dagger$	11	1	
38					+	$  \cdot  $	+	1	-	+	$\top$							$\dagger \dagger$			$\prod$	$\prod$	1	$\prod$
39   40					1	H	$\dagger \dagger$	<del>                                     </del>	1	+	+		$\sqcap$	$-\dagger$		1	$\sqcap$	++	_	1	$\prod$	$\prod$	T	$\prod$



#### INTERCOMMUNICATION

TO: Distribution List

FROM (NAME & EXT): R. J. Martin - X4654

LOCATION & DATE St. Paul - 1 Sept. 83

DEPARTMENT & M.S.: Env. Mgmt. - Uln14

SUBJECT: Hazardous Chemical Use

cc: E. T. Michaud

Environmental regulations require us to maintain very close control on the disposal of chemicals used in your department.

It is timely to meet with you to explain the latest regulations and how they affect Sperry.

We have scheduled a meeting in the Thin Film Dept. Conference Room at Shepard Road at 8:30 on September 14.

The liability of improperly handling waste chemicals could impact everyone that is in a position of responsibility for specifying, ordering or using hazardous materials. This could affect each of you.

Therefore, it is extremely important for you to attend the meeting. Please mark your calendar.

It is expected that the supervisors and managers listed above will invite anyone else that is not included on the list but should be in attendance.

R. J. Martin

Mamager

Environmental Management

/Imk

ATTACHMENT IV CLOSURE PLAN

SPERRY CORPORATION
2751 SHEPARD ROAD
ST. PAUL, MINNESOTA 55164
MND 000 823 922



ECP			REV
	37013		G
PAGE	<del> </del>		
	1	OF	9

DETAIL DESCRIPTION Hazardous Waste Closure of Storage and Treatment Facilities Disk #L-ac-2

40 CFR Part 264

ENGINEER & " Mad lone de D. E. MacDonald

1/3/56

Soger Mark

1/3/86

#### 1.0 Purpose

The purpose of this procedure is to establish the method for closure of the hazardous waste storage and treatment facilities at the Sperry location which were permitted by the State or federal government as such. This procedure also includes an appendix showing the financial requirements for closure of each of the facilities.

#### 2.0 Scope

At such time that the various Sperry hazardous waste storage or treatment facilities would be no longer used, they must be closed in such a manner to minimize the need for further maintenance and would control, minimize or eliminate to the extent necessary to protect human health and the environment escape of hazardous waste after the facility is closed.

3.0 Closure Plan

NOTE: See appendix A.

4.0 Notice of Closure

At such time as one or all of the waste storage or pretreatement facilities is planned to be closed, a plan must be submitted to the Administrator of Region V EPA 180 days preceding the closure.

- 5.0 Time for Closure
  - 5.1 Within 90 days from receiving the last volume of hazardous waste, all of the waste will be treated as required and remove from the site by the hazardous waste hauler.
  - 5.2 Complete closure will be accomplished within 180 days of receiving the final volume of hazardous waste.
- 6.0 Schedule for Final Closure

NOTE: See appendix B.

7.0 Certification of Closure

When closure is completed, the General Manager of the facility must submit to the Region V EPA Administrator certification by Sperry and by an independent registered professional engineer that the facility has been closed in accordance with the specification in the approved closure plan.



ECP			REV
	37013		G
PAGE			
	2	OF	9

ENVIRONMENTAL CONTROL PROCEDURE							
DETAIL DESCRIPTION Hazardous Waste and Treatment Facilities	REF	40 CFR Part 2	64				
ENGINEER D. E. MacDonald	DATE	APPROVAL			DATE		

#### 8.0 Financial Requirements

- 8.1 A cost estimate of the closure of each facility is shown in Appendix
- 8.2 Review the cost estimate in Appendix C on an annual basis and update the estimate according to the formula in 40 CFR Part 264, Subpart G, 264.142.

Revision E



ECP	7 = 0	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	REV
	37013		G
PAGE			
	3	UE	9

ENVIRONMENTAL CON	ITROL F	ROCEDUF	RE				
DETAIL DESCRIPTION Hazardous Wast and Treatment Facilities	e Closure	of Storage	REF	40	CFR	Part	264
ENGINEER D. E. MacDonald	DATE	APPROVAL					DATE

#### APPENDIX A

#### Closure Plan

- 1.0 Steps necessary to close a hazardous material storage area.
  - 1.1 Management of containers, Note: Clearwater, Midway, Shepard Road, and Sperry Park facilities.
    - 1.1.1 Insure that all hazardous waste is in the appropriate containers as described in CFR 49 or the Sperry Hazardous Material Data System and are stored in the appropriate areas according to Sperry Procedures.
    - 1.1.2 Pump any waste from the spill sumps into the appropriate containers. Any remaining residue must also be removed and put into the appropriate containers.
    - 1.1.3 Decontaminate floors, walls, and equipment used for clean up. Place the residue in an appropriate DOT container for disposal.
    - 1.1.4 Apply all necessary labeling, certifications, manifests, etc., as required by Sperry Procedures and government regulations in preparation for shipping the containers to the approved disposal or reclamation site.
    - 1.1.5 Notify the current vendor under contract for disposal or reclamation of the hazardous waste to make the final pick up and ship them according to established procedures.
    - 1.2 Tanks used for treatment or storage of hazardous waste; Note: Shepard Road and Sperry Park facilities.
      - 1.2.1 Treat all hazardous waste stored in tanks by the appropriate method as described in the Sperry Environmental Control Procedures.
      - 1.2.2 Rinse out the tanks thoroughly to remove any residual waste. This waste must also be treated by the appropriate method.
      - 1.2.3 Inspect the interior of the tanks visually to insure complete removal of waste.
      - 1.2.4 Inspect the dikes for hazardous waste residue. If any exists rinse it and pump it into the reaction tank.



ECP .			REV
	37013		G
PAGE			
	4	OF	9

DETAIL DESCRIPTION Hazardous Waste Closure of Storage REF 40 CFR Part 264 and Treatment Facilities

ENGINEER DATE APPROVAL DATE

- 1.2.5 When all of the waste from the storage tanks and diked area have been treated, pump out the remaining treated waste from the reaction tank into the clarifier. Remaining sludge can be placed in an appropriate drum for disposal per paragraph 1.1 of this procedure.
- 1.2.6 Drain the clarifiers through the sludge dewatering filter or centrifuge. Dispose of the sludge per paragraph 1.1. The decanted liquid may be disposed of in the sanitary sewer if it is within the pretreatment standards established at the time of closure. Sample and analyze the effluent to insure compliance.
- 1.2.7 Thoroughly rinse the clarifier and dewatering devices. Collect the residue in drums and dispose of them per paragraph 1.1.
- 2.0 Maximum estimated inventory of waste.

#### 2.1 Storage

#### 2.1.1 Clearwater

A total of 50 drums, each holding 55 gallons of hazardous waste would be the maximum amount in storage at any one time.

#### 2.1.2 Midway

A total of 15 drums, each holding 55 gallons of hazardous waste would be the maximum amount in storage at any one time.

#### 2.1.3 Shepard Road

- A total of 244 drums, each holding 55 gallons of hazardous waste would be the maximum amount of drums in storage at any time.
- A maximum of 25 cubic yards (5000 gallons) of hazardous waste solids can be stored in bulk containers.
- A total of 5,000 gallons of corrosive hazardous waste and 11,000 gallons of ignitable waste can be stored in bulk tanks.
- The treatment system contains a total of 12 tanks, containing from 1,000 - 3,000 gallons.

Revision E



ECP			REV	· Company
	3701	3	G	
PAGE				
	5	OF	9	

DETAIL DESCRIPTION Hazardous Waste Closure of Storage REF 40 CFR Part 264 and Treatment Facilities

ENGINEER DATE APPROVAL DATE

#### 2.1.4 Sperry Park

- A total of 15 drums, each holding 55 gallons of hazardous waste would be the maximum amount of drums in storage at any time.
- A treatment system contains 12 tanks, containing a maximum of 47,000 gallons of waste effluent.

#### 3.0 Final closure schedule.

No storage or treatment facility is planned to be closed at this time.

If a closure were to take place the time schedule is shown in Appendix B, page 404A.



ECP			REV	
_	370	13	G	
PAGE	· · · · · · · · · · · · · · · · · · ·	eric		
	6	OF	9	

DETAIL DESCRIPTION Hazardous Waste Closure of Storage REF 40 CFR Part 264

ENGINEER DATE APPROVAL DATE

APPENDIX B

Schedule for Final Closure

#### NOTES:

- Expected year of closure or partial closure of any of the facilities, is unknown at this time. When it occurs this schedule will apply.
- 2. This schedule includes closure for each of the following facilities: Shepard Road, Sperry Park, Midway and Clearwater.

All hazardous waste placed in correct DOT containers

Clean spill sumps, place material in correct containers

Decontaminate floors, walls and equipment

Apply necessary labels, complete manifests

Notify disposal firm and ship waste to appropriate site

Certification of closure

NOTE: For Shepard Road and Sperry Park the following additional requirements are needed.


Treat all waste remaining in

Remove sludge from clarifier, clean and rinse clarifier

Clean filter press

tanks and dikes

Complete manifest, notify waste vendor and ship sludge



Revision E Page 404A

# non-responsive

# non-responsive

# non-responsive

#### EMERGENCY MOCK SPILL TRAINING

LOCATION: Sperry Park, Plant #8

SCENE OF SPILL: Dock

TIME: 9:00 A.M.

DAY: Monday

DESCRIPTION OF SPILL:

Move Crew was unloading chemical truck, when a pallet broke, and a box containing Ammonium Hydroxide with four one gallon containers broke on the floor. Move Crew notified:

#### 1. NOTIFICATION:

- A. Dial 3000 and give the following information:
  - 1. Name of person calling
  - 2. Location of emergency
  - 3. Nature of emergency

#### 2. COORDINATION:

A. Hazardous Emergency Coordinator, Occupational Health, and Security arrives at the scene of the spill.

#### 3. RECOGNITION AND EVALUATION:

- A. Hazardous Emergency Coordinator gets all the information he can from the Move Crew individual that reported the spill.
- B. He now knows it's Ammonium Hydroxide, and that only Ammonium Hydroxide is involved.
- C. No one has been harmed in anyway.
- D. The area involved has no other chemicals that would react to the spill.

- E. The spill has been contained to the immediate dock area.
- F. Breathing apparatus and protective clothes is necessary for cleanup.
- G. Vacuum cleaner will do the job to clean it up off the floor.

#### 4. CONTROL:

- A. The Hazardous Emergency Coordinator has Security block out all unauthorized personnel.
- B. Calls the Environmental technician to the spill, and has him suit up with protective clothes and a back-pak breathing apparatus.
- Have technician use vacuum cleaner from Environmental

  Management area to get the Ammonium Hydroxide off the floor,

  and also to pick up broken glass and contaiminated cardboard

  box.
- B.2 Use the advice of Occupational Health, during the process of cleanup, that might be helpful.

#### EMERGENCY MOCK SPILL TRAINING

3 aug 83

LOCATION: Shepard Road, Plant 1

SCENE OF SPILL: Chemical Dock

TIME: 11:30 A.M.

DAY: Monday

DESCRIPTION OF SPILL:

Sodium Bisulfite bulk truck was delivering 900 gallons, when in the process of unloading, a camlock fitting on the hose broke, and the shutoff valve failed to close on the truck. Sodium Bisulfite was flowing in such great quanitity from the leak that it was about to run over the berm. Steps to be taken:

- 1. Notification -
  - A. Dial 3000 and give the following information:
    - 1. Name of person calling
    - 2. Location of emergency
    - 3. Nature of emergency
- 2. Action To Be Taken -
  - A. Divert valve in pit so that Sodium Bisulfite flows into standby tank. Also assess the quality of the air in the area to determine if evacuation of the Plating area is necessary. If so, guards will be responsible for this, through the supervision of the Hazardous Emergency Coordinator and Occupational Health personnel.
- 3. Coordination (Recognition and Evaluation)
  - A. Hazardous Emergency Coordinator arrives.
  - B. Security arrives.

- C. Another Environmental technician arrives.
- D. Environmental technician communicates everything he knows of the situation to the Emergency Coordinator.
- D.l Technician reports Sodium Bisulfite is being diverted to standby tank.
- D.2 That flow can't be stopped at truck tank leak.
- D.3 Reports quality of air from Sodium Bisulfite entering standby equalization tank in Waste Treatment Pit.
- D.4 That the truck driver is safe and clear of danger.
- 4. Actions Taken By Hazardous Emergency Coordinator (CONTROL)
  - A. Directs technician that is suited up with back-pak and protective clothing to start sand bagging at berm to hold Sodium Bisulfite from entering storm sewer.
  - B. Tells other technician to suit up and wear breathing apparatus with five minute egress unit that hooks up to two three hundred pound portable cylinders.
  - C. As soon as the second technician is suited up, he'll go in and relieve the other technician so that he can change from back-pak to a longer air supply egress unit.
  - D. Direct Occupational Health to check on quality of air in pit and surrounding area, and for any safety input on spill.
  - E. Directs Security to keep all people clear of spill and uses them as a communications link.
  - F. Monitors air supply to technicians and the concern of their safety.
  - 5. After all danger has passed and everything is under control, the Emergency Coordinator will direct the final clean-up.

#### EMERGENCY MOCK SPILL TRAINING

Location:

Sperry Park, Plant #8

Scene Of Spill: Dock

Time:

9:00 A.M.

Day:

Wednesday

#### DESCRIPTION OF SPILL

Bulk truckload of caustic was being delivered. A large leak developed at the pump of the truck. The driver was unable to stop the leak. Environmental technician that was supervising the unloading took the following steps:

#### 1. Notification

- A. Dial 3000 and give the following information -
  - 1. Name of person calling
  - 2. Location of emergency
  - 3. Nature of emergency

#### 2. Action To Be Taken

- A. Diking can be started by the technician before Emergency Spill Coordinator arrives to prevent a flow to any storm or sanitary drains.
- Coordination (Recognition and Evaluation)
  - A. Hazardous Emergency Coordinator arrives.
  - B. Security arrives.
  - C. An additional technician arrives.
  - D. Occupational Health arrives.
  - E. Environmental technician reports everything he knows of the situation to the Hazardous Emergency Coordinator.
    - E-l That the truck driver is safe and clear of danger
    - E-2 There is no possible way of stopping the leak on the truck
    - E-3 That approximately 450 gallons has been unloaded and there was a total of 4,500 gallons on the truck to start with.
- 4. Action Taken By Hazardous Emergency Coordinator (Control)
  - A. Have technicians continue their diking.
  - B. Have Security clear all unauthorized personel and clear out all vehicles that might @bstruct control and cleanup.
  - C. Contact outside chemical cleanup contractor.

## BREATHING APPERATUS TRAINING

. Š.		00-0	r									
	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec
								DIS Kan				
R. Martin		##										
D. MacDonald												
R. Oines								8-2 RAO	, ž			
M. Wilson		`					···	8-3 mu				
Wm. Polta								8-3 P			]	
R. Ranzau			arg/Milder-park-series		error and a second			FOR				
G. Grinols												
M. Medina						Co-9 MAI		4-3 MA				
M. Kappes												
C Kitzrow												
				-								
					*	0x==1-40+40+404						
					عقير والمستان بعدران							

## SPILL RESPONSE TRAINING

<b>€</b>	(									doi:		
•	Jan	Feb	Mar	Apr	мау	June	July	Aug	Sept	Oct	Nov	Dec
R. Martin						Wi	RM	EW				
D. MacDonald						DM	Da	Dr				
R. Oines						RAO	RAO	RAO	4			
M. Wilson						1	1	mw				
Wm. Polta						BP	BP	BF				
R. Ranzau						RR	RR	BB_				
G. Grinols							<u> </u>	,,				
M. Medina						WN	MM	MW				
M. Kappes	·			<b>-</b>								
I Kitzrow		·										
												-
· .												
				}								
44000, market and the desire of the second s												
			,									
•		1.		and the state of t	dan Armana (p. 14) film		F	ļ				
					Î					-		}

## CLOSURE PLAN, POST-CLOSURE PLAN, AND FINANCIAL REQUIREMENTS

Sperry has a procedure for the requirements of 40 CFR 122.25(a)(13), 264.112-115, 264.178, 264.197, 264.258 and 270.14(a)(13). The procedure is shown in Appendix I-1, Sperry, ECP 37013 (Page 413). This procedure covers the method of closure and the cost. A post-closure plan is not required because this is not a disposal facility and all waste will be removed in the event of a closure. The entire facility will remain unclosed for the facility life.

Copies of the Closure Plan are retained by the Environmental Management

Department Manager and by the Environmental Management Supervisors at the Sperry Park and Shepard Road facilities. The Environmental Management Department

Manager has the responsibility for updating the Closure Procedure and for updating all copies of the procedure. The Closure Equipment Decontamination

Procedures are listed in ECP 37013 starting on Page 416. A statement of Sperry's Financial Test is included in Appendix I-2 (Page 419).

## APPENDIX I-1

HAZARDOUS WASTE CLOSURE OF STORAGE AND TREATMENT FACILITIES



ECP		,	REV	
	370	13	ן ו	र
PAGE				
	1	OF		8

### ENVIRONMENTAL CONTROL PROCEDURE

DETAIL DESCRIPTION Hazardous Waste Closure of Storage and Treatment Facilities Disk #L-ac-2

40 CFR Part 264

D. E. MacDonald

11/14/84 APPROVAL

11/19/84

1.0 Purpose

-

The purpose of this procedure is to establish the method for closure of the hazardous waste storage and treatment facilities at the Sperry location which were permitted by the State or federal government as such. This procedure also includes an appendix showing the financial requirements for closure of each of the facilities.

#### 2.0 Scope

At such time that the various Sperry hazardous waste storage or treatment facilities would be no longer used, they must be closed in such a manner to minimize the need for further maintenance and would control, minimize or eliminate to the extent necessary to protect human health and the environment escape of hazardous waste after the facility is closed.

#### 3.0 Closure Plan

NOTE: See appendix A.

#### 4.0 Notice of Closure

At such time as one or all of the waste storage or pretreatement facilities is planned to be closed, a plan must be submitted to the Administrator of Region V EPA 180 days preceding the closure.

#### 5.0 Time for Closure

- 5.1 Within 90 days from receiving the last volume of hazardous waste, all of the waste will be treated as required and remove from the site by the hazardous waste hauler.
- 5.2 Complete closure will be accomplished within 180 days of receiving the final volume of hazardous waste.

#### 6.0 Schedule for Final Closure

NOTE: See appendix B.

#### 7.0 Certification of Closure

When closure is completed, the General Manager of the facility must submit to the Region V EPA Administrator certification by Sperry and by an independent registered professional engineer that the facility has been closed in accordance with the specification in the approved closure plan.



ECP			REV	į
	370	13	F	i
PAGE				
	2	OF	8	

DETAIL DESCRIPTION Hazardous Wa and Treatment Facilities	ste Closure	of Storage	HEF 40 CFR Pa	ert 264
ENGINEER D. E. MacDonald	DATE	APPROVAL	2 5 2	DATE

8.0 Financial Requirements

8.1 A cost estimate of the closure of each facility is shown in Appendix C.

8.2 Review the cost estimate in Appendix C on an annual basis and update the estimate according to the formula in 40 CFR Part 264, Subpart G, 264.142.

Rev. D 3/13/85

Page 415



ECP			REV
	370	13	F
PAGE		·	<u> </u>
	3	ΩE	8

ENVIRONNENTAL	CONTROL	PROCEDURE
F=0 4 4 10 1 6 1 4 16 16 16 16 16 16 16 16 16 16 16 16 16	Ø2. Ø3. R. Ø. B. B. Ø2. €2.	8 17 5 Arrest promote produce a great of a great of

DETAIL DESCRIPTION Hazardous Waste and Treatment Facilities			E F	R Part 264
engineer D. E. MacDonald	DATE	APPROVAL		DATE

APPENDIX A

Closure Plan

4

- 1.0 Steps necessary to close a hazardous material storage area.
  - 1.1 Management of containers, Note: Clearwater, Midway, Shepard Road, and Sperry Park facilities.
    - 1.1.1 Insure that all hazardous waste is in the appropriate containers as described in CFR 49 or the Sperry Hazardous Material Data System and are stored in the appropriate areas according to Sperry Procedures.
    - 1.1.2 Pump any waste from the spill sumps into the appropriate containers. Any remaining residue must also be removed and put into the appropriate containers.
    - 1.1.3 Decontaminate floors, walls, and equipment used for clean up.

      Place the residue in an appropriate DOT container for disposal.
    - 1.1.4 Apply all necessary labeling, certifications, manifests, etc., as required by Sperry Procedures and government regulations in preparation for shipping the containers to the approved disposal or reclamation site.
    - 1.1.5 Notify the current vendor under contract for disposal or reclamation of the hazardous waste to make the final pick up and ship them according to established procedures.
  - 1.2 Tanks used for treatment or storage of hazardous waste; Note: Shepard Road and Sperry Park facilities.
    - 1.2.1 Treat all hazardous waste stored in tanks by the appropriate method as described in the Sperry Environmental Control Procedures.
    - 1.2.2 Rinse out the tanks thoroughly to remove any residual waste. This waste must also be treated by the appropriate method.
    - 1.2.3 Inspect the interior of the tanks visually to insure complete removal of waste.
    - 1.2.4 Inspect the dikes for hazardous waste residue. If any exists rinse it and pump it into the reaction tank.

Rev. D 3/13/85



-

ECP			REV	
	3701	.3	F	
PAGE				
	1,	OF	R	

## ENVIRONMENTAL CONTROL PROCEDURE

DETAIL DESCRIPTION Hazardous Waste Closure of Storage and Treatment Facilities

ENGINEER

DATE

APPROVAL

DATE

- 1.2.5 When all of the waste from the storage tanks and diked area have been treated, pump out the remaining treated waste from the reaction tank into the clarifier. Remaining sludge can be placed in an appropriate drum for disposal per paragraph 1.1 of this procedure.
- 1.2.6 Drain the clarifiers through the sludge dewatering filter or centrifuge. Dispose of the sludge per paragraph 1.1. The decanted liquid may be disposed of in the sanitary sewer if it is within the pretreatment standards established at the time of closure. Sample and analyze the effluent to insure compliance.
- 1.2.7 Thoroughly rinse the clarifier and dewatering devices. Collect the residue in drums and dispose of them per paragraph 1.1.
- 2.0 Maximum estimated inventory of waste.

#### 2.1 Storage

#### 2.1.1 Clearwater

A total of 50 drums, each holding 55 gallons of hazardous waste would be the maximum amount in storage at any one time.

#### 2.1.2 Midway

A total of 15 drums, each holding 55 gallons of hazardous waste would be the maximum amount in storage at any one time.

#### 2.1.3 Shepard Road

- A total of 244 drums, each holding 55 gallons of hazardous waste would be the maximum amount of drums in storage at any time.
- 2. A maximum of 25 cubic yards (5000 gallons) of hazardous waste solids can be stored in bulk containers.
- 3. A total of 5,000 gallons of hazardous waste can be stored in a bulk tank.
- 4. The treatment system contains a total of 12 tanks, containing from 1,000 3,000 gallons.

#### 2.1.4 Sperry Park

A total of 15 drums, each holding 55 gallons of hazardous waste would be the maximum amount of drums in storage at any time.



ECP	,		REV		
	370	13		F	
PAGE					
	5	OF		8	

ENVIRONNIENTA	L CONTROL	PROCEDURE

DETAIL DESCRIPTION Hazardous Waste and Treatment Facilities	Closure o	of Storage	PEF 40 CF	R Part 264
D. E. MacDonald	DATE	APPROVAL	-	DATE

 A treatment system contains 12 tanks, containing a maximum of 47,000 gallons of waste effluent.

3.0 Final closure schedule.

No storage or treatment facility is planned to be closed at this time.

If a closure were to take place the time schedule is shown in Appendix B, page 404A.

Rev. D 3/13/85

Page 418



ECP	/		REV	
	370	13	F	
PAGE				
	6	OF	8	

## ENVIRONMENTAL CONTROL PROCEDURE

DETAIL DESCRIPTION Hazardous Waste Closure of Storage REF
and Treatment Facilities

ENGINEER
D. E. MacDonald

DATE APPROVAL

DATE

APPENDIX B

Schedule for Final Closure

#### NOTES:

\*

- 1. Expected year of closure or partial closure of any of the facilities, is unknown at this time. When it occurs this schedule will apply.
- 2. This schedule includes closure for each of the following facilities: Shepard Road, Sperry Park, Midway and Clearwater.

All hazardous waste placed in correct DOT containers

Clean spill sumps, place material in correct containers

Decontaminate floors, walls and equipment

Apply necessary labels, complete manifests

Notify disposal firm and ship waste to appropriate site

Certification of closure

NOTE: For Shepard Road and Sperry Park the following additional requirements are needed.


Treat all waste remaining in tanks and dikes

Remove sludge from clarifier, clean and rinse clarifier

Clean filter press

113 14 14

Complete manifest, notify waste vendor and ship sludge



# non-responsive

## non-responsive

APPENDIX I-2 FINANCIAL TEST

Financial Asserve

OMIN 30 100 HILLS

kobert F. Jondreau Blue Bell

1641 310 K. M. Hoffman AUG 1 6 1924

[J4][ July 6, 1984

Substit Financial Assurance for Liability Closure and Post-Closure Care of Hazardous Waste Treatment, Storage or Disposal Facilities.

Enclosed for your information is a copy of the Financial Assurance rackage that was mailed on June 26, 1984 to Era kegions IV, V and 1% and the Tennessee Department of Public Health.

Please let me know if you have any questions.

enu/encls:

TO: Roger Mortini FROM: Will Paul

#### COPY OF THE SPERRY FINANCIAL ASSURANCE LETTER

This letter demonstrates Sperry's financial responsibility for liability coverage and closure and/or post-closure care as specified in Subpart H of CFR Parts 264 and 265. The letter was written by Vincent R. McLean, Executive Vice President and Chief Financial Officer, dated 14 June 1984. Sperry is required to submit this information annually.

THE HAVE COME THAT ION TOWN AS FREE CASE FOR THE ART FRECASE FOR TOWN AND TOWN AND THE CONTRACT OF THE CONTRAC

VIIICE LITE MCLEAN E OF CHINE VILLE FROM LAND CHILE FROM LAND CHILE

#### Dear Sir:

I am the chief financial officer of Sperry Corporation, 1290 Avenue of the Americas, New York, N.Y. 10104. This letter is in support of the use of the financial test to demonstrate financial responsibility for liability coverage and closure and/or post-closure care as specified in Subpart H of 40 CFR Parts 264 and 265.

The owner or operator identified above is the owner or operator f the following facilities for which liability coverage is being emonstrated through the financial test specified in Subpart H of 40 CFR Parts 264 and 265:

Business Unit		
Sperry Corp.	EPA ID No.	Address
Flight Systems	AZD009004961	21111 N. 19th St. Phoenix, AZ 85027
Computer Systems	TND003382801	Sperry Road Bristol, TN 37620
Computer Systems	MND000823922	2751 Shepard Road St. Paul, MN
Computer Systems	MND000823914	3333 Pilot Knob Road Eagan, MN 55116
Computer Systems	FLD004097184	Route 584 Oldsmar, FL 33551
Computer Systems	MND079731519	2276 Highcrest Road Roseville, MN 55113

The owner or operator identified above owns or operates the following acilities for which financial assurance for closure or post-closure care is demonstrated through the financial test specified in Subpart H of 40 CFR Parts 264 and 265. The current closure and/or post-closure cost estimates covered by the test are shown for each facility:

Ausiness Unit of Sperry Corp.	LPA ID No.	Address (	TSD Category	Closure Cost Est.
Flight Sys.	A2D009004961	21111 N.19th St. Phoenix, AZ 85027	S	\$ 53,776
Computer Sys.	TRD003382801	Sperry Road Bristol, TN	T.S.	71,030
Computer Sys.	MND000823922	2751 Shepard Rd. St.Paul, MN 55116	T.S.	23,365
Computer Sys.	MND000823914	3333 Pilot Knob Rd. Eagan, MN 55116	. T.S.	3,795
Computer Sys.	FLD004097184	Route 584 Oldsmar, FL 33557	S	6,820
Computer Sys.	MND079731519	2276 Highcrest Rd. Roseville,MN 55113	G.S.T.	15,180

In States where EPA is not administering the financial requirements of Subpart H of 40 CFR Parts 264 and 265, this owner or operator is demonstrating financial assurance for the closure or post-closure care of the following facilities through the use of a test equivalent or substantially equivalent to the financial test specified in Subpart H of 40 CFR Parts 264 and 265. The current closure and/or post-closure cost estimates covered by such a test are shown for each facility:

NONE.

The owner or operator identified above owns or operates the following hazardous waste management facilities for which financial assurance for closure or, if a disposal facility, post-closure care, is not demonstrated either to EPA or a State through the financial test or any other financial assurance mechanism specified in Subpart H of 40 CFR Parts 264 and 265 or equivalent or substantially equivalent State mechanisms. The current closure and/or post-closure cost estimates not covered by such financial assurance are shown for each facility:

NONE.

This owner or operator is required to file a Form 10K with the Securities and Exchange Commission (SEC) for the latest fiscal year.

The fiscal year of this owner or operator ends on March 31. The figures for the following items marked with an asterisk are derived from this owner's or operator's independently audited, year-end financial statements for the latest completed fiscal year ended March 31, 1984.

#### CLOSURE OR POST-CLOSURE CARE AND LIABILITY COVERAGE

The sum of net income plus depreciation,

depletion, and amortization

Total assets in U. S.

\*10.

ell.

Sum of current closure and post-1. closure cost estimates (total of 173,966 ALL cost estimates listed above) 2. Amount of annual aggregate liability coverage to be demonstrated 8,000,000 8,173,966 3. Sum of lines 1 and 2 **4**4. Total liabilities 2,699.7 Tangible net worth 2,778.8 **6**. 2,802.9 Ket worth \*7 Current assets 2,639.1 **8** • Current liabilities 1,556.1 1,083.0 \*9. Net working capital (line 7 minus line 8)

419.9

\$ 3,920.3

(Lines 4 through 11

in millions)

	•	1'es	110
12.	Is line 5 at least \$10 million?	X	
13.	Is line 5 at least 6 times line 3?	X	
14.	Is line 9 at least 6 times line 3?	COLOR PROPERTIES DE LA COLOR D	* —mmm
15.	Are at least 90% of assets located in the U.S.? If not, complete line 16.	#Entitle@seemakits	X
16.	Is line ll at least 6 times line 3?	<b>X</b>	
17.	Is line 4 divided by line 6 less than 2.0?	X	
18.	Is line 10 divided by line 4 greater than 0.1?	<u> </u>	onor-in-in-in-in-in-in-in-in-in-in-in-in-in-
19.	Is line 7 divided by line 8 greater than 1.5?	X	وبضوينيتسويشك

I hereby certify that the wording of this letter is identical to the wording specified in 40 CFR 264.151(g) as such regulations were constituted on the date shown immediately below.

Thurst R. M Leen

Vincent R. McLean Executive Vice President and Chief Financial Officer

June 14, 1984

COPY OF MEMO FROM ARTHUR YOUNG AND COMPANY

This auditor's report confirms that the contents of the Financial Assusrance

Letter complies with the Federal requirements.



## LATHUR YOUNG

277 Park Avenue New York, New York 10172 Telephone (212) 407-1500 Teleph 1H1-177704

June 15, 1984

The Board of Directors Sperry Corporation

We have read the letter dated June 14, 1984 from Vincent R.

McLean, chief financial officer of Sperry Corporation, submitted to the Regional Administrators of the Environmental Protection Agency in support of the use of the financial test, as specified in Subpart H of 40 CFR Parts 264 and 265, to demonstrate financial responsibility for liability coverage and closure and post-closure care of the Corporation's hazardous waste treatment, storage and disposal facilities at the locations listed in that letter.

connection with Subpart H of 40 CFR Parts 264 and 265, we have compared the independently audited consolidated financial statements of Sperry Corporation for the year ended March 31, 1984 to the specified data in that letter indicated as being derived from such independently audited consolidated financial statements. In connection with this comparison, no matters came to our attention that caused us to believe that the specified data should be adjusted.

This report is solely to assist you in complying with the reporting requirements associated with the financial test, as specified in Subpart H of 40 CFR Parts 264 and 265, to demonstrate financial responsibility for liability coverage and closure and post-closure care, and should not be referred to or used for any other purpose.

Athen young a Confung

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachement and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalities for submitting false information, including the possibility of fine and imprisonment.

Date:	Signature

E.T. Michaud, Director
Facilities Resources

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachment and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate and complete. I am aware that there are significant penalities for submitting false information, including the possibility of fine and imprisonment.

Date: July 2, 1984 Signature

P. F. Ives, Director

Resources Management

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachement and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalities for submitting false information, including the possibility of fine and imprisonment.

Date: 9/1/84

Signature

E.T. Michaud, Director

Facilities Resources

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachement and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalities for submitting false information, including the possibility of fine and imprisonment.

Date: 10/8/84

Signature

E.T. Michaud, Director

Facilities Resources

Revision:

#### CERTIFICATION

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachment and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalities for submitting false information, including the possibility of fine and imprisonment.

Date: 19 Dec 1984 Signature Kondlh

R. N. Arneberg, Director

Resources Management